

NAG Library Function Document

nag_dtfttp (f01vlc)

1 Purpose

nag_dtfttp (f01vlc) copies a real triangular matrix, stored in a Rectangular Full Packed (RFP) format array, to a standard packed format array.

2 Specification

```
#include <nag.h>
#include <nagf01.h>

void nag_dtfttp (Nag_OrderType order, Nag_RFP_Store transr,
                 Nag_UploType uplo, Integer n, const double ar[], double ap[],
                 NagError *fail)
```

3 Description

nag_dtfttp (f01vlc) packs a real n by n triangular matrix A , stored in RFP format, to packed format. This function is intended for possible use in conjunction with functions from Chapters f06, f07 and f16 where some functions that use triangular matrices store them in RFP format. The RFP storage format is described in Section 3.3.3 in the f07 Chapter Introduction and the packed storage format is described in Section 3.3.2 in the f07 Chapter Introduction.

4 References

Gustavson F G, Waśniewski J, Dongarra J J and Langou J (2010) Rectangular full packed format for Cholesky's algorithm: factorization, solution, and inversion *ACM Trans. Math. Software* **37**, 2

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **transr** – Nag_RFP_Store *Input*
On entry: specifies whether the normal RFP representation of A or its transpose is stored.
transr = Nag_RFP_Normal
The RFP representation of the matrix A is stored.
transr = Nag_RFP_Trans
The transpose of the RFP representation of the matrix A is stored.
Constraint: **transr** = Nag_RFP_Normal or Nag_RFP_Trans.
- 3: **uplo** – Nag_UploType *Input*
On entry: specifies whether A is upper or lower triangular.
uplo = Nag_Upper
 A is upper triangular.

uplo = Nag_Lower
A is lower triangular.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

4: **n** – Integer *Input*

On entry: *n*, the order of the matrix *A*.

Constraint: **n** ≥ 0.

5: **ar**[**n** × (**n** + 1)/2] – const double *Input*

On entry: the upper or lower *n* by *n* triangular matrix *A* (as specified by **uplo**) in either normal or transposed RFP format (as specified by **transr**). The storage format is described in Section 3.3.3 in the f07 Chapter Introduction.

6: **ap**[*dim*] – double *Output*

Note: the dimension, *dim*, of the array **ap** must be at least **n** × (**n** + 1)/2.

On exit: the *n* by *n* triangular matrix *A*, packed by rows or columns depending on **order**.

The storage of elements A_{ij} depends on the **order** and **uplo** arguments as follows:

if **order** = Nag_ColMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ap**[(*j* − 1) × *j*/2 + *i* − 1], for $i \leq j$;
 if **order** = Nag_ColMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ap**[(2*n* − *j*) × (*j* − 1)/2 + *i* − 1], for $i \geq j$;
 if **order** = Nag_RowMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ap**[(2*n* − *i*) × (*i* − 1)/2 + *j* − 1], for $i \leq j$;
 if **order** = Nag_RowMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ap**[(*i* − 1) × *i*/2 + *j* − 1], for $i \geq j$.

7: **fail** – NagError * *Input/Output*

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument *⟨value⟩* had an illegal value.

NE_INT

On entry, **n** = *⟨value⟩*.

Constraint: **n** ≥ 0.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.
See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

Not applicable.

8 Parallelism and Performance

nag_dtfttp (f01vlc) is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example reads in a triangular matrix in RFP format and copies it to packed format.

10.1 Program Text

```
/* nag_dtfttp (f01vlc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf01.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer exit_status = 0, indent = 0, ncols = 80;
    Integer i, j, k, lar1, lar2, lenap, lenar, n, pdar, q;
    /* Arrays */
    double *ap = 0, *ar = 0;
    char nag_enum_transr[40], nag_enum_uplo[40], form[] = "%5.2f";
    /* Nag Types */
    Nag_OrderType order;
    Nag_RFP_Store transr;
    Nag_UploType uplo;
    NagError fail;

#ifdef NAG_COLUMN_MAJOR
    order = Nag_ColMajor;
#define AR(I,J) ar[J*pdar + I]
#define KU(I,J) (I + J*(J+1)/2)
#define KL(I,J) (J*(n-1) - J*(J-1)/2 + I)
#else
    order = Nag_RowMajor;
#define AR(I,J) ar[I*pdar + J]
#define KL(I,J) (J + I*(I+1)/2)
#define KU(I,J) (I*(n-1) - I*(I-1)/2 + J)
#endif

    INIT_FAIL(fail);
```

```

    printf("nag_dtfttp (f01vlc) Example Program Results\n\n");
    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
    scanf_s("%" NAG_IFMT "%*[\n] ", &n);
    scanf_s("%39s ", nag_enum_transr, (unsigned)_countof(nag_enum_transr));
    scanf_s("%39s %*[\n] ", nag_enum_uplo,
            (unsigned)_countof(nag_enum_uplo));
#else
    scanf("%*[\n] ");
    scanf("%" NAG_IFMT "%*[\n] ", &n);
    scanf("%39s ", nag_enum_transr);
    scanf("%39s %*[\n] ", nag_enum_uplo);
#endif
    lenap = (n * (n + 1)) / 2;
    lenar = lenap;
    if (!(ap = NAG_ALLOC(lenap, double)) || !(ar = NAG_ALLOC(lenar, double)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }
    /* Nag_RFP_Store */
    transr = (Nag_RFP_Store) nag_enum_name_to_value(nag_enum_transr);
    uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_uplo);

    k = n / 2;
    q = n - k;
    if (transr == Nag_RFP_Normal) {
        lar1 = 2 * k + 1;
        lar2 = q;
    }
    else {
        lar1 = q;
        lar2 = 2 * k + 1;
    }
    if (order == Nag_RowMajor) {
        pdar = lar2;
    }
    else {
        pdar = lar1;
    }
    /* Read an RFP matrix into array AR. */
    for (i = 0; i < lar1; i++) {
#ifdef _WIN32
        for (j = 0; j < lar2; j++)
            scanf_s("%lf ", &AR(i, j));
#else
        for (j = 0; j < lar2; j++)
            scanf("%lf ", &AR(i, j));
#endif
    }

    /* Print the Rectangular Full Packed array
     * showing how the elements are arranged using
     * nag_gen_real_mat_print_comp (x04cbc).
     * Print real general matrix (comprehensive).
     */
    fflush(stdout);
    nag_gen_real_mat_print_comp(order, Nag_GeneralMatrix, Nag_NonUnitDiag, lar1,
                                lar2, ar, pdar, form,
                                "RFP Packed Array AR (graphical representation):",
                                Nag_IntegerLabels, NULL, Nag_IntegerLabels,
                                NULL, ncols, indent, NULL, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_gen_real_mat_print_comp (x04cbc).\n%s\n",
              fail.message);
        exit_status = 1;
    }
}

```

```

/* Convert real triangular matrix from Rectangular Full Packed to
 * packed vector form using nag_dtfttp (f01vlc).
 */
nag_dtfttp(order, transr, uplo, n, ar, ap, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_dtfttp (f01vlc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print the packed vector using macros KL or KU. */
printf("\n Packed Matrix AP (printed using KL/KU macros):\n\n");
for (i = 0; i < n; i++) {
    printf(" ");
    if (uplo == Nag_Upper) {
        for (j = 0; j < i; j++)
            printf("%6s", " ");
        for (j = i; j < n; j++)
            printf("%6.2f", ap[KU(i, j)]);
    }
    else {
        for (j = 0; j <= i; j++)
            printf("%6.2f", ap[KL(i, j)]);
    }
    printf("\n");
}

END:
    NAG_FREE(ap);
    NAG_FREE(ar);
    return exit_status;
}

```

10.2 Program Data

nag_dtfttp (f01vlc) Example Program Data

4	:	n
Nag_RFP_Normal Nag_Upper	:	transr, uplo
1.30 1.40		
2.30 2.40		
3.30 3.40		
1.10 4.40		
1.20 2.20	:	RFP array ar[]

10.3 Program Results

nag_dtfttp (f01vlc) Example Program Results

RFP Packed Array AR (graphical representation):

	1	2
1	1.30	1.40
2	2.30	2.40
3	3.30	3.40
4	1.10	4.40
5	1.20	2.20

Packed Matrix AP (printed using KL/KU macros):

1.10	1.20	1.30	1.40
	2.20	2.30	2.40
		3.30	3.40
			4.40
