

# NAG Library Function Document

## nag\_zgbsvx (f07bpc)

### 1 Purpose

nag\_zgbsvx (f07bpc) uses the *LU* factorization to compute the solution to a complex system of linear equations

$$AX = B, \quad A^T X = B \quad \text{or} \quad A^H X = B,$$

where  $A$  is an  $n$  by  $n$  band matrix with  $k_l$  subdiagonals and  $k_u$  superdiagonals, and  $X$  and  $B$  are  $n$  by  $r$  matrices. Error bounds on the solution and a condition estimate are also provided.

### 2 Specification

```
#include <nag.h>
#include <nagf07.h>

void nag_zgbsvx (Nag_OrderType order, Nag_FactoredFormType fact,
                 Nag_TransType trans, Integer n, Integer kl, Integer ku, Integer nrhs,
                 Complex ab[], Integer pdab, Complex afb[], Integer pdafb,
                 Integer ipiv[], Nag_EquilibrationType *eque, double r[], double c[],
                 Complex b[], Integer pdb, Complex x[], Integer pdx, double *rcond,
                 double ferr[], double berr[], double *recip_growth_factor,
                 NagError *fail)
```

### 3 Description

nag\_zgbsvx (f07bpc) performs the following steps:

#### 1. Equilibration

The linear system to be solved may be badly scaled. However, the system can be equilibrated as a first stage by setting **fact** = Nag\_EquilibrateAndFactor. In this case, real scaling factors are computed and these factors then determine whether the system is to be equilibrated. Equilibrated forms of the systems  $AX = B$ ,  $A^T X = B$  and  $A^H X = B$  are

$$(D_R A D_C)(D_C^{-1} X) = D_R B,$$

$$(D_R A D_C)^T (D_R^{-1} X) = D_C B,$$

and

$$(D_R A D_C)^H (D_R^{-1} X) = D_C B,$$

respectively, where  $D_R$  and  $D_C$  are diagonal matrices, with positive diagonal elements, formed from the computed scaling factors.

When equilibration is used,  $A$  will be overwritten by  $D_R A D_C$  and  $B$  will be overwritten by  $D_R B$  (or  $D_C B$  when the solution of  $A^T X = B$  or  $A^H X = B$  is sought).

#### 2. Factorization

The matrix  $A$ , or its scaled form, is copied and factored using the *LU* decomposition

$$A = PLU,$$

where  $P$  is a permutation matrix,  $L$  is a unit lower triangular matrix, and  $U$  is upper triangular.

This stage can be by-passed when a factored matrix (with scaled matrices and scaling factors) are supplied; for example, as provided by a previous call to nag\_zgbsvx (f07bpc) with the same matrix  $A$ .

### 3. Condition Number Estimation

The *LU* factorization of *A* determines whether a solution to the linear system exists. If some diagonal element of *U* is zero, then *U* is exactly singular, no solution exists and the function returns with a failure. Otherwise the factorized form of *A* is used to estimate the condition number of the matrix *A*. If the reciprocal of the condition number is less than *machine precision* then a warning code is returned on final exit.

### 4. Solution

The (equilibrated) system is solved for *X* ( $D_C^{-1}X$  or  $D_R^{-1}X$ ) using the factored form of *A* ( $D_R A D_C$ ).

### 5. Iterative Refinement

Iterative refinement is applied to improve the computed solution matrix and to calculate error bounds and backward error estimates for the computed solution.

### 6. Construct Solution Matrix *X*

If equilibration was used, the matrix *X* is premultiplied by  $D_C$  (if **trans** = Nag\_NoTrans) or  $D_R$  (if **trans** = Nag\_Trans or Nag\_ConjTrans) so that it solves the original system before equilibration.

## 4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

Higham N J (2002) *Accuracy and Stability of Numerical Algorithms* (2nd Edition) SIAM, Philadelphia

## 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag\_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

2: **fact** – Nag\_FactoredFormType *Input*

*On entry:* specifies whether or not the factorized form of the matrix *A* is supplied on entry, and if not, whether the matrix *A* should be equilibrated before it is factorized.

**fact** = Nag\_Factored

**afb** and **ipiv** contain the factorized form of *A*. If **equed**  $\neq$  Nag\_NoEquilibration, the matrix *A* has been equilibrated with scaling factors given by **r** and **c**. **ab**, **afb** and **ipiv** are not modified.

**fact** = Nag\_NotFactored

The matrix *A* will be copied to **afb** and factorized.

**fact** = Nag\_EquilibrateAndFactor

The matrix *A* will be equilibrated if necessary, then copied to **afb** and factorized.

*Constraint:* **fact** = Nag\_Factored, Nag\_NotFactored or Nag\_EquilibrateAndFactor.

- 3: **trans** – Nag\_TransType Input  
*On entry:* specifies the form of the system of equations.  
**trans** = Nag\_NoTrans  
 $AX = B$  (No transpose).  
**trans** = Nag\_Trans  
 $A^T X = B$  (Transpose).  
**trans** = Nag\_ConjTrans  
 $A^H X = B$  (Conjugate transpose).  
*Constraint:* **trans** = Nag\_NoTrans, Nag\_Trans or Nag\_ConjTrans.
- 4: **n** – Integer Input  
*On entry:*  $n$ , the number of linear equations, i.e., the order of the matrix  $A$ .  
*Constraint:* **n**  $\geq 0$ .
- 5: **kl** – Integer Input  
*On entry:*  $k_l$ , the number of subdiagonals within the band of the matrix  $A$ .  
*Constraint:* **kl**  $\geq 0$ .
- 6: **ku** – Integer Input  
*On entry:*  $k_u$ , the number of superdiagonals within the band of the matrix  $A$ .  
*Constraint:* **ku**  $\geq 0$ .
- 7: **nrhs** – Integer Input  
*On entry:*  $r$ , the number of right-hand sides, i.e., the number of columns of the matrix  $B$ .  
*Constraint:* **nrhs**  $\geq 0$ .
- 8: **ab**[*dim*] – Complex Input/Output  
**Note:** the dimension, *dim*, of the array **ab** must be at least  $\max(1, \mathbf{pdab} \times \mathbf{n})$ .  
*On entry:* the  $n$  by  $n$  coefficient matrix  $A$ .  
This is stored as a notional two-dimensional array with row elements or column elements stored contiguously. The storage of elements  $A_{ij}$ , for row  $i = 1, \dots, n$  and column  $j = \max(1, i - k_l), \dots, \min(n, i + k_u)$ , depends on the **order** argument as follows:  
if **order** = Nag\_ColMajor,  $A_{ij}$  is stored as **ab**[( $j - 1$ )  $\times$  **pdab** + **ku** +  $i - j$ ];  
if **order** = Nag\_RowMajor,  $A_{ij}$  is stored as **ab**[( $i - 1$ )  $\times$  **pdab** + **kl** +  $j - i$ ].  
See Section 9 for further details.  
If **fact** = Nag\_Factored and **equed**  $\neq$  Nag\_NoEquilibration,  $A$  must have been equilibrated by the scaling factors in **r** and/or **c**.  
*On exit:* if **fact** = Nag\_Factored or Nag\_NotFactored, or if **fact** = Nag\_EquilibrateAndFactor and **equed** = Nag\_NoEquilibration, **ab** is not modified.  
If **equed**  $\neq$  Nag\_NoEquilibration then, if no constraints are violated,  $A$  is scaled as follows:  
if **equed** = Nag\_RowEquilibration,  $A = D_r A$ ;  
if **equed** = Nag\_ColumnEquilibration,  $A = A D_c$ ;  
if **equed** = Nag\_RowAndColumnEquilibration,  $A = D_r A D_c$ .

- 9: **pdab** – Integer *Input*  
*On entry:* the stride separating row or column elements (depending on the value of **order**) of the matrix *A* in the array **ab**.  
*Constraint:*  $\text{pdab} \geq \text{kl} + \text{ku} + 1$ .
- 10: **afb**[*dim*] – Complex *Input/Output*  
**Note:** the dimension, *dim*, of the array **afb** must be at least  $\max(1, \text{pdafb} \times \mathbf{n})$ .  
*On entry:* if **fact** = Nag\_NotFactored or Nag\_EquilibrateAndFactor, **afb** need not be set.  
 If **fact** = Nag\_Factored, details of the *LU* factorization of the *n* by *n* band matrix *A*, as computed by nag\_zgbtrf (f07brc).  
 The elements,  $u_{ij}$ , of the upper triangular band factor *U* with  $k_l + k_u$  super-diagonals, and the multipliers,  $l_{ij}$ , used to form the lower triangular factor *L* are stored. The elements  $u_{ij}$ , for  $i = 1, \dots, n$  and  $j = i, \dots, \min(n, i + k_l + k_u)$ , and  $l_{ij}$ , for  $i = 1, \dots, n$  and  $j = \max(1, i - k_l), \dots, i$ , are stored where  $A_{ij}$  is stored on entry.  
 If **equed**  $\neq$  Nag\_NoEquilibration, **afb** is the factorized form of the equilibrated matrix *A*.  
*On exit:* if **fact** = Nag\_Factored, **afb** is unchanged from entry.  
 Otherwise, if no constraints are violated, then if **fact** = Nag\_NotFactored, **afb** returns details of the *LU* factorization of the band matrix *A*, and if **fact** = Nag\_EquilibrateAndFactor, **afb** returns details of the *LU* factorization of the equilibrated band matrix *A* (see the description of **ab** for the form of the equilibrated matrix).
- 11: **pdafb** – Integer *Input*  
*On entry:* the stride separating row or column elements (depending on the value of **order**) of the matrix *A* in the array **afb**.  
*Constraint:*  $\text{pdafb} \geq 2 \times \text{kl} + \text{ku} + 1$ .
- 12: **ipiv**[*dim*] – Integer *Input/Output*  
**Note:** the dimension, *dim*, of the array **ipiv** must be at least  $\max(1, \mathbf{n})$ .  
*On entry:* if **fact** = Nag\_NotFactored or Nag\_EquilibrateAndFactor, **ipiv** need not be set.  
 If **fact** = Nag\_Factored, **ipiv** contains the pivot indices from the factorization  $A = LU$ , as computed by nag\_dgbtrf (f07bdc); row *i* of the matrix was interchanged with row **ipiv**[*i* – 1].  
*On exit:* if **fact** = Nag\_Factored, **ipiv** is unchanged from entry.  
 Otherwise, if no constraints are violated, **ipiv** contains the pivot indices that define the permutation matrix *P*; at the *i*th step row *i* of the matrix was interchanged with row **ipiv**[*i* – 1]. **ipiv**[*i* – 1] = *i* indicates a row interchange was not required.  
 If **fact** = Nag\_NotFactored, the pivot indices are those corresponding to the factorization  $A = LU$  of the original matrix *A*.  
 If **fact** = Nag\_EquilibrateAndFactor, the pivot indices are those corresponding to the factorization of  $A = LU$  of the equilibrated matrix *A*.
- 13: **equed** – Nag\_EquilibrationType \* *Input/Output*  
*On entry:* if **fact** = Nag\_NotFactored or Nag\_EquilibrateAndFactor, **equed** need not be set.  
 If **fact** = Nag\_Factored, **equed** must specify the form of the equilibration that was performed as follows:  
     if **equed** = Nag\_NoEquilibration, no equilibration;  
     if **equed** = Nag\_RowEquilibration, row equilibration, i.e., *A* has been premultiplied by  $D_R$ ;

if **equed** = Nag\_ColumnEquilibration, column equilibration, i.e.,  $A$  has been postmultiplied by  $D_C$ ;

if **equed** = Nag\_RowAndColumnEquilibration, both row and column equilibration, i.e.,  $A$  has been replaced by  $D_R A D_C$ .

*On exit:* if **fact** = Nag\_Factored, **equed** is unchanged from entry.

Otherwise, if no constraints are violated, **equed** specifies the form of equilibration that was performed as specified above.

*Constraint:* if **fact** = Nag\_Factored, **equed** = Nag\_NoEquilibration, Nag\_RowEquilibration, Nag\_ColumnEquilibration or Nag\_RowAndColumnEquilibration.

14: **r**[*dim*] – double *Input/Output*

**Note:** the dimension, *dim*, of the array **r** must be at least  $\max(1, \mathbf{n})$ .

*On entry:* if **fact** = Nag\_NotFactored or Nag\_EquilibrateAndFactor, **r** need not be set.

If **fact** = Nag\_Factored and **equed** = Nag\_RowEquilibration or Nag\_RowAndColumnEquilibration, **r** must contain the row scale factors for  $A$ ,  $D_R$ ; each element of **r** must be positive.

*On exit:* if **fact** = Nag\_Factored, **r** is unchanged from entry.

Otherwise, if no constraints are violated and **equed** = Nag\_RowEquilibration or Nag\_RowAndColumnEquilibration, **r** contains the row scale factors for  $A$ ,  $D_R$ , such that  $A$  is multiplied on the left by  $D_R$ ; each element of **r** is positive.

15: **c**[*dim*] – double *Input/Output*

**Note:** the dimension, *dim*, of the array **c** must be at least  $\max(1, \mathbf{n})$ .

*On entry:* if **fact** = Nag\_NotFactored or Nag\_EquilibrateAndFactor, **c** need not be set.

If **fact** = Nag\_Factored or **equed** = Nag\_ColumnEquilibration or Nag\_RowAndColumnEquilibration, **c** must contain the column scale factors for  $A$ ,  $D_C$ ; each element of **c** must be positive.

*On exit:* if **fact** = Nag\_Factored, **c** is unchanged from entry.

Otherwise, if no constraints are violated and **equed** = Nag\_ColumnEquilibration or Nag\_RowAndColumnEquilibration, **c** contains the row scale factors for  $A$ ,  $D_C$ ; each element of **c** is positive.

16: **b**[*dim*] – Complex *Input/Output*

**Note:** the dimension, *dim*, of the array **b** must be at least

$\max(1, \mathbf{pdb} \times \mathbf{nrhs})$  when **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{n} \times \mathbf{pdb})$  when **order** = Nag\_RowMajor.

The (*i*, *j*)th element of the matrix  $B$  is stored in

**b**[(*j* – 1) × **pdb** + *i* – 1] when **order** = Nag\_ColMajor;  
**b**[(*i* – 1) × **pdb** + *j* – 1] when **order** = Nag\_RowMajor.

*On entry:* the  $n$  by  $r$  right-hand side matrix  $B$ .

*On exit:* if **equed** = Nag\_NoEquilibration, **b** is not modified.

If **trans** = Nag\_NoTrans and **equed** = Nag\_RowEquilibration or Nag\_RowAndColumnEquilibration, **b** is overwritten by  $D_R B$ .

If **trans** = Nag\_Trans or Nag\_ConjTrans and **equed** = Nag\_ColumnEquilibration or Nag\_RowAndColumnEquilibration, **b** is overwritten by  $D_C B$ .

- 17: **pdb** – Integer *Input*
- On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **b**.
- Constraints:*
- if **order** = Nag\_ColMajor, **pdb**  $\geq \max(1, \mathbf{n})$ ;  
 if **order** = Nag\_RowMajor, **pdb**  $\geq \max(1, \mathbf{nrhs})$ .
- 18: **x[dim]** – Complex *Output*
- Note:** the dimension, *dim*, of the array **x** must be at least
- $\max(1, \mathbf{pdx} \times \mathbf{nrhs})$  when **order** = Nag\_ColMajor;  
 $\max(1, \mathbf{n} \times \mathbf{pdx})$  when **order** = Nag\_RowMajor.
- The (*i*, *j*)th element of the matrix *X* is stored in
- x**[(*j* – 1)  $\times$  **pdx** + *i* – 1] when **order** = Nag\_ColMajor;  
**x**[(*i* – 1)  $\times$  **pdx** + *j* – 1] when **order** = Nag\_RowMajor.
- On exit:* if **fail.code** = NE\_NOERROR or NE\_SINGULAR\_WP, the *n* by *r* solution matrix *X* to the original system of equations. Note that the arrays *A* and *B* are modified on exit if **equed**  $\neq$  Nag\_NoEquilibration, and the solution to the equilibrated system is  $D_C^{-1}X$  if **trans** = Nag\_NoTrans and **equed** = Nag\_ColumnEquilibration or Nag\_RowAndColumnEquilibration, or  $D_R^{-1}X$  if **trans** = Nag\_Trans or Nag\_ConjTrans and **equed** = Nag\_RowEquilibration or Nag\_RowAndColumnEquilibration.
- 19: **pdx** – Integer *Input*
- On entry:* the stride separating row or column elements (depending on the value of **order**) in the array **x**.
- Constraints:*
- if **order** = Nag\_ColMajor, **pdx**  $\geq \max(1, \mathbf{n})$ ;  
 if **order** = Nag\_RowMajor, **pdx**  $\geq \max(1, \mathbf{nrhs})$ .
- 20: **rcond** – double \* *Output*
- On exit:* if no constraints are violated, an estimate of the reciprocal condition number of the matrix *A* (after equilibration if that is performed), computed as  $\mathbf{rcond} = 1.0 / (\|A\|_1 \|A^{-1}\|_1)$ .
- 21: **ferr[nrhs]** – double *Output*
- On exit:* if **fail.code** = NE\_NOERROR or NE\_SINGULAR\_WP, an estimate of the forward error bound for each computed solution vector, such that  $\|\hat{x}_j - x_j\|_\infty / \|x_j\|_\infty \leq \mathbf{ferr}[j - 1]$  where  $\hat{x}_j$  is the *j*th column of the computed solution returned in the array **x** and  $x_j$  is the corresponding column of the exact solution *X*. The estimate is as reliable as the estimate for **rcond**, and is almost always a slight overestimate of the true error.
- 22: **berr[nrhs]** – double *Output*
- On exit:* if **fail.code** = NE\_NOERROR or NE\_SINGULAR\_WP, an estimate of the component-wise relative backward error of each computed solution vector  $\hat{x}_j$  (i.e., the smallest relative change in any element of *A* or *B* that makes  $\hat{x}_j$  an exact solution).
- 23: **recip-growth-factor** – double \* *Output*
- On exit:* if **fail.code** = NE\_NOERROR, the reciprocal pivot growth factor  $\|A\|/\|U\|$ , where  $\|\cdot\|$  denotes the maximum absolute element norm. If **recip-growth-factor**  $\ll 1$ , the stability of the *LU* factorization of (equilibrated) *A* could be poor. This also means that the solution **x**, condition estimate **rcond**, and forward error bound **ferr** could be unreliable. If the factorization fails with

**fail.code** = NE\_SINGULAR, then **recip.growth.factor** contains the reciprocal pivot growth factor for the leading **fail.errnum** columns of *A*.

24: **fail** – NagError \*

*Input/Output*

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_INT

On entry, **kl** =  $\langle value \rangle$ .

Constraint: **kl**  $\geq 0$ .

On entry, **ku** =  $\langle value \rangle$ .

Constraint: **ku**  $\geq 0$ .

On entry, **n** =  $\langle value \rangle$ .

Constraint: **n**  $\geq 0$ .

On entry, **nrhs** =  $\langle value \rangle$ .

Constraint: **nrhs**  $\geq 0$ .

On entry, **pdab** =  $\langle value \rangle$ .

Constraint: **pdab**  $> 0$ .

On entry, **pdafb** =  $\langle value \rangle$ .

Constraint: **pdafb**  $> 0$ .

On entry, **pdb** =  $\langle value \rangle$ .

Constraint: **pdb**  $> 0$ .

On entry, **pdx** =  $\langle value \rangle$ .

Constraint: **pdx**  $> 0$ .

### NE\_INT\_2

On entry, **pdb** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .

Constraint: **pdb**  $\geq \max(1, \mathbf{n})$ .

On entry, **pdb** =  $\langle value \rangle$  and **nrhs** =  $\langle value \rangle$ .

Constraint: **pdb**  $\geq \max(1, \mathbf{nrhs})$ .

On entry, **pdx** =  $\langle value \rangle$  and **n** =  $\langle value \rangle$ .

Constraint: **pdx**  $\geq \max(1, \mathbf{n})$ .

On entry, **pdx** =  $\langle value \rangle$  and **nrhs** =  $\langle value \rangle$ .

Constraint: **pdx**  $\geq \max(1, \mathbf{nrhs})$ .

### NE\_INT\_3

On entry, **pdab** =  $\langle value \rangle$ , **kl** =  $\langle value \rangle$  and **ku** =  $\langle value \rangle$ .

Constraint: **pdab**  $\geq \mathbf{kl} + \mathbf{ku} + 1$ .

On entry, **pdafb** =  $\langle value \rangle$ , **kl** =  $\langle value \rangle$  and **ku** =  $\langle value \rangle$ .  
 Constraint: **pdafb**  $\geq 2 \times \mathbf{kl} + \mathbf{ku} + 1$ .

#### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.  
 See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

#### NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.  
 See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

#### NE\_SINGULAR

Element  $\langle value \rangle$  of the diagonal is exactly zero. The factorization has been completed, but the factor  $U$  is exactly singular, so the solution and error bounds could not be computed.  
**rcond** = 0.0 is returned.

#### NE\_SINGULAR\_WP

$U$  is nonsingular, but **rcond** is less than *machine precision*, meaning that the matrix is singular to working precision. Nevertheless, the solution and error bounds are computed because there are a number of situations where the computed solution can be more accurate than the value of **rcond** would suggest.

## 7 Accuracy

For each right-hand side vector  $b$ , the computed solution  $\hat{x}$  is the exact solution of a perturbed system of equations  $(A + E)\hat{x} = b$ , where

$$|E| \leq c(n)\epsilon P|L||U|,$$

$c(n)$  is a modest linear function of  $n$ , and  $\epsilon$  is the *machine precision*. See Section 9.3 of Higham (2002) for further details.

If  $x$  is the true solution, then the computed solution  $\hat{x}$  satisfies a forward error bound of the form

$$\frac{\|x - \hat{x}\|_{\infty}}{\|\hat{x}\|_{\infty}} \leq w_c \text{cond}(A, \hat{x}, b)$$

where  $\text{cond}(A, \hat{x}, b) = \frac{\| |A^{-1}|(|A||\hat{x}| + |b|) \|_{\infty}}{\|\hat{x}\|_{\infty}} \leq \text{cond}(A) = \| |A^{-1}| |A| \|_{\infty} \leq \kappa_{\infty}(A)$ . If  $\hat{x}$  is the  $j$ th column of  $X$ , then  $w_c$  is returned in **berr**[ $j - 1$ ] and a bound on  $\|x - \hat{x}\|_{\infty}/\|\hat{x}\|_{\infty}$  is returned in **ferr**[ $j - 1$ ]. See Section 4.4 of Anderson *et al.* (1999) for further details.

## 8 Parallelism and Performance

nag\_zgbsvx (f07bpc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

nag\_zgbsvx (f07bpc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.



## 9 Further Comments

The band storage scheme for the array **ab** is illustrated by the following example, when  $n = 6$ ,  $k_l = 1$ , and  $k_u = 2$ . Storage of the band matrix  $A$  in the array **ab**:

<b>order = Nag_ColMajor</b>						<b>order = Nag_RowMajor</b>				
						*	$a_{11}$	$a_{12}$	$a_{13}$	
*	*	$a_{13}$	$a_{24}$	$a_{35}$	$a_{46}$	$a_{21}$	$a_{22}$	$a_{23}$	$a_{24}$	
*	$a_{12}$	$a_{23}$	$a_{34}$	$a_{45}$	$a_{56}$	$a_{32}$	$a_{33}$	$a_{34}$	$a_{35}$	
$a_{11}$	$a_{22}$	$a_{33}$	$a_{44}$	$a_{55}$	$a_{66}$	$a_{43}$	$a_{44}$	$a_{45}$	$a_{46}$	
$a_{21}$	$a_{32}$	$a_{43}$	$a_{54}$	$a_{65}$	*	$a_{54}$	$a_{55}$	$a_{56}$	*	
						$a_{65}$	$a_{66}$	*	*	

The total number of floating-point operations required to solve the equations  $AX = B$  depends upon the pivoting required, but if  $n \gg k_l + k_u$  then it is approximately bounded by  $O(nk_l(k_l + k_u))$  for the factorization and  $O(n(2k_l + k_u)r)$  for the solution following the factorization. The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization. The solution is then refined, and the errors estimated, using iterative refinement; see nag\_zgbrfs (f07bvc) for information on the floating-point operations required.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

The real analogue of this function is nag\_dgbsvx (f07bbc).

## 10 Example

This example solves the equations

$$AX = B,$$

where  $A$  is the band matrix

$$A = \begin{pmatrix} -1.65 + 2.26i & -2.05 - 0.85i & 0.97 - 2.84i & 0 & & \\ & 6.30i & -1.48 - 1.75i & -3.99 + 4.01i & 0.59 - 0.48i & \\ 0 & & -0.77 + 2.83i & -1.06 + 1.94i & 3.33 - 1.04i & \\ 0 & & 0 & 4.48 - 1.09i & -0.46 - 1.72i & \end{pmatrix}$$

and

$$B = \begin{pmatrix} -1.06 + 21.50i & 12.85 + 2.84i \\ -22.72 - 53.90i & -70.22 + 21.57i \\ 28.24 - 38.60i & -20.73 - 1.23i \\ -34.56 + 16.73i & 26.01 + 31.97i \end{pmatrix}.$$

Estimates for the backward errors, forward errors, condition number and pivot growth are also output, together with information on the equilibration of  $A$ .

### 10.1 Program Text

```
/* nag_zgbsvx (f07bpc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nagx04.h>
#include <nag_stdlib.h>
#include <nagf07.h>

int main(void)
```

```

{

/* Scalars */
double growth_factor, rcond;
Integer exit_status = 0, i, j, kl, ku, n, nrhs, pdab, pdafb, pdb, pdx;

/* Arrays */
Complex *ab = 0, *afb = 0, *b = 0, *x = 0;
double *berr = 0, *c = 0, *ferr = 0, *r = 0;
Integer *ipiv = 0;

/* Nag Types */
NagError fail;
Nag_OrderType order;
Nag_EquilibrationType equed;

#ifdef NAG_COLUMN_MAJOR
#define AB(I, J) ab[(J-1)*pdab + ku + I - J]
#define B(I, J) b[(J-1)*pdb + I - 1]
    order = Nag_ColMajor;
#else
#define AB(I, J) ab[(I-1)*pdab + kl + J - I]
#define B(I, J) b[(I-1)*pdb + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_zgbsvx (f07bpc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n]");
#else
    scanf("%*[\n]");
#endif

#ifdef _WIN32
    scanf_s("%" NAG_IFMT "%" NAG_IFMT "%" NAG_IFMT "%" NAG_IFMT "%*[\n]", &n,
        &nrhs, &kl, &ku);
#else
    scanf("%" NAG_IFMT "%" NAG_IFMT "%" NAG_IFMT "%" NAG_IFMT "%*[\n]", &n,
        &nrhs, &kl, &ku);
#endif

    if (n < 0 || kl < 0 || ku < 0 || nrhs < 0) {
        printf("Invalid n or kl or ku or nrhs\n");
        exit_status = 1;
        goto END;
    }

    /* Allocate memory */
    if (!(ab = NAG_ALLOC((kl + ku + 1) * n, Complex)) ||
        !(afb = NAG_ALLOC((2 * kl + ku + 1) * n, Complex)) ||
        !(b = NAG_ALLOC(n * nrhs, Complex)) ||
        !(x = NAG_ALLOC(n * nrhs, Complex)) ||
        !(berr = NAG_ALLOC(nrhs, double)) ||
        !(c = NAG_ALLOC(n, double)) ||
        !(ferr = NAG_ALLOC(nrhs, double)) ||
        !(r = NAG_ALLOC(n, double)) || !(ipiv = NAG_ALLOC(n, Integer)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    pdab = kl + ku + 1;
    pdafb = 2 * kl + ku + 1;
#ifdef NAG_COLUMN_MAJOR
    pdb = n;
    pdx = n;
#else
    pdb = nrhs;

```

```

    pdx = nrhs;
#endif

    /* Read the band matrix A and B from data file */
    for (i = 1; i <= n; ++i)
        for (j = MAX(i - kl, 1); j <= MIN(i + ku, n); ++j)
#ifdef _WIN32
            scanf_s(" ( %lf , %lf )", &AB(i, j).re, &AB(i, j).im);
#else
            scanf(" ( %lf , %lf )", &AB(i, j).re, &AB(i, j).im);
#endif
#ifdef _WIN32
            scanf_s("%*[^\\n]");
#else
            scanf("%*[^\\n]");
#endif

        for (i = 1; i <= n; ++i)
            for (j = 1; j <= nrhs; ++j)
#ifdef _WIN32
                scanf_s(" ( %lf , %lf )", &B(i, j).re, &B(i, j).im);
#else
                scanf(" ( %lf , %lf )", &B(i, j).re, &B(i, j).im);
#endif
#ifdef _WIN32
            scanf_s("%*[^\\n]");
#else
            scanf("%*[^\\n]");
#endif

    /* Solve the equations AX = B for X using nag_zgbsvx (f07bpc). */
    nag_zgbsvx(order, Nag_EquilibrateAndFactor, Nag_NoTrans, n, kl, ku, nrhs,
               ab, pdab, afb, pdafb, ipiv, &equed, r, c, b, pdb, x, pdx, &rcond,
               ferr, berr, &growth_factor, &fail);
    if (fail.code != NE_NOERROR && fail.code != NE_SINGULAR) {
        printf("Error from nag_zgbsvx (f07bpc).\\n%s\\n", fail.message);
        exit_status = 1;
        goto END;
    }

    /* Print solution usbing nag_gen_complx_mat_print_comp (x04dbc). */
    fflush(stdout);
    nag_gen_complx_mat_print_comp(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n,
                                   nrhs, x, pdx, Nag_BracketForm, "%7.4f",
                                   "Solution(s)", Nag_IntegerLabels, 0,
                                   Nag_IntegerLabels, 0, 80, 0, 0, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_gen_complx_mat_print_comp (x04dbc).\\n%s\\n",
               fail.message);
        exit_status = 1;
        goto END;
    }

    /* Print error bounds, condition number, the form of equilibration
     * and the pivot growth factor
     */
    printf("\\nBackward errors (machine-dependent)\\n");
    for (j = 1; j <= nrhs; ++j)
        printf("%11.1e%s", berr[j - 1], j % 7 == 0 ? "\\n" : " ");

    printf("\\n\\nEstimated forward error bounds (machine-dependent)\\n");
    for (j = 1; j <= nrhs; ++j)
        printf("%11.1e%s", ferr[j - 1], j % 7 == 0 ? "\\n" : " ");

    printf("\\nEstimate of reciprocal condition number\\n%11.1e\\n\\n", rcond);
    if (equed == Nag_NoEquilibration)
        printf("A has not been equilibrated\\n");
    else if (equed == Nag_RowEquilibration)
        printf("A has been row scaled as diag(R)*A\\n");
    else if (equed == Nag_ColumnEquilibration)
        printf("A has been column scaled as A*diag(C)\\n");

```

```

else if (equet == Nag_RowAndColumnEquilibration)
    printf("A has been row and column scaled as diag(R)*A*diag(C)\n");

printf("\nEstimate of reciprocal pivot growth factor\n%11.1e\n",
        growth_factor);
if (fail.code == NE_SINGULAR)
    printf("Error from nag_zgbsvx (f07bpc).\n%s\n", fail.message);
END:
NAG_FREE(ab);
NAG_FREE(afb);
NAG_FREE(b);
NAG_FREE(x);
NAG_FREE(berr);
NAG_FREE(c);
NAG_FREE(ferr);
NAG_FREE(r);
NAG_FREE(ipiv);

return exit_status;
}

#undef AB
#undef B

```

## 10.2 Program Data

```

nag_zgbsvx (f07bpc) Example Program Data
      4      2      1      2      : n, nrhs, kl and ku
(-1.65, 2.26) (-2.05,-0.85) ( 0.97,-2.84)
( 0.00, 6.30) (-1.48,-1.75) (-3.99, 4.01) ( 0.59,-0.48)
      (-0.77, 2.83) (-1.06, 1.94) ( 3.33,-1.04)
      ( 4.48,-1.09) (-0.46,-1.72) : matrix A
( -1.06, 21.50) ( 12.85,  2.84)
(-22.72,-53.90) (-70.22, 21.57)
( 28.24,-38.60) (-20.73, -1.23)
(-34.56, 16.73) ( 26.01, 31.97) : matrix B

```

## 10.3 Program Results

```

nag_zgbsvx (f07bpc) Example Program Results

Solution(s)
      1      2
1 (-3.0000, 2.0000) ( 1.0000, 6.0000)
2 ( 1.0000,-7.0000) (-7.0000,-4.0000)
3 (-5.0000, 4.0000) ( 3.0000, 5.0000)
4 ( 6.0000,-8.0000) (-8.0000, 2.0000)

Backward errors (machine-dependent)
1.8e-17      6.7e-17

Estimated forward error bounds (machine-dependent)
3.5e-14      4.3e-14
Estimate of reciprocal condition number
9.6e-03

A has not been equilibrated

Estimate of reciprocal pivot growth factor
1.0e+00

```

---