

NAG Library Function Document

nag_dsbgst (f08uec)

1 Purpose

nag_dsbgst (f08uec) reduces a real symmetric-definite generalized eigenproblem $Az = \lambda Bz$ to the standard form $Cy = \lambda y$, where A and B are band matrices, A is a real symmetric matrix, and B has been factorized by nag_dpbstf (f08ufc).

2 Specification

```
#include <nag.h>
#include <nagf08.h>

void nag_dsbgst (Nag_OrderType order, Nag_VectType vect, Nag_UploType uplo,
                Integer n, Integer ka, Integer kb, double ab[], Integer pdab,
                const double bb[], Integer pdbb, double x[], Integer pdx,
                NagError *fail)
```

3 Description

To reduce the real symmetric-definite generalized eigenproblem $Az = \lambda Bz$ to the standard form $Cy = \lambda y$, where A , B and C are banded, nag_dsbgst (f08uec) must be preceded by a call to nag_dpbstf (f08ufc) which computes the split Cholesky factorization of the positive definite matrix B : $B = S^T S$. The split Cholesky factorization, compared with the ordinary Cholesky factorization, allows the work to be approximately halved.

This function overwrites A with $C = X^T A X$, where $X = S^{-1} Q$ and Q is a orthogonal matrix chosen (implicitly) to preserve the bandwidth of A . The function also has an option to allow the accumulation of X , and then, if z is an eigenvector of C , Xz is an eigenvector of the original system.

4 References

Crawford C R (1973) Reduction of a band-symmetric generalized eigenvalue problem *Comm. ACM* **16** 41–44

Kaufman L (1984) Banded eigenvalue solvers on vector machines *ACM Trans. Math. Software* **10** 73–86

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **vect** – Nag_VectType *Input*

On entry: indicates whether X is to be returned.

vect = Nag_DoNotForm
 X is not returned.

vect = Nag_FormX
X is returned.

Constraint: **vect** = Nag_DoNotForm or Nag_FormX.

3: **uplo** – Nag_UploType *Input*

On entry: indicates whether the upper or lower triangular part of *A* is stored.

uplo = Nag_Upper
 The upper triangular part of *A* is stored.

uplo = Nag_Lower
 The lower triangular part of *A* is stored.

Constraint: **uplo** = Nag_Upper or Nag_Lower.

4: **n** – Integer *Input*

On entry: *n*, the order of the matrices *A* and *B*.

Constraint: **n** ≥ 0.

5: **ka** – Integer *Input*

On entry: if **uplo** = Nag_Upper, the number of superdiagonals, *k_a*, of the matrix *A*.

If **uplo** = Nag_Lower, the number of subdiagonals, *k_a*, of the matrix *A*.

Constraint: **ka** ≥ 0.

6: **kb** – Integer *Input*

On entry: if **uplo** = Nag_Upper, the number of superdiagonals, *k_b*, of the matrix *B*.

If **uplo** = Nag_Lower, the number of subdiagonals, *k_b*, of the matrix *B*.

Constraint: **ka** ≥ **kb** ≥ 0.

7: **ab**[*dim*] – double *Input/Output*

Note: the dimension, *dim*, of the array **ab** must be at least max(1, **pdab** × **n**).

On entry: the upper or lower triangle of the *n* by *n* symmetric band matrix *A*.

This is stored as a notional two-dimensional array with row elements or column elements stored contiguously. The storage of elements of *A_{ij}*, depends on the **order** and **uplo** arguments as follows:

if **order** = Nag_ColMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ab**[*k_a* + *i* - *j* + (*j* - 1) × **pdab**], for *j* = 1, ..., *n* and
 i = max(1, *j* - *k_a*), ..., *j*;
 if **order** = Nag_ColMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ab**[*i* - *j* + (*j* - 1) × **pdab**], for *j* = 1, ..., *n* and
 i = *j*, ..., min(*n*, *j* + *k_a*);
 if **order** = Nag_RowMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ab**[*j* - *i* + (*i* - 1) × **pdab**], for *i* = 1, ..., *n* and
 j = *i*, ..., min(*n*, *i* + *k_a*);
 if **order** = Nag_RowMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ab**[*k_a* + *j* - *i* + (*i* - 1) × **pdab**], for *i* = 1, ..., *n* and
 j = max(1, *i* - *k_a*), ..., *i*.

On exit: the upper or lower triangle of **ab** is overwritten by the corresponding upper or lower triangle of *C* as specified by **uplo**.

- 8: **pdab** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix *A* in the array **ab**.
Constraint: **pdab** \geq **ka** + 1.
- 9: **bb**[*dim*] – const double *Input*
Note: the dimension, *dim*, of the array **bb** must be at least $\max(1, \mathbf{pdbb} \times \mathbf{n})$.
On entry: the banded split Cholesky factor of *B* as specified by **uplo**, **n** and **kb** and returned by nag_dpbstf (f08ufc).
- 10: **pdbb** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix in the array **bb**.
Constraint: **pdbb** \geq **kb** + 1.
- 11: **x**[*dim*] – double *Output*
Note: the dimension, *dim*, of the array **x** must be at least
 $\max(1, \mathbf{pdx} \times \mathbf{n})$ when **vect** = Nag_FormX;
1 when **vect** = Nag_DoNotForm.
The (*i*, *j*)th element of the matrix *X* is stored in
 $\mathbf{x}[(j-1) \times \mathbf{pdx} + i - 1]$ when **order** = Nag_ColMajor;
 $\mathbf{x}[(i-1) \times \mathbf{pdx} + j - 1]$ when **order** = Nag_RowMajor.
On exit: the *n* by *n* matrix $X = S^{-1}Q$, if **vect** = Nag_FormX.
If **vect** = Nag_DoNotForm, **x** is not referenced.
- 12: **pdx** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) in the array **x**.
Constraints:
if **vect** = Nag_FormX, **pdx** \geq $\max(1, \mathbf{n})$;
if **vect** = Nag_DoNotForm, **pdx** \geq 1.
- 13: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument *value* had an illegal value.

NE_ENUM_INT_2

On entry, **vect** = $\langle value \rangle$, **pdx** = $\langle value \rangle$ and **n** = $\langle value \rangle$.
 Constraint: if **vect** = Nag_FormX, **pdx** $\geq \max(1, \mathbf{n})$;
 if **vect** = Nag_DoNotForm, **pdx** ≥ 1 .

NE_INT

On entry, **ka** = $\langle value \rangle$.
 Constraint: **ka** ≥ 0 .

On entry, **n** = $\langle value \rangle$.
 Constraint: **n** ≥ 0 .

On entry, **pdab** = $\langle value \rangle$.
 Constraint: **pdab** > 0 .

On entry, **pdbb** = $\langle value \rangle$.
 Constraint: **pdbb** > 0 .

On entry, **pdx** = $\langle value \rangle$.
 Constraint: **pdx** > 0 .

NE_INT_2

On entry, **ka** = $\langle value \rangle$ and **kb** = $\langle value \rangle$.
 Constraint: **ka** $\geq \mathbf{kb} \geq 0$.

On entry, **pdab** = $\langle value \rangle$ and **ka** = $\langle value \rangle$.
 Constraint: **pdab** $\geq \mathbf{ka} + 1$.

On entry, **pdbb** = $\langle value \rangle$ and **kb** = $\langle value \rangle$.
 Constraint: **pdbb** $\geq \mathbf{kb} + 1$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.
 See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.
 See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

Forming the reduced matrix C is a stable procedure. However it involves implicit multiplication by B^{-1} . When nag_dsbgst (f08uec) is used as a step in the computation of eigenvalues and eigenvectors of the original problem, there may be a significant loss of accuracy if B is ill-conditioned with respect to inversion.

8 Parallelism and Performance

nag_dsbgst (f08uec) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations is approximately $6n^2k_B$, when **vect** = Nag_DoNotForm, assuming $n \gg k_A, k_B$; there are an additional $(3/2)n^3(k_B/k_A)$ operations when **vect** = Nag_FormX.

The complex analogue of this function is nag_zhbgst (f08usc).

10 Example

This example computes all the eigenvalues of $Az = \lambda Bz$, where

$$A = \begin{pmatrix} 0.24 & 0.39 & 0.42 & 0.00 \\ 0.39 & -0.11 & 0.79 & 0.63 \\ 0.42 & 0.79 & -0.25 & 0.48 \\ 0.00 & 0.63 & 0.48 & -0.03 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 2.07 & 0.95 & 0.00 & 0.00 \\ 0.95 & 1.69 & -0.29 & 0.00 \\ 0.00 & -0.29 & 0.65 & -0.33 \\ 0.00 & 0.00 & -0.33 & 1.17 \end{pmatrix}.$$

Here A is symmetric, B is symmetric positive definite, and A and B are treated as band matrices. B must first be factorized by nag_dpbstf (f08ufc). The program calls nag_dsbgst (f08uec) to reduce the problem to the standard form $Cy = \lambda y$, then nag_dsbtrd (f08hec) to reduce C to tridiagonal form, and nag_dsterf (f08jfc) to compute the eigenvalues.

10.1 Program Text

```
/* nag_dsbgst (f08uec) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf08.h>

int main(void)
{
    /* Scalars */
    Integer i, j, k1, k2, ka, kb, n, pdab, pddb, pdx, d_len, e_len;
    Integer exit_status = 0;
    NagError fail;
    Nag_UploType uplo;
    Nag_OrderType order;
    /* Arrays */
    char nag_enum_arg[40];
    double *ab = 0, *bb = 0, *d = 0, *e = 0, *x = 0;

#ifdef NAG_COLUMN_MAJOR
#define AB_UPPER(I, J) ab[(J-1)*pdab + k1 + I - J - 1]
#define AB_LOWER(I, J) ab[(J-1)*pdab + I - J]
#define BB_UPPER(I, J) bb[(J-1)*pddb + k2 + I - J - 1]
#define BB_LOWER(I, J) bb[(J-1)*pddb + I - J]
    order = Nag_ColMajor;
#else
#define AB_UPPER(I, J) ab[(I-1)*pdab + J - I]
#define AB_LOWER(I, J) ab[(I-1)*pdab + k1 + J - I - 1]
#define BB_UPPER(I, J) bb[(I-1)*pddb + J - I]
#define BB_LOWER(I, J) bb[(I-1)*pddb + k2 + J - I - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    printf("nag_dsbgst (f08uec) Example Program Results\n\n");
```

```

/* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
#ifdef _WIN32
    scanf_s("%" NAG_IFMT "%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &n, &ka, &kb);
#else
    scanf("%" NAG_IFMT "%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &n, &ka, &kb);
#endif
    pdab = ka + 1;
    pddb = kb + 1;
    pdx = n;
    d_len = n;
    e_len = n - 1;

/* Allocate memory */
if (!(ab = NAG_ALLOC(pdab * n, double)) ||
    !(bb = NAG_ALLOC(pddb * n, double)) ||
    !(d = NAG_ALLOC(d_len, double)) ||
    !(e = NAG_ALLOC(e_len, double)) || !(x = NAG_ALLOC(n * n, double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read whether Upper or Lower part of A is stored */
#ifdef _WIN32
    scanf_s("%39s%*[\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
    scanf("%39s%*[\n] ", nag_enum_arg);
#endif
/* nag_enum_name_to_value (x04nac).
 * Converts NAG enum member name to value
 */
uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);
/* Read A and B from data file */
k1 = ka + 1;
k2 = kb + 1;
if (uplo == Nag_Upper) {
    for (i = 1; i <= n; ++i) {
        for (j = i; j <= MIN(i + ka, n); ++j)
#ifdef _WIN32
            scanf_s("%lf", &AB_UPPER(i, j));
#else
            scanf("%lf", &AB_UPPER(i, j));
#endif
    }
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
}
else {
    for (i = 1; i <= n; ++i) {
        for (j = MAX(1, i - ka); j <= i; ++j)
#ifdef _WIN32
            scanf_s("%lf", &AB_LOWER(i, j));
#else
            scanf("%lf", &AB_LOWER(i, j));
#endif
    }
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
}
if (uplo == Nag_Upper) {

```

```

        for (i = 1; i <= n; ++i) {
            for (j = i; j <= MIN(i + kb, n); ++j)
#ifdef _WIN32
                scanf_s("%lf", &BB_UPPER(i, j));
#else
                scanf("%lf", &BB_UPPER(i, j));
#endif
        }
#ifdef _WIN32
        scanf_s("%*[\n] ");
#else
        scanf("%*[\n] ");
#endif
    }
    else {
        for (i = 1; i <= n; ++i) {
            for (j = MAX(1, i - kb); j <= i; ++j)
#ifdef _WIN32
                scanf_s("%lf", &BB_LOWER(i, j));
#else
                scanf("%lf", &BB_LOWER(i, j));
#endif
        }
#ifdef _WIN32
        scanf_s("%*[\n] ");
#else
        scanf("%*[\n] ");
#endif
    }
    /* Compute the split Cholesky factorization of B */
    /* nag_dpbstf (f08ufc).
     * Computes a split Cholesky factorization of real symmetric
     * positive-definite band matrix A
     */
    nag_dpbstf(order, uplo, n, kb, bb, pddb, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_dpbstf (f08ufc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Reduce the problem to standard form C*y = lambda*y, */
    /* storing the result in A */
    /* nag_dsbgst (f08uec).
     * Reduction of real symmetric-definite banded generalized
     * eigenproblem Ax = lambda Bx to standard form
     * Cy = lambda y, such that C has the same bandwidth as A
     */
    nag_dsbgst(order, Nag_DoNotForm, uplo, n, ka, kb, ab, pdab, bb, pddb,
               x, pdx, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_dsbgst (f08uec).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Reduce C to tridiagonal form T = (Q^T)*C*Q */
    /* nag_dsbtrd (f08hec).
     * Orthogonal reduction of real symmetric band matrix to
     * symmetric tridiagonal form
     */
    nag_dsbtrd(order, Nag_DoNotForm, uplo, n, ka, ab, pdab, d, e,
               x, pdx, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_dsbtrd (f08hec).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Calculate the eigenvalues of T (same as C) */
    /* nag_dsterf (f08jfc).
     * All eigenvalues of real symmetric tridiagonal matrix,
     * root-free variant of QL or QR
     */

```

```

nag_dsterf(n, d, e, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_dsterf (f08jfc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
/* Print eigenvalues */
printf(" Eigenvalues\n");
for (i = 0; i < n; ++i)
    printf(" %8.4lf", d[i]);
printf("\n");
END:
NAG_FREE(ab);
NAG_FREE(bb);
NAG_FREE(d);
NAG_FREE(e);
NAG_FREE(x);
return exit_status;
}

```

10.2 Program Data

```

nag_dsbgst (f08uec) Example Program Data
4 2 1 :Values of n, ka and kb
Nag_Lower :Value of uplo
0.24
0.39 -0.11
0.42 0.79 -0.25
0.63 0.48 -0.03 :End of matrix A
2.07
0.95 1.69
-0.29 0.65
-0.33 1.17 :End of matrix B

```

10.3 Program Results

nag_dsbgst (f08uec) Example Program Results

```

Eigenvalues
-0.8305 -0.6401 0.0992 1.8525

```
