

NAG Library Function Document

nag_dsbmv (f16pdc)

1 Purpose

nag_dsbmv (f16pdc) performs matrix-vector multiplication for a real symmetric band matrix.

2 Specification

```
#include <nag.h>
#include <nagf16.h>

void nag_dsbmv (Nag_OrderType order, Nag_UploType uplo, Integer n, Integer k,
               double alpha, const double ab[], Integer pdab, const double x[],
               Integer incx, double beta, double y[], Integer incy, NagError *fail)
```

3 Description

nag_dsbmv (f16pdc) performs the matrix-vector operation

$$y \leftarrow \alpha Ax + \beta y,$$

where A is an n by n real symmetric band matrix with k subdiagonals and k superdiagonals, x and y are n -element real vectors, and α and β are real scalars.

4 References

Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001) *Basic Linear Algebra Subprograms Technical (BLAST) Forum Standard* University of Tennessee, Knoxville, Tennessee <http://www.netlib.org/blas/blast-forum/blas-report.pdf>

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **uplo** – Nag_UploType *Input*
On entry: specifies whether the upper or lower triangular part of A is stored.
uplo = Nag_Upper
The upper triangular part of A is stored.
uplo = Nag_Lower
The lower triangular part of A is stored.
Constraint: **uplo** = Nag_Upper or Nag_Lower.
- 3: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: **n** ≥ 0 .

- 4: **k** – Integer *Input*
On entry: k , the number of subdiagonals or superdiagonals of the matrix A .
Constraint: $k \geq 0$.
- 5: **alpha** – double *Input*
On entry: the scalar α .
- 6: **ab**[*dim*] – const double *Input*
Note: the dimension, *dim*, of the array **ab** must be at least $\max(1, \mathbf{pdab} \times \mathbf{n})$.
On entry: the n by n symmetric band matrix A .
This is stored as a notional two-dimensional array with row elements or column elements stored contiguously. The storage of elements of A_{ij} , depends on the **order** and **uplo** arguments as follows:
if **order** = Nag_ColMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ab**[$k + i - j + (j - 1) \times \mathbf{pdab}$], for $j = 1, \dots, n$ and $i = \max(1, j - k), \dots, j$;
if **order** = Nag_ColMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ab**[$i - j + (j - 1) \times \mathbf{pdab}$], for $j = 1, \dots, n$ and $i = j, \dots, \min(n, j + k)$;
if **order** = Nag_RowMajor and **uplo** = Nag_Upper,
 A_{ij} is stored in **ab**[$j - i + (i - 1) \times \mathbf{pdab}$], for $i = 1, \dots, n$ and $j = i, \dots, \min(n, i + k)$;
if **order** = Nag_RowMajor and **uplo** = Nag_Lower,
 A_{ij} is stored in **ab**[$k + j - i + (i - 1) \times \mathbf{pdab}$], for $i = 1, \dots, n$ and $j = \max(1, i - k), \dots, i$.
- 7: **pdab** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix A in the array **ab**.
Constraint: $\mathbf{pdab} \geq k + 1$.
- 8: **x**[*dim*] – const double *Input*
Note: the dimension, *dim*, of the array **x** must be at least $\max(1, 1 + (\mathbf{n} - 1)|\mathbf{incx}|)$.
On entry: the n -element vector x .
If $\mathbf{incx} > 0$, x_i must be stored in **x**[($i - 1$) \times \mathbf{incx}], for $i = 1, 2, \dots, \mathbf{n}$.
If $\mathbf{incx} < 0$, x_i must be stored in **x**[($\mathbf{n} - i$) \times $|\mathbf{incx}|$], for $i = 1, 2, \dots, \mathbf{n}$.
Intermediate elements of **x** are not referenced. If $\mathbf{n} = 0$, **x** is not referenced and may be **NULL**.
- 9: **incx** – Integer *Input*
On entry: the increment in the subscripts of **x** between successive elements of x .
Constraint: $\mathbf{incx} \neq 0$.
- 10: **beta** – double *Input*
On entry: the scalar β .
- 11: **y**[*dim*] – double *Input/Output*
Note: the dimension, *dim*, of the array **y** must be at least $\max(1, 1 + (\mathbf{n} - 1)|\mathbf{incy}|)$.
On entry: the vector y . See **x** for details of storage.

If **beta** = 0, **y** need not be set.

On exit: the updated vector *y*.

12: **incy** – Integer

Input

On entry: the increment in the subscripts of **y** between successive elements of *y*.

Constraint: **incy** \neq 0.

13: **fail** – NagError *

Input/Output

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **incx** = $\langle value \rangle$.

Constraint: **incx** \neq 0.

On entry, **incy** = $\langle value \rangle$.

Constraint: **incy** \neq 0.

On entry, **k** = $\langle value \rangle$.

Constraint: **k** \geq 0.

On entry, **n** = $\langle value \rangle$.

Constraint: **n** \geq 0.

NE_INT_2

On entry, **pdab** = $\langle value \rangle$, **k** = $\langle value \rangle$.

Constraint: **pdab** \geq **k** + 1.

NE_INTERNAL_ERROR

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

The BLAS standard requires accurate implementations which avoid unnecessary over/underflow (see Section 2.7 of Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001)).

8 Parallelism and Performance

nag_dsbmv (f16pdc) is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example computes the matrix-vector product

$$y = \alpha Ax + \beta y$$

where

$$A = \begin{pmatrix} 1.0 & 2.0 & 3.0 & 0.0 & 0.0 \\ 2.0 & 2.0 & 3.0 & 4.0 & 0.0 \\ 3.0 & 3.0 & 3.0 & 4.0 & 5.0 \\ 0.0 & 4.0 & 4.0 & 4.0 & 5.0 \\ 0.0 & 0.0 & 5.0 & 5.0 & 5.0 \end{pmatrix},$$

$$x = \begin{pmatrix} -1.0 \\ 2.0 \\ -3.0 \\ 2.0 \\ -1.0 \end{pmatrix},$$

$$y = \begin{pmatrix} 10.0 \\ 1.5 \\ 9.5 \\ 8.5 \\ 24.0 \end{pmatrix},$$

$$\alpha = 1.5 \quad \text{and} \quad \beta = 1.0.$$

10.1 Program Text

```
/* nag_dsmbv (f16pdc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf16.h>

int main(void)
{
    /* Scalars */
    double alpha, beta;
    Integer exit_status, i, incx, incy, j, k, kd, n, pdab, xlen, ylen;

    /* Arrays */
    double *ab = 0, *x = 0, *y = 0;
    char nag_enum_arg[40];

    /* Nag Types */
    NagError fail;
    Nag_OrderType order;
    Nag_UploType uplo;

#ifdef NAG_COLUMN_MAJOR
#define AB_UPPER(I, J) ab[(J-1)*pdab + k + I - J - 1]
#define AB_LOWER(I, J) ab[(J-1)*pdab + I - J]
#endif
```

```

    order = Nag_ColMajor;
#else
#define AB_UPPER(I, J) ab[(I-1)*pdab + J - I]
#define AB_LOWER(I, J) ab[(I-1)*pdab + k + J - I - 1]
    order = Nag_RowMajor;
#endif

    exit_status = 0;
    INIT_FAIL(fail);

    printf("nag_dsmbv (f16pdc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
    /* Read the problem dimension */
#ifdef _WIN32
    scanf_s("%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &n, &kd);
#else
    scanf("%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &n, &kd);
#endif
    /* Read uplo */
#ifdef _WIN32
    scanf_s("%39s%*[\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
    scanf("%39s%*[\n] ", nag_enum_arg);
#endif
    /* nag_enum_name_to_value (x04nac).
     * Converts NAG enum member name to value
     */
    uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);
    /* Read scalar parameters */
#ifdef _WIN32
    scanf_s("%lf%lf%*[\n] ", &alpha, &beta);
#else
    scanf("%lf%lf%*[\n] ", &alpha, &beta);
#endif
    /* Read increment parameters */
#ifdef _WIN32
    scanf_s("%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &incx, &incy);
#else
    scanf("%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &incx, &incy);
#endif

    pdab = kd + 1;
    xlen = MAX(1, 1 + (n - 1) * ABS(incx));
    ylen = MAX(1, 1 + (n - 1) * ABS(incy));

    if (n > 0) {
        /* Allocate memory */
        if (!(ab = NAG_ALLOC(pdab * n, double)) ||
            !(x = NAG_ALLOC(xlen, double)) || !(y = NAG_ALLOC(ylen, double)))
        {
            printf("Allocation failure\n");
            exit_status = -1;
            goto END;
        }
    }
    else {
        printf("Invalid n\n");
        exit_status = 1;
        return exit_status;
    }

    /* Read A from data file */
    k = kd + 1;
    if (uplo == Nag_Upper) {
        for (i = 1; i <= n; ++i) {

```

```

        for (j = i; j <= MIN(i + kd, n); ++j)
#ifdef _WIN32
            scanf_s("%lf", &AB_UPPER(i, j));
#else
            scanf("%lf", &AB_UPPER(i, j));
#endif
        }
#ifdef _WIN32
        scanf_s("%*[^\\n] ");
#else
        scanf("%*[^\\n] ");
#endif
    }
    else {
        for (i = 1; i <= n; ++i) {
            for (j = MAX(1, i - kd); j <= i; ++j)
#ifdef _WIN32
                scanf_s("%lf", &AB_LOWER(i, j));
#else
                scanf("%lf", &AB_LOWER(i, j));
#endif
        }
#ifdef _WIN32
        scanf_s("%*[^\\n] ");
#else
        scanf("%*[^\\n] ");
#endif
    }

    /* Input vectors x and y */

    for (i = 1; i <= xlen; ++i)
#ifdef _WIN32
        scanf_s("%lf%*[^\\n] ", &x[i - 1]);
#else
        scanf("%lf%*[^\\n] ", &x[i - 1]);
#endif
    for (i = 1; i <= ylen; ++i)
#ifdef _WIN32
        scanf_s("%lf%*[^\\n] ", &y[i - 1]);
#else
        scanf("%lf%*[^\\n] ", &y[i - 1]);
#endif

    /* nag_dsbmv (f16pdc).
     * Symmetric banded matrix-vector multiply.
     */
    nag_dsbmv(order, uplo, n, kd, alpha, ab, pdab, x, incx,
              beta, y, incy, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_dsbmv.\\n%s\\n", fail.message);
        exit_status = 1;
        goto END;
    }

    /* Print output vector y */
    printf("%s\\n", "  y");
    for (i = 1; i <= ylen; ++i) {
        printf("%11f\\n", y[i - 1]);
    }

END:
    NAG_FREE(ab);
    NAG_FREE(x);
    NAG_FREE(y);

    return exit_status;
}

```

10.2 Program Data

```
nag_dsbmv (f16pdc) Example Program Data
  5  2                               :Values of n and kd
  Nag_Lower                          :Value of uplo
  1.5 1.0                            : alpha, beta
  1 1                                : incx, incy
  1.0
  2.0 2.0
  3.0 3.0 3.0
      4.0 4.0 4.0
      5.0 5.0 5.0      :End of matrix A

  -1.0
  2.0
  -3.0
  2.0
  -1.0                        : the end of vector x
  10.0
  1.5
  9.5
  8.5
  24.0                        : the end of vector y
```

10.3 Program Results

```
nag_dsbmv (f16pdc) Example Program Results

  y
  1.000000
  3.000000
  5.000000
  7.000000
  9.000000
```
