

NAG Library Function Document

nag_zsyrk (f16zuc)

1 Purpose

nag_zsyrk (f16zuc) performs a rank- k update on a complex symmetric matrix.

2 Specification

```
#include <nag.h>
#include <nagf16.h>

void nag_zsyrk (Nag_OrderType order, Nag_UploType uplo, Nag_TransType trans,
               Integer n, Integer k, Complex alpha, const Complex a[], Integer pda,
               Complex beta, Complex c[], Integer pdc, NagError *fail)
```

3 Description

nag_zsyrk (f16zuc) performs one of the symmetric rank- k update operations

$$C \leftarrow \alpha AA^T + \beta C \quad \text{or} \quad C \leftarrow \alpha A^T A + \beta C,$$

where A is a complex matrix, C is an n by n complex symmetric matrix, and α and β are complex scalars.

4 References

Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001) *Basic Linear Algebra Subprograms Technical (BLAST) Forum Standard* University of Tennessee, Knoxville, Tennessee <http://www.netlib.org/blas/blast-forum/blas-report.pdf>

5 Arguments

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.
Constraint: **order** = Nag_RowMajor or Nag_ColMajor.
- 2: **uplo** – Nag_UploType *Input*
On entry: specifies whether the upper or lower triangular part of C is stored.
uplo = Nag_Upper
The upper triangular part of C is stored.
uplo = Nag_Lower
The lower triangular part of C is stored.
Constraint: **uplo** = Nag_Upper or Nag_Lower.

- 3: **trans** – Nag_TransType *Input*
On entry: specifies the operation to be performed.
trans = Nag_NoTrans
 $C \leftarrow \alpha AA^T + \beta C$.
trans = Nag_Trans
 $C \leftarrow \alpha A^T A + \beta C$.
Constraint: **trans** = Nag_NoTrans or Nag_Trans.
- 4: **n** – Integer *Input*
On entry: n , the order of the matrix C ; the number of rows of A if **trans** = Nag_NoTrans, or the number of columns of A otherwise.
Constraint: $n \geq 0$.
- 5: **k** – Integer *Input*
On entry: k , the number of columns of A if **trans** = Nag_NoTrans, or the number of rows of A otherwise.
Constraint: $k \geq 0$.
- 6: **alpha** – Complex *Input*
On entry: the scalar α .
- 7: **a**[*dim*] – const Complex *Input*
Note: the dimension, *dim*, of the array **a** must be at least
 $\max(1, \mathbf{pda} \times \mathbf{k})$ when **trans** = Nag_NoTrans and **order** = Nag_ColMajor;
 $\max(1, \mathbf{n} \times \mathbf{pda})$ when **trans** = Nag_NoTrans and **order** = Nag_RowMajor;
 $\max(1, \mathbf{pda} \times \mathbf{n})$ when **trans** = Nag_Trans and **order** = Nag_ColMajor;
 $\max(1, \mathbf{k} \times \mathbf{pda})$ when **trans** = Nag_Trans and **order** = Nag_RowMajor.
If **order** = Nag_ColMajor, A_{ij} is stored in **a**[($j - 1$) \times **pda** + $i - 1$].
If **order** = Nag_RowMajor, A_{ij} is stored in **a**[($i - 1$) \times **pda** + $j - 1$].
On entry: the matrix A ; A is n by k if **trans** = Nag_NoTrans, or k by n otherwise.
- 8: **pda** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) in the array **a**.
Constraints:
if **order** = Nag_ColMajor,
if **trans** = Nag_NoTrans, **pda** $\geq \max(1, \mathbf{n})$;
if **trans** = Nag_Trans, **pda** $\geq \max(1, \mathbf{k})$.;
if **order** = Nag_RowMajor,
if **trans** = Nag_NoTrans, **pda** $\geq \max(1, \mathbf{k})$;
if **trans** = Nag_Trans, **pda** $\geq \max(1, \mathbf{n})$.
- 9: **beta** – Complex *Input*
On entry: the scalar β .
- 10: **c**[*dim*] – Complex *Input/Output*
Note: the dimension, *dim*, of the array **c** must be at least $\max(1, \mathbf{pdc} \times \mathbf{n})$.

On entry: the n by n symmetric matrix C .

If **order** = Nag_ColMajor, C_{ij} is stored in $\mathbf{c}[(j-1) \times \mathbf{pdc} + i - 1]$.

If **order** = Nag_RowMajor, C_{ij} is stored in $\mathbf{c}[(i-1) \times \mathbf{pdc} + j - 1]$.

If **uplo** = Nag_Upper, the upper triangular part of C must be stored and the elements of the array below the diagonal are not referenced.

If **uplo** = Nag_Lower, the lower triangular part of C must be stored and the elements of the array above the diagonal are not referenced.

On exit: the updated matrix C .

11: **pdc** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix C in the array \mathbf{c} .

Constraint: $\mathbf{pdc} \geq \max(1, \mathbf{n})$.

12: **fail** – NagError * *Input/Output*

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle \text{value} \rangle$ had an illegal value.

NE_ENUM_INT_2

On entry, **trans** = $\langle \text{value} \rangle$, **k** = $\langle \text{value} \rangle$, **pda** = $\langle \text{value} \rangle$.

Constraint: if **trans** = Nag_NoTrans, $\mathbf{pda} \geq \max(1, \mathbf{k})$.

On entry, **trans** = $\langle \text{value} \rangle$, **k** = $\langle \text{value} \rangle$, **pda** = $\langle \text{value} \rangle$.

Constraint: if **trans** = Nag_Trans, $\mathbf{pda} \geq \max(1, \mathbf{k})$.

On entry, **trans** = $\langle \text{value} \rangle$, **n** = $\langle \text{value} \rangle$, **pda** = $\langle \text{value} \rangle$.

Constraint: if **trans** = Nag_NoTrans, $\mathbf{pda} \geq \max(1, \mathbf{n})$.

On entry, **trans** = $\langle \text{value} \rangle$, **n** = $\langle \text{value} \rangle$, **pda** = $\langle \text{value} \rangle$.

Constraint: if **trans** = Nag_Trans, $\mathbf{pda} \geq \max(1, \mathbf{n})$.

NE_INT

On entry, **k** = $\langle \text{value} \rangle$.

Constraint: $\mathbf{k} \geq 0$.

On entry, **n** = $\langle \text{value} \rangle$.

Constraint: $\mathbf{n} \geq 0$.

NE_INT_2

On entry, **pdc** = $\langle \text{value} \rangle$, **n** = $\langle \text{value} \rangle$.

Constraint: $\mathbf{pdc} \geq \max(1, \mathbf{n})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

The BLAS standard requires accurate implementations which avoid unnecessary over/underflow (see Section 2.7 of Basic Linear Algebra Subprograms Technical (BLAST) Forum (2001)).

8 Parallelism and Performance

nag_zsyrk (f16zuc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

None.

10 Example

Perform rank- k update of complex symmetric 4 by 4 matrix C using 4 by 2 matrix A ($k = 2$), $C = C - (1.0 - 1.0i)AA^T$, where

$$C = \begin{pmatrix} 4.78 + 1.03i & 2.00 - 0.30i & 2.89 - 1.34i & -1.89 + 1.15i \\ 2.00 - 0.30i & -4.11 - 2.30i & 2.36 - 4.25i & 0.04 - 3.69i \\ 2.89 - 1.34i & 2.36 - 4.25i & 4.15 + 0.57i & -0.02 + 0.46i \\ -1.89 + 1.15i & 0.04 - 3.69i & -0.02 + 0.46i & 0.33 - 1.91i \end{pmatrix}$$

and

$$A = \begin{pmatrix} 1.7 - 2.3i & -1.8 + 2.4i \\ 2.9 - 2.1i & 1.2 + 1.4i \\ -2.9 + 1.0i & 0.6 + 0.8i \\ 1.5 + 0.9i & -1.4 - 1.7i \end{pmatrix}.$$

10.1 Program Text

```
/* nag_zsyrk (f16zuc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf16.h>
```

```

#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Complex alpha, beta;
    Integer adim1, adim2, exit_status, i, j, k, n, pda, pdc;

    /* Arrays */
    Complex *a = 0, *c = 0;
    char nag_enum_arg[40];

    /* Nag Types */
    NagError fail;
    Nag_OrderType order;
    Nag_UploType uplo;
    Nag_TransType trans;
    Nag_MatrixType matrix;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J-1)*pda + I - 1]
#define C(I, J) c[(J-1)*pdc + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I-1)*pda + J - 1]
#define C(I, J) c[(I-1)*pdc + J - 1]
    order = Nag_RowMajor;
#endif

    exit_status = 0;
    INIT_FAIL(fail);

    printf("nag_zsyrc (f16zuc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif

    /* Read the problem dimensions */
#ifdef _WIN32
    scanf_s("%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &n, &k);
#else
    scanf("%" NAG_IFMT "%" NAG_IFMT "%*[\n] ", &n, &k);
#endif

    /* Read the uplo parameter */
#ifdef _WIN32
    scanf_s("%39s%*[\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
    scanf("%39s%*[\n] ", nag_enum_arg);
#endif
    /* nag_enum_name_to_value (x04nac).
     * Converts NAG enum member name to value
     */
    uplo = (Nag_UploType) nag_enum_name_to_value(nag_enum_arg);
    /* Read the transpose parameter */
#ifdef _WIN32
    scanf_s("%39s%*[\n] ", nag_enum_arg, (unsigned)_countof(nag_enum_arg));
#else
    scanf("%39s%*[\n] ", nag_enum_arg);
#endif
    /* nag_enum_name_to_value (x04nac), see above. */
    trans = (Nag_TransType) nag_enum_name_to_value(nag_enum_arg);
    /* Read scalar parameters */
#ifdef _WIN32
    scanf_s(" ( %lf , %lf )%*[\n] ", &alpha.re, &alpha.im);
#else

```

```

    scanf(" ( %lf , %lf )%*[\n] ", &alpha.re, &alpha.im);
#endif
#ifdef _WIN32
    scanf_s(" ( %lf , %lf )%*[\n] ", &beta.re, &beta.im);
#else
    scanf(" ( %lf , %lf )%*[\n] ", &beta.re, &beta.im);
#endif

    if (trans == Nag_NoTrans) {
        adim1 = n;
        adim2 = k;
    }
    else {
        adim1 = k;
        adim2 = n;
    }

#ifdef NAG_COLUMN_MAJOR
    pda = adim1;
#else
    pda = adim2;
#endif
    pdc = n;
    if (k > 0 && n > 0) {
        /* Allocate memory */
        if (!(a = NAG_ALLOC(k * n, Complex)) || !(c = NAG_ALLOC(n * n, Complex)))
        {
            printf("Allocation failure\n");
            exit_status = -1;
            goto END;
        }
    }
    else {
        printf("Invalid k or n\n");
        exit_status = 1;
        return exit_status;
    }

    /* Input matrix A. */
    for (i = 1; i <= adim1; ++i) {
        for (j = 1; j <= adim2; ++j)
#ifdef _WIN32
            scanf_s(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#else
            scanf(" ( %lf , %lf )", &A(i, j).re, &A(i, j).im);
#endif
    }
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
    }
    /* Input matrix C. */
    if (uplo == Nag_Upper) {
        for (i = 1; i <= n; ++i) {
            for (j = i; j <= n; ++j)
#ifdef _WIN32
                scanf_s(" ( %lf , %lf )", &C(i, j).re, &C(i, j).im);
#else
                scanf(" ( %lf , %lf )", &C(i, j).re, &C(i, j).im);
#endif
            }
    }
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
    }
    else {
        for (i = 1; i <= n; ++i) {
            for (j = 1; j <= i; ++j)

```

```

#ifdef _WIN32
    scanf_s(" ( %lf , %lf )", &C(i, j).re, &C(i, j).im);
#else
    scanf(" ( %lf , %lf )", &C(i, j).re, &C(i, j).im);
#endif
}
#ifdef _WIN32
    scanf_s("%*[^\\n] ");
#else
    scanf("%*[^\\n] ");
#endif
}

/* nag_zsyk (f16zuc).
 * Rank k update of complex symmetric matrix.
 */
nag_zsyk(order, uplo, trans, n, k, alpha, a, pda, beta, c, pdc, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_zsyk (f16zuc).\\n%s\\n", fail.message);
    exit_status = 1;
    goto END;
}
if (uplo == Nag_Upper) {
    matrix = Nag_UpperMatrix;
}
else {
    matrix = Nag_LowerMatrix;
}
/* Print updated matrix C */
/* nag_gen_complx_mat_print_comp (x04dbc).
 * Print complex general matrix (comprehensive)
 */
fflush(stdout);
nag_gen_complx_mat_print_comp(order, matrix, Nag_NonUnitDiag, n, n, c,
                              pdc, Nag_BracketForm, "%6.2f",
                              "Updated Matrix C", Nag_IntegerLabels,
                              0, Nag_IntegerLabels, 0, 80, 0, 0, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_gen_complx_mat_print_comp (x04dbc).\\n%s"
           "\\n", fail.message);
    exit_status = 1;
    goto END;
}
END:
    NAG_FREE(a);
    NAG_FREE(c);

    return exit_status;
}

```

10.2 Program Data

```

nag_zsyk (f16zuc) Example Program Data
4 2 :Values of n and k
Nag_Lower :Value of uplo
Nag_NoTrans :Value of trans
( -1.0, 1.0) :Value of alpha
( 1.0, 0.0) :Value of beta
( 1.7, -2.3) ( -1.8, 2.4)
( 2.9, -2.1) ( 1.2, 1.4)
( -2.9, 1.0) ( 0.6, 0.8)
( 1.5, 0.9) ( -1.4, -1.7) :End of matrix A
( 4.78, 1.03)
( 2.00,-0.30) (-4.11,-2.30)
( 2.89,-1.34) ( 2.36,-4.25) ( 4.15, 0.57)
(-1.89, 1.15) ( 0.04,-3.69) (-0.02, 0.46) ( 0.33,-1.91) :End of matrix C

```

10.3 Program Results

nag_zsyrk (f16zuc) Example Program Results

Updated Matrix C

	1	2	3	4
1	(26.16, 12.57)			
2	(17.30, 4.16)	(1.23, 10.00)		
3	(0.15, -15.34)	(-1.72, -21.75)	(1.86, 12.54)	
4	(-10.89, 14.59)	(-2.36, 7.79)	(7.96, -1.02)	(-7.64, -8.86)
