

NAG Library Function Document

nag_cov_to_corr (g02bwc)

1 Purpose

nag_cov_to_corr (g02bwc) calculates a matrix of Pearson product-moment correlation coefficients from sums of squares and cross-products of deviations about the mean.

2 Specification

```
#include <nag.h>
#include <nagg02.h>

void nag_cov_to_corr (Integer m, double r[], NagError *fail)
```

3 Description

nag_cov_to_corr (g02bwc) calculates a matrix of Pearson product-moment correlation coefficients from sums of squares and cross-products about the mean for observations on m variables which can be computed by a single call to nag_sum_sqs (g02buc) or a series of calls to nag_sum_sqs_update (g02btc). The sums of squares and cross-products are stored in an array packed by column and are overwritten by the correlation coefficients.

Let c_{jk} be the cross-product of deviations from the mean, for $j = 1, 2, \dots, m$ and $k = j, \dots, m$, then the product-moment correlation coefficient, r_{jk} is given by

$$r_{jk} = \frac{c_{jk}}{\sqrt{c_{jj}c_{kk}}}.$$

4 References

None.

5 Arguments

- 1: **m** – Integer *Input*
On entry: m , the number of variables.
Constraint: $m \geq 1$.
- 2: **r**[(**m** × **m** + **m**)/2] – double *Input/Output*
On entry: contains the upper triangular part of the sums of squares and cross-products matrix of deviations from the mean. These are stored packed by column, i.e., the cross-product between variable j and k , $k \geq j$, is stored in **r**[($k \times (k - 1)/2 + j - 1$)].
On exit: the Pearson product-moment correlation coefficients.
 These are stored packed by column corresponding to the input cross-products.
- 3: **fail** – NagError * *Input/Output*
 The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, $m = \langle value \rangle$.

Constraint: $m \geq 1$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

NE_ZERO_VARIANCE

On entry, a variable has zero variance.

7 Accuracy

The accuracy of nag_cov_to_corr (g02bwc) is entirely dependent upon the accuracy of the elements of array **r**.

8 Parallelism and Performance

nag_cov_to_corr (g02bwc) is not threaded in any implementation.

9 Further Comments

nag_cov_to_corr (g02bwc) may also be used to calculate the correlations between parameter estimates from the variance-covariance matrix of the parameter estimates as is given by several functions in this chapter.

10 Example

A program to calculate the correlation matrix from raw data. The sum of squares and cross-products about the mean are calculated from the raw data by a call to nag_sum_sqs (g02buc). The correlation matrix is then calculated from these values.

10.1 Program Text

```

/* nag_cov_to_corr (g02bwc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <stdio.h>
#include <string.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg02.h>
#include <nagx04.h>

int main(void)
{
    /* Arrays */
    char nag_enum_mean[40], nag_enum_weight[40];
    double *c = 0, *wmean = 0, *wt = 0, *x = 0;
    double *wtpttr = 0;
    /* Scalars */
    double sw;
    Integer exit_status, j, k, m, n, pdx;
    Nag_OrderType order;
    Nag_SumSquare mean;
    Nag_Boolean weight;
    NagError fail;

#ifdef NAG_LOAD_FP
    /* The following line is needed to force the Microsoft linker
       to load floating point support */
    float force_loading_of_ms_float_support = 0;
#endif /* NAG_LOAD_FP */

#ifdef NAG_COLUMN_MAJOR
#define X(I, J) x[(J-1)*pdx + I - 1]
    order = Nag_ColMajor;
#else
#define X(I, J) x[(I-1)*pdx + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);

    exit_status = 0;
    printf("nag_cov_to_corr (g02bwc) Example Program Results\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif

#ifdef _WIN32
    while (scanf_s("%39s %39s %" NAG_IFMT "%" NAG_IFMT "%*[\n]", nag_enum_mean,
        (unsigned)_countof(nag_enum_mean), nag_enum_weight,
        (unsigned)_countof(nag_enum_weight), &m, &n) != EOF) {
#else
    while (scanf("%39s %39s %" NAG_IFMT "%" NAG_IFMT "%*[\n]",
        nag_enum_mean, nag_enum_weight, &m, &n) != EOF) {
#endif
        /* nag_enum_name_to_value (x04nac).
         * Converts NAG enum member name to value
         */
        mean = (Nag_SumSquare) nag_enum_name_to_value(nag_enum_mean);
        weight = (Nag_Boolean) nag_enum_name_to_value(nag_enum_weight);

```

```

/* Allocate memory */
if (!(c = NAG_ALLOC((m * (m + 1)) / 2, double)) ||
    !(wmean = NAG_ALLOC(m, double)) ||
    !(wt = NAG_ALLOC(n, double)) || !(x = NAG_ALLOC(n * m, double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}
#ifdef NAG_COLUMN_MAJOR
    pdx = n;
#else
    pdx = m;
#endif
for (j = 1; j <= n; ++j)
#ifdef _WIN32
    scanf_s("%lf", &wt[j - 1]);
#else
    scanf("%lf", &wt[j - 1]);
#endif
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif

    for (j = 1; j <= n; ++j) {
        for (k = 1; k <= m; ++k)
#ifdef _WIN32
            scanf_s("%lf", &X(j, k));
#else
            scanf("%lf", &X(j, k));
#endif
    }
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif

    if (weight)
        wtptr = wt;

/* Calculate the sums of squares and cross-products matrix */
/* nag_sum_sqs (g02buc).
 * Computes a weighted sum of squares matrix
 */
nag_sum_sqs(order, mean, n, m, x, pdx, wtptr, &sw, wmean, c, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_sum_sqs (g02buc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Calculate the correlation matrix */
/* nag_cov_to_corr (g02bwc).
 * Computes a correlation matrix from a sum of squares
 * matrix
 */
nag_cov_to_corr(m, c, &fail);

/* Print the correlation matrix */
if (fail.code == NE_NOERROR) {
    printf("\n");
    /* nag_pack_real_mat_print (x04ccc).
     * Print real packed triangular matrix (easy-to-use)
     */
    fflush(stdout);
    nag_pack_real_mat_print(Nag_ColMajor, Nag_Upper, Nag_NonUnitDiag, m,
                           c, "Correlation matrix", 0, &fail);
    if (fail.code != NE_NOERROR) {

```

```

        printf("Error from nag_pack_real_mat_print (x04ccc).\n%s\n",
               fail.message);
        exit_status = 1;
        goto END;
    }
}
else if (fail.code == NE_ZERO_VARIANCE) {
    printf("\n");
    printf("NOTE: some variances are zero\n\n");
    /* nag_pack_real_mat_print (x04ccc), see above. */
    fflush(stdout);
    nag_pack_real_mat_print(Nag_ColMajor, Nag_Upper, Nag_NonUnitDiag, m,
                           c, "Correlation matrix", 0, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_pack_real_mat_print (x04ccc).\n%s\n",
               fail.message);
        exit_status = 1;
        goto END;
    }
}
else {
    printf("Error from nag_cov_to_corr (g02bwc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

NAG_FREE(c);
NAG_FREE(wmean);
NAG_FREE(wt);
NAG_FREE(x);
}

END:
    NAG_FREE(c);
    NAG_FREE(wmean);
    NAG_FREE(wt);
    NAG_FREE(x);

    return exit_status;
}

```

10.2 Program Data

nag_cov_to_corr (g02bwc) Example Program Data

Nag_AboutMean	Nag_TRUE	3	3
0.1300	1.3070	0.3700	
9.1231	3.7011	4.5230	
0.9310	0.0900	0.8870	
0.0009	0.0099	0.0999	

10.3 Program Results

nag_cov_to_corr (g02bwc) Example Program Results

Correlation matrix			
	1	2	3
1	1.0000	0.9908	0.9903
2		1.0000	0.9624
3			1.0000
