

## NAG Library Function Document

### nag\_rand\_gen\_discrete (g05tdc)

#### 1 Purpose

nag\_rand\_gen\_discrete (g05tdc) generates a vector of pseudorandom integers from a discrete distribution with a given PDF (probability density function) or CDF (cumulative distribution function)  $p$ .

#### 2 Specification

```
#include <nag.h>
#include <nagg05.h>

void nag_rand_gen_discrete (Nag_ModeRNG mode, Integer n, const double p[],
    Integer np, Integer ip1, Nag_DiscreteDistrib itype, double r[],
    Integer lr, Integer state[], Integer x[], NagError *fail)
```

#### 3 Description

nag\_rand\_gen\_discrete (g05tdc) generates a sequence of  $n$  integers  $x_i$ , from a discrete distribution defined by information supplied in **p**. This may either be the PDF or CDF of the distribution. A reference vector is first set up to contain the CDF of the distribution in its higher elements, followed by an index.

Setting up the reference vector and subsequent generation of variates can each be performed by separate calls to nag\_rand\_gen\_discrete (g05tdc) or may be combined in a single call.

One of the initialization functions nag\_rand\_init\_repeatable (g05kfc) (for a repeatable sequence if computed sequentially) or nag\_rand\_init\_nonrepeatable (g05kgc) (for a non-repeatable sequence) must be called prior to the first call to nag\_rand\_gen\_discrete (g05tdc).

#### 4 References

Kendall M G and Stuart A (1969) *The Advanced Theory of Statistics (Volume 1)* (3rd Edition) Griffin

Knuth D E (1981) *The Art of Computer Programming (Volume 2)* (2nd Edition) Addison–Wesley

#### 5 Arguments

1: **mode** – Nag\_ModeRNG *Input*

*On entry:* a code for selecting the operation to be performed by the function.

**mode** = Nag\_InitializeReference  
Set up reference vector only.

**mode** = Nag\_GenerateFromReference  
Generate variates using reference vector set up in a prior call to nag\_rand\_gen\_discrete (g05tdc).

**mode** = Nag\_InitializeAndGenerate  
Set up reference vector and generate variates.

**mode** = Nag\_GenerateWithoutReference  
Generate variates without using the reference vector.

*C o n s t r a i n t :* **mode** = Nag\_InitializeReference, Nag\_GenerateFromReference,  
Nag\_InitializeAndGenerate or Nag\_GenerateWithoutReference.

- 2: **n** – Integer *Input*  
*On entry:*  $n$ , the number of pseudorandom numbers to be generated.  
*Constraint:*  $n \geq 0$ .
- 3: **p[np]** – const double *Input*  
*On entry:* the PDF or CDF of the distribution.  
*Constraints:*  
 $0.0 \leq p[i-1] \leq 1.0$ , for  $i = 1, 2, \dots, np$ ;  
if **itype** = Nag\_PDF,  $\sum_{i=1}^{np} p[i-1] = 1.0$ ;  
if **itype** = Nag\_CDF,  $p[i-1] < p[j-1]$ ,  $i < j$  and  $p[np-1] = 1.0$ .
- 4: **np** – Integer *Input*  
*On entry:* the number of values supplied in **p** defining the PDF or CDF of the discrete distribution.  
*Constraint:*  $np > 0$ .
- 5: **ip1** – Integer *Input*  
*On entry:* the value of the variate, a whole number, to which the probability in **p**[0] corresponds.
- 6: **itype** – Nag\_DiscreteDistrib *Input*  
*On entry:* indicates the type of information contained in **p**.  
**itype** = Nag\_PDF  
**p** contains a probability distribution function (PDF).  
**itype** = Nag\_CDF  
**p** contains a cumulative distribution function (CDF).  
*Constraint:* **itype** = Nag\_PDF or Nag\_CDF.
- 7: **r[lr]** – double *Communication Array*  
*On entry:* if **mode** = Nag\_GenerateFromReference, the reference vector from the previous call to nag\_rand\_gen\_discrete (g05tdc).  
*On exit:* the reference vector.
- 8: **lr** – Integer *Input*  
*On entry:* the dimension of the array **r**.  
*Suggested value:*  
if **mode**  $\neq$  Nag\_GenerateWithoutReference,  $lr = 10 + 1.4 \times np$  approximately (for optimum efficiency in generating variates);  
otherwise **lr** = 1.  
*Constraints:*  
if **mode** = Nag\_InitializeReference or Nag\_InitializeAndGenerate,  $lr \geq np + 8$ ;  
if **mode** = Nag\_GenerateFromReference, **lr** should remain unchanged from the previous call to nag\_rand\_gen\_discrete (g05tdc).
- 9: **state[dim]** – Integer *Communication Array*  
**Note:** the dimension, *dim*, of this array is dictated by the requirements of associated functions that must have been previously called. This array MUST be the same array passed as argument

**state** in the previous call to nag\_rand\_init\_repeatable (g05kfc) or nag\_rand\_init\_nonrepeatable (g05kgc).

*On entry:* contains information on the selected base generator and its current state.

*On exit:* contains updated information on the state of the generator.

10: **x[n]** – Integer *Output*

*On exit:* contains  $n$  pseudorandom numbers from the specified discrete distribution.

11: **fail** – NagError \* *Input/Output*

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

### NE\_BAD\_PARAM

On entry, argument  $\langle value \rangle$  had an illegal value.

### NE\_INT

On entry, **lr** is too small when **mode** = Nag\_InitializeReference or Nag\_InitializeAndGenerate: **lr** =  $\langle value \rangle$ , minimum length required =  $\langle value \rangle$ .

On entry, **n** =  $\langle value \rangle$ .

Constraint: **n**  $\geq 0$ .

On entry, **np** =  $\langle value \rangle$ .

Constraint: **np**  $> 0$ .

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

### NE\_INVALID\_STATE

On entry, **state** vector has been corrupted or not initialized.

### NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

### NE\_PREV\_CALL

The value of **np** or **ip1** is not the same as when **r** was set up in a previous call.

Previous value of **np** =  $\langle value \rangle$  and **np** =  $\langle value \rangle$ .

Previous value of **ip1** =  $\langle value \rangle$  and **ip1** =  $\langle value \rangle$ .

### NE\_REAL\_ARRAY

On entry, at least one element of the vector **p** is less than 0.0 or greater than 1.0.

On entry, **itype** = Nag\_CDF and the values of **p** are not all in strictly ascending order.

On entry, **itype** = Nag\_PDF and the sum of the elements of **p** do not equal one.

On entry, **p**[**np** - 1] = *value*.

Constraint: if **itype** = Nag\_CDF, **p**[**np** - 1] = 1.0.

## NE\_REF\_VEC

On entry, some of the elements of the array **r** have been corrupted or have not been initialized.

## 7 Accuracy

Not applicable.

## 8 Parallelism and Performance

nag\_rand\_gen\_discrete (g05tdc) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

None.

## 10 Example

This example prints 20 pseudorandom variates from a discrete distribution whose PDF,  $p$ , is defined as follows:

$n$	$p$
-5	0.01
-4	0.02
-3	0.04
-2	0.08
-1	0.20
0	0.30
1	0.20
2	0.08
3	0.04
4	0.02
5	0.01

The reference vector is set up and the variates are generated by a single call to nag\_rand\_gen\_discrete (g05tdc), after initialization by nag\_rand\_init\_repeatable (g05kfc).

### 10.1 Program Text

```
/* nag_rand_gen_discrete (g05tdc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */
/* Pre-processor includes */
#include <stdio.h>
#include <math.h>
#include <nag.h>
```

```

#include <nag_stdlib.h>
#include <nagg05.h>

int main(void)
{
    /* Integer scalar and array declarations */
    Integer exit_status = 0;
    Integer i, lr, lstate;
    Integer *state = 0, *x = 0;

    /* NAG structures */
    NagError fail;
    Nag_ModeRNG mode;

    /* Double scalar and array declarations */
    double *r = 0;

    /* Set the distribution parameters */
    Integer np = 11;
    Nag_DiscreteDistrib itype = Nag_PDF;
    double p[] = { 0.010e0, 0.020e0, 0.040e0, 0.080e0, 0.20e0,
        0.30e0, 0.20e0, 0.080e0, 0.040e0, 0.020e0,
        0.010e0
    };
    Integer ip1 = -5;

    /* Set the sample size */
    Integer n = 20;

    /* Choose the base generator */
    Nag_BaseRNG genid = Nag_Basic;
    Integer subid = 0;

    /* Set the seed */
    Integer seed[] = { 1762543 };
    Integer lseed = 1;

    /* Initialize the error structure */
    INIT_FAIL(fail);

    printf("nag_rand_gen_discrete (g05tdc) Example Program Results\n\n");

    /* Get the length of the state array */
    lstate = -1;
    nag_rand_init_repeatable(genid, subid, seed, lseed, state, &lstate, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
            fail.message);
        exit_status = 1;
        goto END;
    }

    /* Calculate the size of the reference vector */
    lr = 10 + 1.4 * np;

    /* Allocate arrays */
    if (!(r = NAG_ALLOC(lr, double)) ||
        !(state = NAG_ALLOC(lstate, Integer)) || !(x = NAG_ALLOC(n, Integer)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Initialize the generator to a repeatable sequence */
    nag_rand_init_repeatable(genid, subid, seed, lseed, state, &lstate, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_rand_init_repeatable (g05kfc).\n%s\n",
            fail.message);
        exit_status = 1;
        goto END;
    }

```

```
    }

    /* Generate the variates, initializing the reference
       vector at the same time */
    mode = Nag_InitializeAndGenerate;
    nag_rand_gen_discrete(mode, n, p, np, ipl, itype, r, lr, state, x, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_rand_gen_discrete (g05tdc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }

    /* Display the variates */
    for (i = 0; i < n; i++)
        printf("%12" NAG_IFMT "\n", x[i]);

END:
    NAG_FREE(r);
    NAG_FREE(state);
    NAG_FREE(x);

    return exit_status;
}
```

## 10.2 Program Data

None.

## 10.3 Program Results

nag\_rand\_gen\_discrete (g05tdc) Example Program Results

```
0
-2
1
1
-2
0
0
1
0
1
-3
-1
0
-3
0
-1
-1
5
2
0
```

---