

NAG Library Function Document

nag_complex_bessel_k (s18dcc)

1 Purpose

nag_complex_bessel_k (s18dcc) returns a sequence of values for the modified Bessel functions $K_{\nu+n}(z)$ for complex z , non-negative ν and $n = 0, 1, \dots, N-1$, with an option for exponential scaling.

2 Specification

```
#include <nag.h>
#include <nags.h>

void nag_complex_bessel_k (double fnu, Complex z, Integer n,
    Nag_ScaleResType scal, Complex cy[], Integer *nz, NagError *fail)
```

3 Description

nag_complex_bessel_k (s18dcc) evaluates a sequence of values for the modified Bessel function $K_\nu(z)$, where z is complex, $-\pi < \arg z \leq \pi$, and ν is the real, non-negative order. The N -member sequence is generated for orders $\nu, \nu+1, \dots, \nu+N-1$. Optionally, the sequence is scaled by the factor e^z .

The function is derived from the function CBESK in Amos (1986).

Note: although the function may not be called with ν less than zero, for negative orders the formula $K_{-\nu}(z) = K_\nu(z)$ may be used.

When N is greater than 1, extra values of $K_\nu(z)$ are computed using recurrence relations.

For very large $|z|$ or $(\nu + N - 1)$, argument reduction will cause total loss of accuracy, and so no computation is performed. For slightly smaller $|z|$ or $(\nu + N - 1)$, the computation is performed but results are accurate to less than half of *machine precision*. If $|z|$ is very small, near the machine underflow threshold, or $(\nu + N - 1)$ is too large, there is a risk of overflow and so no computation is performed. In all the above cases, a warning is given by the function.

4 References

Abramowitz M and Stegun I A (1972) *Handbook of Mathematical Functions* (3rd Edition) Dover Publications

Amos D E (1986) Algorithm 644: A portable package for Bessel functions of a complex argument and non-negative order *ACM Trans. Math. Software* **12** 265–273

5 Arguments

- 1: **fnu** – double *Input*
On entry: ν , the order of the first member of the sequence of functions.
Constraint: **fnu** ≥ 0.0 .
- 2: **z** – Complex *Input*
On entry: the argument z of the functions.
Constraint: **z** $\neq (0.0, 0.0)$.

- 3: **n** – Integer *Input*
On entry: N , the number of members required in the sequence $K_\nu(z), K_{\nu+1}(z), \dots, K_{\nu+N-1}(z)$.
Constraint: $n \geq 1$.
- 4: **scal** – Nag_ScaleResType *Input*
On entry: the scaling option.
scal = Nag_UnscaleRes
The results are returned unscaled.
scal = Nag_ScaleRes
The results are returned scaled by the factor e^z .
Constraint: **scal** = Nag_UnscaleRes or Nag_ScaleRes.
- 5: **cy[n]** – Complex *Output*
On exit: the N required function values: **cy**[$i - 1$] contains $K_{\nu+i-1}(z)$, for $i = 1, 2, \dots, N$.
- 6: **nz** – Integer * *Output*
On exit: the number of components of **cy** that are set to zero due to underflow. If **nz** > 0 and $\text{Re}(z) \geq 0.0$, elements **cy**[0], **cy**[1], \dots , **cy**[**nz** - 1] are set to zero. If $\text{Re}(z) < 0.0$, **nz** simply states the number of underflows, and not which elements they are.
- 7: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_COMPLEX_ZERO

On entry, $z = (0.0, 0.0)$.

NE_INT

On entry, **n** = $\langle value \rangle$.

Constraint: $n \geq 1$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

NE_OVERFLOW_LIKELY

No computation because $|z| = \langle value \rangle < \langle value \rangle$.

No computation because $fnu + n - 1 = \langle value \rangle$ is too large.

NE_REAL

On entry, $fnu = \langle value \rangle$.

Constraint: $fnu \geq 0.0$.

NE_TERMINATION_FAILURE

No computation – algorithm termination condition not met.

NE_TOTAL_PRECISION_LOSS

No computation because $|z| = \langle value \rangle > \langle value \rangle$.

No computation because $fnu + n - 1 = \langle value \rangle > \langle value \rangle$.

NW_SOME_PRECISION_LOSS

Results lack precision because $|z| = \langle value \rangle > \langle value \rangle$.

Results lack precision because $fnu + n - 1 = \langle value \rangle > \langle value \rangle$.

7 Accuracy

All constants in `nag_complex_bessel_k` (s18dcc) are given to approximately 18 digits of precision. Calling the number of digits of precision in the floating-point arithmetic being used t , then clearly the maximum number of correct digits in the results obtained is limited by $p = \min(t, 18)$. Because of errors in argument reduction when computing elementary functions inside `nag_complex_bessel_k` (s18dcc), the actual number of correct digits is limited, in general, by $p - s$, where $s \approx \max(1, |\log_{10} |z||, |\log_{10} \nu|)$ represents the number of digits lost due to the argument reduction. Thus the larger the values of $|z|$ and ν , the less the precision in the result. If `nag_complex_bessel_k` (s18dcc) is called with $n > 1$, then computation of function values via recurrence may lead to some further small loss of accuracy.

If function values which should nominally be identical are computed by calls to `nag_complex_bessel_k` (s18dcc) with different base values of ν and different n , the computed values may not agree exactly. Empirical tests with modest values of ν and z have shown that the discrepancy is limited to the least significant 3 – 4 digits of precision.

8 Parallelism and Performance

`nag_complex_bessel_k` (s18dcc) is not threaded in any implementation.

9 Further Comments

The time taken for a call of `nag_complex_bessel_k` (s18dcc) is approximately proportional to the value of n , plus a constant. In general it is much cheaper to call `nag_complex_bessel_k` (s18dcc) with n greater than 1, rather than to make N separate calls to `nag_complex_bessel_k` (s18dcc).

Paradoxically, for some values of z and ν , it is cheaper to call `nag_complex_bessel_k` (s18dcc) with a larger value of n than is required, and then discard the extra function values returned. However, it is not possible to state the precise circumstances in which this is likely to occur. It is due to the fact that the base value used to start recurrence may be calculated in different regions for different n , and the costs in each region may differ greatly.

Note that if the function required is $K_0(x)$ or $K_1(x)$, i.e., $\nu = 0.0$ or 1.0 , where x is real and positive, and only a single function value is required, then it may be much cheaper to call `nag_bessel_k0`

(s18acc), nag_bessel_k1 (s18adc), nag_bessel_k0_scaled (s18ccc) or nag_bessel_k1_scaled (s18cdc), depending on whether a scaled result is required or not.

10 Example

The example program prints a caption and then proceeds to read sets of data from the input data stream. The first datum is a value for the order **fnu**, the second is a complex value for the argument, **z**, and the third is a character value used as a flag to set the argument **scal**. The program calls the function with **n = 2** to evaluate the function for orders **fnu** and **fnu + 1**, and it prints the results. The process is repeated until the end of the input data stream is encountered.

10.1 Program Text

```

/* nag_complex_bessel_k (s18dcc) Example Program.
 *
 * NAGPRODCODE Version.
 *
 * Copyright 2016 Numerical Algorithms Group.
 *
 * Mark 26, 2016.
 */

#include <nag.h>
#include <stdio.h>
#include <nag_stdlib.h>
#include <nags.h>

int main(void)
{
    Integer exit_status = 0;
    Complex z, cy[2];
    double fnu;
    const Integer n = 2;
    Integer nz;
    char nag_enum_arg[40];
    Nag_ScaleResType scal;
    NagError fail;

    INIT_FAIL(fail);

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n]");
#else
    scanf("%*[\n]");
#endif
    printf("nag_complex_bessel_k (s18dcc) Example Program Results\n");
    printf("Calling with n = %" NAG_IFMT "\n", n);
    printf("      fnu      z      scal      cy[0]"
           "      cy[1]      nz\n");
#ifdef _WIN32
    while (scanf_s(" %lf (%lf,%lf) %39s%[\n] ", &fnu, &z.re, &z.im,
                  nag_enum_arg, (unsigned)_countof(nag_enum_arg)) != EOF) {
#else
    while (scanf(" %lf (%lf,%lf) %39s%[\n] ", &fnu, &z.re, &z.im,
                nag_enum_arg) != EOF) {
#endif
        /* nag_enum_name_to_value (x04nac).
         * Converts NAG enum member name to value
         */
        scal = (Nag_ScaleResType) nag_enum_name_to_value(nag_enum_arg);

        /* nag_complex_bessel_k (s18dcc).
         * Modified Bessel functions K_(nu+a)(z), real a >= 0,
         * complex z, nu = 0,1,2,...
         */
        nag_complex_bessel_k(fnu, z, n, scal, cy, &nz, &fail);
        if (fail.code != NE_NOERROR) {

```

```

        printf("Error from nag_complex_bessel_k (s18dcc).\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    printf("%7.4f (%7.3f,%7.3f) %-14s (%7.3f,%7.3f) (%7.3f,%7.3f) "
           "%\" NAG_IFMT "\n", fnu, z.re, z.im, nag_enum_arg, cy[0].re,
           cy[0].im, cy[1].re, cy[1].im, nz);
}

END:

    return exit_status;
}

```

10.2 Program Data

nag_complex_bessel_k (s18dcc) Example Program Data

0.00	(0.3, 0.4)	Nag_UnscaleRes	
2.30	(2.0, 0.0)	Nag_UnscaleRes	
2.12	(-1.0, 0.0)	Nag_UnscaleRes	
5.10	(3.0, 2.0)	Nag_UnscaleRes	
5.10	(3.0, 2.0)	Nag_ScaleRes	- Values of fnu, z and scal

10.3 Program Results

nag_complex_bessel_k (s18dcc) Example Program Results

Calling with n = 2

fnu	z	scal	cy[0]	cy[1]	nz
0.0000	(0.300, 0.400)	Nag_UnscaleRes	(0.831, -0.803)	(0.831, -1.735)	0
2.3000	(2.000, 0.000)	Nag_UnscaleRes	(0.325, 0.000)	(0.909, 0.000)	0
2.1200	(-1.000, 0.000)	Nag_UnscaleRes	(1.763, -1.047)	(-8.087, 3.147)	0
5.1000	(3.000, 2.000)	Nag_UnscaleRes	(-0.426, 0.243)	(-0.810, 1.255)	0
5.1000	(3.000, 2.000)	Nag_ScaleRes	(-0.880, -9.803)	(-16.150, -25.293)	0
