

NAG Library Routine Document

F01VCF (DTPTR)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F01VCF (DTPTR) unpacks a real triangular matrix, stored in a standard packed format array, to a full format array.

2 Specification

```
SUBROUTINE F01VCF (UPLO, N, AP, A, LDA, INFO)
  INTEGER          N, LDA, INFO
  REAL (KIND=nag_wp) AP(N*(N+1)/2), A(LDA,*)
  CHARACTER(1)     UPLO
```

The routine may be called by its LAPACK name *dtptr*.

3 Description

F01VCF (DTPTR) unpacks a real n by n triangular matrix A , stored in an array of length $n(n+1)/2$, to conventional storage in a full format array. This routine is intended for possible use in conjunction with routines from Chapters F06, F07, F08 and F16 where some routines use triangular matrices stored in the packed form. Packed storage format is described in Section 3.3.2 in the F07 Chapter Introduction.

4 References

None.

5 Arguments

- | | | |
|----|--|--------------|
| 1: | UPLO – CHARACTER(1)
<i>On entry:</i> specifies whether A is upper or lower triangular.
UPLO = 'U'
A is upper triangular.
UPLO = 'L'
A is lower triangular.
<i>Constraint:</i> UPLO = 'U' or 'L'. | <i>Input</i> |
| 2: | N – INTEGER
<i>On entry:</i> n , the order of the matrix A .
<i>Constraint:</i> $N \geq 0$. | <i>Input</i> |
| 3: | AP($N \times (N+1)/2$) – REAL (KIND=nag_wp) array
<i>On entry:</i> the n by n triangular matrix A , packed by columns.
More precisely, | <i>Input</i> |

if UPLO = 'U', the upper triangle of A must be stored with element A_{ij} in $AP(i + j(j - 1)/2)$ for $i \leq j$;

if UPLO = 'L', the lower triangle of A must be stored with element A_{ij} in $AP(i + (2n - j)(j - 1)/2)$ for $i \geq j$.

4: A(LDA,*) – REAL (KIND=nag_wp) array

Output

Note: the second dimension of the array A must be at least N.

On exit: the triangular matrix A .

If UPLO = 'U', A is upper triangular and the elements of the array below the diagonal are not referenced.

If UPLO = 'L', A is lower triangular and the elements of the array above the diagonal are not referenced.

5: LDA – INTEGER

Input

On entry: the first dimension of the array A as declared in the (sub)program from which F01VCF (DTPTR) is called.

Constraint: $LDA \geq \max(1, N)$.

6: INFO – INTEGER

Output

On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

Not applicable.

8 Parallelism and Performance

F01VCF (DTPTR) is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example reads in a triangular matrix packed by columns and unpacks it to full format.

10.1 Program Text

```
Program f01vcfe
```

```
!      F01VCF Example Program Text
```

```
!      Mark 26 Release. NAG Copyright 2016.
```

```
!      .. Use Statements ..
```

```
      Use nag_library, Only: dtpttr, nag_wp, x04cbf
```

```
!      .. Implicit None Statement ..
```

```

Implicit None
! .. Parameters ..
Integer, Parameter      :: incl = 1, indent = 0, ncols = 80,      &
                          nin = 5, nout = 6
Character (1), Parameter      :: diag = 'N', intlabel = 'I',      &
                          matrix = 'G', nolabel = 'N'
Character (4), Parameter      :: form = 'F5.2'
! .. Local Scalars ..
Integer      :: i, ifail, info, lda, lenap, n
Character (18)      :: title
Character (1)      :: uplo
! .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: a(:, :), ap(:)
Character (1)      :: clabs(1), rlabs(1)
! .. Executable Statements ..
Write (nout,*) 'F01VCF Example Program Results'
! Skip heading in data file
Read (nin,*)
Write (nout,*)
Flush (nout)
Read (nin,*) n, uplo
lda = n
lenap = (n*(n+1))/2
Allocate (a(lda,n),ap(lenap))

! Read a packed vector of order n
Do i = 1, lenap
  Read (nin,*) ap(i)
End Do

! Print the packed vector
title = 'Packed Matrix AP: '
ifail = 0
Call x04cbf(matrix,diag,lenap,incl,ap,lenap,form,title,intlabel,rlabs,      &
  nolabel,clabs,ncols,indent,ifail)

Write (nout,*)
Flush (nout)

! Convert to triangular form
! The NAG name equivalent of dtptr is f01vcf
Call dtptr(uplo,n,ap,a,lda,info)

! Print the unpacked matrix
title = 'Unpacked Matrix A:'
ifail = 0
Call x04cbf(uplo,diag,n,n,a,lda,form,title,intlabel,rlabs,intlabel,      &
  clabs,ncols,indent,ifail)

End Program f01vcfe

```

10.2 Program Data

F01VCF Example Program Data

```

4 'U'      : n, uplo
1.1        : Packed Matrix AP
1.2
2.2
1.3
2.3
3.3
1.4
2.4
3.4
4.4

```

10.3 Program Results

F01VCF Example Program Results

Packed Matrix AP:

```
1  1.10
2  1.20
3  2.20
4  1.30
5  2.30
6  3.30
7  1.40
8  2.40
9  3.40
10 4.40
```

Unpacked Matrix A:

```
      1      2      3      4
1  1.10  1.20  1.30  1.40
2      2.20  2.30  2.40
3      3.30  3.40
4
```
