

NAG Library Routine Document

F01VLF (DTFTTP)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F01VLF (DTFTTP) copies a real triangular matrix, stored in a Rectangular Full Packed (RFP) format array, to a standard packed format array.

2 Specification

```
SUBROUTINE F01VLF (TRANSR, UPLO, N, AR, AP, INFO)
  INTEGER          N, INFO
  REAL (KIND=nag_wp) AR(N*(N+1)/2), AP(N*(N+1)/2)
  CHARACTER(1)     TRANSR, UPLO
```

The routine may be called by its LAPACK name *dtfttp*.

3 Description

F01VLF (DTFTTP) packs a real n by n triangular matrix A , stored in RFP format, to packed format. This routine is intended for possible use in conjunction with routines from Chapters F06, F07 and F16 where some routines that use triangular matrices store them in RFP format. The RFP storage format is described in Section 3.3.3 in the F07 Chapter Introduction and the packed storage format is described in Section 3.3.2 in the F07 Chapter Introduction.

4 References

Gustavson F G, Waśniewski J, Dongarra J J and Langou J (2010) Rectangular full packed format for Cholesky's algorithm: factorization, solution, and inversion *ACM Trans. Math. Software* **37**, 2

5 Arguments

- 1: TRANSR – CHARACTER(1) *Input*
On entry: specifies whether the normal RFP representation of A or its transpose is stored.
 TRANSR = 'N'
 The RFP representation of the matrix A is stored.
 TRANSR = 'T'
 The transpose of the RFP representation of the matrix A is stored.
Constraint: TRANSR = 'N' or 'T'.
- 2: UPLO – CHARACTER(1) *Input*
On entry: specifies whether A is upper or lower triangular.
 UPLO = 'U'
 A is upper triangular.
 UPLO = 'L'
 A is lower triangular.
Constraint: UPLO = 'U' or 'L'.

- 3: N – INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.
- 4: AR($N \times (N + 1)/2$) – REAL (KIND=nag_wp) array *Input*
On entry: the upper or lower n by n triangular matrix A (as specified by UPLO) in either normal or transposed RFP format (as specified by TRANSR). The storage format is described in Section 3.3.3 in the F07 Chapter Introduction.
- 5: AP($N \times (N + 1)/2$) – REAL (KIND=nag_wp) array *Output*
On exit: the n by n triangular matrix A , packed by columns.
 More precisely,
 if UPLO = 'U', the upper triangle of A is stored with element A_{ij} in AP($i + j(j - 1)/2$) for $i \leq j$;
 if UPLO = 'L', the lower triangle of A is stored with element A_{ij} in AP($i + (2n - j)(j - 1)/2$) for $i \geq j$.
- 6: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

$-999 < \text{INFO} < 0$

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO = -999

Dynamic memory allocation failed.

See Section 3.7 in *How to Use the NAG Library and its Documentation* for further information.

7 Accuracy

Not applicable.

8 Parallelism and Performance

F01VLF (DTFTTP) is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example reads in a triangular matrix in RFP format and copies it to packed format.

10.1 Program Text

```

Program f01vlf

!      F01VLF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
      Use nag_library, Only: dtfttp, nag_wp, x04cbf
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: incl = 1, indent = 0, ncols = 80,      &
                                   nin = 5, nout = 6
      Character (1), Parameter    :: diag = 'N', intlabel = 'I',          &
                                   matrix = 'G', nlabel = 'N'
      Character (4), Parameter    :: form = 'F5.2'
!      .. Local Scalars ..
      Integer                     :: i, ifail, info, k, lar1, lenap,      &
                                   lenar, n, q
      Character (21)              :: title
      Character (1)               :: transr, uplo
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: ap(:), ar(:)
      Character (1)               :: clabs(1), rlabs(1)
!      .. Executable Statements ..
      Write (nout,*) 'F01VLF Example Program Results'
!      Skip heading in data file
      Read (nin,*)
      Write (nout,*)
      Flush (nout)
      Read (nin,*) n, uplo, transr
      lenap = (n*(n+1))/2
      lenar = lenap

      Allocate (ap(lenap),ar(lenar))

!      Setup notional dimensions of RFP matrix AR
      k = n/2
      q = n - k
      If (transr=='N' .Or. transr=='n') Then
         lar1 = 2*k + 1
      Else
         lar1 = q
      End If

!      Read an RFP matrix into array AR
      Do i = 1, lar1
         Read (nin,*) ar(i:lenar:lar1)
      End Do

!      Print the Rectangular Full Packed array
      title = 'RFP Packed Array AR:'
      ifail = 0
      Call x04cbf(matrix,diag,lenar,incl,ar,lenar,form,title,intlabel,rlabs,      &
                  nlabel,clabs,ncols,indent,ifail)

      Write (nout,*)
      Flush (nout)

!      Convert to packed vector form
!      The NAG name equivalent of dtfttp is f01vlf
      Call dtfttp(transr,uplo,n,ar,ap,info)

!      Print the packed vector
      title = 'Packed Array AP:'

```

```
        ifail = 0
        Call x04cbf(matrix,diag,lenap,incl,ap,lenap,form,title,intlabel,rlabs,    &
            nolabel,clabs,ncols,indent,ifail)

    End Program f01vlfe
```

10.2 Program Data

```
F01VLF Example Program Data
4      'U'      'N' : n, uplo, transr
1.30   1.40
2.30   2.40
3.30   3.40
1.10   4.40
1.20   2.20      : RFP Matrix AR
```

10.3 Program Results

F01VLF Example Program Results

RFP Packed Array AR:

```
1  1.30
2  2.30
3  3.30
4  1.10
5  1.20
6  1.40
7  2.40
8  3.40
9  4.40
10 2.20
```

Packed Array AP:

```
1  1.10
2  1.20
3  2.20
4  1.30
5  2.30
6  3.30
7  1.40
8  2.40
9  3.40
10 4.40
```
