

# NAG Library Routine Document

## F06RKF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F06RKF returns, via the function name, the value of the 1-norm, the  $\infty$ -norm, the Frobenius norm, or the maximum absolute value of the elements of a real  $n$  by  $n$  triangular matrix, stored in packed form.

### 2 Specification

```
FUNCTION F06RKF (NORM, UPLO, DIAG, N, AP, WORK)
REAL (KIND=nag_wp) F06RKF
INTEGER                N
REAL (KIND=nag_wp) AP(*), WORK(*)
CHARACTER(1)           NORM, UPLO, DIAG
```

### 3 Description

None.

### 4 References

None.

### 5 Arguments

- 1: NORM – CHARACTER(1) *Input*  
*On entry:* specifies the value to be returned.  
 NORM = '1' or 'O'  
     The 1-norm.  
 NORM = 'I'  
     The  $\infty$ -norm.  
 NORM = 'F' or 'E'  
     The Frobenius (or Euclidean) norm.  
 NORM = 'M'  
     The value  $\max_{i,j} |a_{ij}|$  (not a norm).  
*Constraint:* NORM = '1', 'O', 'I', 'F', 'E' or 'M'.
- 2: UPLO – CHARACTER(1) *Input*  
*On entry:* specifies whether  $A$  is upper or lower triangular.  
 UPLO = 'U'  
      $A$  is upper triangular.  
 UPLO = 'L'  
      $A$  is lower triangular.  
*Constraint:* UPLO = 'U' or 'L'.

- 3:     DIAG – CHARACTER(1) *Input*  
       *On entry:* specifies whether  $A$  has nonunit or unit diagonal elements.  
       DIAG = 'N'  
           The diagonal elements are stored explicitly.  
       DIAG = 'U'  
           The diagonal elements are assumed to be 1, and are not referenced.  
       *Constraint:* DIAG = 'N' or 'U'.
- 4:     N – INTEGER *Input*  
       *On entry:*  $n$ , the order of the matrix  $A$ .  
       When  $N = 0$ , F06RKF returns zero.  
       *Constraint:*  $N \geq 0$ .
- 5:     AP(\*) – REAL (KIND=nag\_wp) array *Input*  
       **Note:** the dimension of the array AP must be at least  $N \times (N + 1)/2$ .  
       *On entry:* the  $n$  by  $n$  triangular matrix  $A$ , packed by columns.  
       More precisely,  
           if UPLO = 'U', the upper triangle of  $A$  must be stored with element  $A_{ij}$  in  
           AP( $i + j(j - 1)/2$ ) for  $i \leq j$ ;  
           if UPLO = 'L', the lower triangle of  $A$  must be stored with element  $A_{ij}$  in  
           AP( $i + (2n - j)(j - 1)/2$ ) for  $i \geq j$ .  
       If DIAG = 'U', the diagonal elements of  $A$  are assumed to be 1, and are not referenced; the same  
       storage scheme is used whether DIAG = 'N' or 'U'.
- 6:     WORK(\*) – REAL (KIND=nag\_wp) array *Workspace*  
       **Note:** the dimension of the array WORK must be at least  $\max(1, N)$  if NORM = 'I', and at least 1  
       otherwise.

## 6 Error Indicators and Warnings

None.

## 7 Accuracy

Not applicable.

## 8 Parallelism and Performance

F06RKF is not threaded in any implementation.

## 9 Further Comments

None.

## 10 Example

None.

---