

# NAG Library Routine Document

## F06SRF (ZHER2)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F06SRF (ZHER2) computes the rank-2 update of a complex Hermitian matrix.

### 2 Specification

```
SUBROUTINE F06SRF (UPLO, N, ALPHA, X, INCX, Y, INCY, A, LDA)
  INTEGER                N, INCX, INCY, LDA
  COMPLEX (KIND=nag_wp) ALPHA, X(*), Y(*), A(LDA,*)
  CHARACTER(1)          UPLO
```

The routine may be called by its BLAS name *zher2*.

### 3 Description

F06SRF (ZHER2) performs the Hermitian rank-2 update operation

$$A \leftarrow \alpha xy^H + \bar{\alpha} yx^H + A,$$

where  $A$  is an  $n$  by  $n$  complex Hermitian matrix,  $x$  and  $y$  are  $n$ -element complex vectors, and  $\alpha$  is a complex scalar.

### 4 References

None.

### 5 Arguments

- |    |   |              |
|----|---|--------------|
| 1: | UPLO – CHARACTER(1)<br><i>On entry:</i> specifies whether the upper or lower triangular part of $A$ is stored.<br>UPLO = 'U'<br>The upper triangular part of $A$ is stored.<br>UPLO = 'L'<br>The lower triangular part of $A$ is stored.<br><i>Constraint:</i> UPLO = 'U' or 'L'. | <i>Input</i> |
| 2: | N – INTEGER<br><i>On entry:</i> $n$ , the order of the matrix $A$ .<br><i>Constraint:</i> $N \geq 0$ .  | <i>Input</i> |
| 3: | ALPHA – COMPLEX (KIND=nag_wp)<br><i>On entry:</i> the scalar $\alpha$ .   | <i>Input</i> |
| 4: | X(*) – COMPLEX (KIND=nag_wp) array<br><b>Note:</b> the dimension of the array X must be at least $\max(1, 1 + (N - 1) \times  \text{INCX} )$ .<br><i>On entry:</i> the $n$ -element vector $x$ .  | <i>Input</i> |

If  $\text{INCX} > 0$ ,  $x_i$  must be stored in  $X(1 + (i - 1) \times \text{INCX})$ , for  $i = 1, 2, \dots, N$ .

If  $\text{INCX} < 0$ ,  $x_i$  must be stored in  $X(1 - (N - i) \times \text{INCX})$ , for  $i = 1, 2, \dots, N$ .

Intermediate elements of  $X$  are not referenced.

5:  $\text{INCX}$  – INTEGER

*Input*

*On entry:* the increment in the subscripts of  $X$  between successive elements of  $x$ .

*Constraint:*  $\text{INCX} \neq 0$ .

6:  $Y(*)$  – COMPLEX (KIND=nag\_wp) array

*Input*

**Note:** the dimension of the array  $Y$  must be at least  $\max(1, 1 + (N - 1) \times |\text{INCY}|)$ .

*On entry:* the  $n$ -element vector  $y$ .

If  $\text{INCY} > 0$ ,  $y_i$  must be stored in  $Y(1 + (i - 1) \times \text{INCY})$ , for  $i = 1, 2, \dots, N$ .

If  $\text{INCY} < 0$ ,  $y_i$  must be stored in  $Y(1 - (N - i) \times \text{INCY})$ , for  $i = 1, 2, \dots, N$ .

Intermediate elements of  $Y$  are not referenced.

7:  $\text{INCY}$  – INTEGER

*Input*

*On entry:* the increment in the subscripts of  $Y$  between successive elements of  $y$ .

*Constraint:*  $\text{INCY} \neq 0$ .

8:  $A(\text{LDA}, *)$  – COMPLEX (KIND=nag\_wp) array

*Input/Output*

**Note:** the second dimension of the array  $A$  must be at least  $\max(1, N)$ .

*On entry:* the  $n$  by  $n$  Hermitian matrix  $A$ .

If  $\text{UPLO} = 'U'$ , the upper triangular part of  $A$  must be stored and the elements of the array below the diagonal are not referenced.

If  $\text{UPLO} = 'L'$ , the lower triangular part of  $A$  must be stored and the elements of the array above the diagonal are not referenced.

*On exit:* the updated matrix  $A$ . The imaginary parts of the diagonal elements are set to zero.

9:  $\text{LDA}$  – INTEGER

*Input*

*On entry:* the first dimension of the array  $A$  as declared in the (sub)program from which F06SRF (ZHER2) is called.

*Constraint:*  $\text{LDA} \geq \max(1, N)$ .

## 6 Error Indicators and Warnings

None.

## 7 Accuracy

Not applicable.

## 8 Parallelism and Performance

F06SRF (ZHER2) is not threaded in any implementation.

## 9 Further Comments

None.

## **10 Example**

None.

---