

NAG Library Routine Document

F06ZFF (ZTRMM)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F06ZFF (ZTRMM) performs one of the matrix-matrix operations

$$\begin{array}{l} B \leftarrow \alpha AB, \quad B \leftarrow \alpha A^T B, \quad B \leftarrow \alpha A^H B, \\ B \leftarrow \alpha BA, \quad B \leftarrow \alpha BA^T \quad \text{or} \quad B \leftarrow \alpha BA^H, \end{array}$$

where B is an m by n complex matrix, A is a complex triangular matrix, and α is a complex scalar.

2 Specification

```
SUBROUTINE F06ZFF (SIDE, UPLO, TRANSA, DIAG, M, N, ALPHA, A, LDA, B, &
                  LDB)
```

```
INTEGER                M, N, LDA, LDB
COMPLEX (KIND=nag_wp) ALPHA, A(LDA,*), B(LDB,*)
CHARACTER(1)           SIDE, UPLO, TRANSA, DIAG
```

The routine may be called by its BLAS name *ztrmm*.

3 Description

None.

4 References

None.

5 Arguments

- 1: SIDE – CHARACTER(1) *Input*
On entry: specifies whether B is operated on from the left or the right.
 SIDE = 'L'
 B is pre-multiplied from the left.
 SIDE = 'R'
 B is post-multiplied from the right.
Constraint: SIDE = 'L' or 'R'.
- 2: UPLO – CHARACTER(1) *Input*
On entry: specifies whether A is upper or lower triangular.
 UPLO = 'U'
 A is upper triangular.
 UPLO = 'L'
 A is lower triangular.
Constraint: UPLO = 'U' or 'L'.

- 3: TRANSA – CHARACTER(1) *Input*
On entry: specifies whether the operation involves A , A^T or A^H .
TRANSA = 'N'
The operation involves A .
TRANSA = 'T'
The operation involves A^T .
TRANSA = 'C'
The operation involves A^H .
Constraint: TRANSA = 'N', 'T' or 'C'.
- 4: DIAG – CHARACTER(1) *Input*
On entry: specifies whether A has nonunit or unit diagonal elements.
DIAG = 'N'
The diagonal elements are stored explicitly.
DIAG = 'U'
The diagonal elements are assumed to be 1, and are not referenced.
Constraint: DIAG = 'N' or 'U'.
- 5: M – INTEGER *Input*
On entry: m , the number of rows of the matrix B ; the order of A if SIDE = 'L'.
Constraint: $M \geq 0$.
- 6: N – INTEGER *Input*
On entry: n , the number of columns of the matrix B ; the order of A if SIDE = 'R'.
Constraint: $N \geq 0$.
- 7: ALPHA – COMPLEX (KIND=nag_wp) *Input*
On entry: the scalar α .
- 8: A(LDA,*) – COMPLEX (KIND=nag_wp) array *Input*
Note: the second dimension of the array A must be at least $\max(1, M)$ if SIDE = 'L' and at least $\max(1, N)$ if SIDE = 'R'.
On entry: the triangular matrix A ; A is m by m if SIDE = 'L', or n by n if SIDE = 'R'.
If UPLO = 'U', A is upper triangular and the elements of the array below the diagonal are not referenced.
If UPLO = 'L', A is lower triangular and the elements of the array above the diagonal are not referenced.
If DIAG = 'U', the diagonal elements of A are assumed to be 1, and are not referenced.
- 9: LDA – INTEGER *Input*
On entry: the first dimension of the array A as declared in the (sub)program from which F06ZFF (ZTRMM) is called.
Constraints:
if SIDE = 'L', $LDA \geq \max(1, M)$;
if SIDE = 'R', $LDA \geq \max(1, N)$.

- 10: B(LDB,*) – COMPLEX (KIND=nag_wp) array Input/Output
Note: the second dimension of the array B must be at least $\max(1, N)$.
On entry: the m by n matrix B .
If ALPHA = 0, B need not be set.
On exit: the updated matrix B .
- 11: LDB – INTEGER Input
On entry: the first dimension of the array B as declared in the (sub)program from which F06ZFF (ZTRMM) is called.
Constraint: $LDB \geq \max(1, M)$.

6 Error Indicators and Warnings

None.

7 Accuracy

Not applicable.

8 Parallelism and Performance

F06ZFF (ZTRMM) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

None.

10 Example

None.
