

NAG Library Routine Document

F07BAF (DGBSV)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F07BAF (DGBSV) computes the solution to a real system of linear equations

$$AX = B,$$

where A is an n by n band matrix, with k_l subdiagonals and k_u superdiagonals, and X and B are n by r matrices.

2 Specification

```
SUBROUTINE F07BAF (N, KL, KU, NRHS, AB, LDAB, IPIV, B, LDB, INFO)
  INTEGER          N, KL, KU, NRHS, LDAB, IPIV(N), LDB, INFO
  REAL (KIND=nag_wp) AB(LDAB,*), B(LDB,*)
```

The routine may be called by its LAPACK name *dgbsv*.

3 Description

F07BAF (DGBSV) uses the LU decomposition with partial pivoting and row interchanges to factor A as $A = PLU$, where P is a permutation matrix, L is a product of permutation and unit lower triangular matrices with k_l subdiagonals, and U is upper triangular with $(k_l + k_u)$ superdiagonals. The factored form of A is then used to solve the system of equations $AX = B$.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

- 1: N – INTEGER *Input*
On entry: n , the number of linear equations, i.e., the order of the matrix A .
Constraint: $N \geq 0$.
- 2: KL – INTEGER *Input*
On entry: k_l , the number of subdiagonals within the band of the matrix A .
Constraint: $KL \geq 0$.
- 3: KU – INTEGER *Input*
On entry: k_u , the number of superdiagonals within the band of the matrix A .
Constraint: $KU \geq 0$.

- 4: NRHS – INTEGER *Input*
On entry: r , the number of right-hand sides, i.e., the number of columns of the matrix B .
Constraint: $\text{NRHS} \geq 0$.
- 5: AB(LDAB,*) – REAL (KIND=nag_wp) array *Input/Output*
Note: the second dimension of the array AB must be at least $\max(1, N)$.
On entry: the n by n coefficient matrix A .
The matrix is stored in rows $k_l + 1$ to $2k_l + k_u + 1$; the first k_l rows need not be set, more precisely, the element A_{ij} must be stored in

$$\text{AB}(k_l + k_u + 1 + i - j, j) = A_{ij} \quad \text{for } \max(1, j - k_u) \leq i \leq \min(n, j + k_l).$$
See Section 9 for further details.
On exit: if $\text{INFO} \geq 0$, AB is overwritten by details of the factorization.
The upper triangular band matrix U , with $k_l + k_u$ superdiagonals, is stored in rows 1 to $k_l + k_u + 1$ of the array, and the multipliers used to form the matrix L are stored in rows $k_l + k_u + 2$ to $2k_l + k_u + 1$.
- 6: LDAB – INTEGER *Input*
On entry: the first dimension of the array AB as declared in the (sub)program from which F07BAF (DGBSV) is called.
Constraint: $\text{LDAB} \geq 2 \times \text{KL} + \text{KU} + 1$.
- 7: IPIV(N) – INTEGER array *Output*
On exit: if no constraints are violated, the pivot indices that define the permutation matrix P ; at the i th step row i of the matrix was interchanged with row $\text{IPIV}(i)$. $\text{IPIV}(i) = i$ indicates a row interchange was not required.
- 8: B(LDB,*) – REAL (KIND=nag_wp) array *Input/Output*
Note: the second dimension of the array B must be at least $\max(1, \text{NRHS})$.
On entry: the n by r right-hand side matrix B .
On exit: if $\text{INFO} = 0$, the n by r solution matrix X .
- 9: LDB – INTEGER *Input*
On entry: the first dimension of the array B as declared in the (sub)program from which F07BAF (DGBSV) is called.
Constraint: $\text{LDB} \geq \max(1, N)$.
- 10: INFO – INTEGER *Output*
On exit: $\text{INFO} = 0$ unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

$\text{INFO} < 0$

If $\text{INFO} = -i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

Element $\langle value \rangle$ of the diagonal is exactly zero. The factorization has been completed, but the factor U is exactly singular, so the solution could not be computed.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A + E)\hat{x} = b,$$

where

$$\|E\|_1 = O(\epsilon)\|A\|_1$$

and ϵ is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \leq \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$, the condition number of A with respect to the solution of the linear equations. See Section 4.4 of Anderson *et al.* (1999) for further details.

Following the use of F07BAF (DGBSV), F07BGF (DGBCON) can be used to estimate the condition number of A and F07BHF (DGBRFS) can be used to obtain approximate error bounds. Alternatives to F07BAF (DGBSV), which return condition and error estimates directly are F04BBF and F07BBF (DGBSVX).

8 Parallelism and Performance

F07BAF (DGBSV) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07BAF (DGBSV) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The band storage scheme for the array AB is illustrated by the following example, when $n = 6$, $k_l = 1$, and $k_u = 2$. Storage of the band matrix A in the array AB:

*	*	*	+	+	+
*	*	a_{13}	a_{24}	a_{35}	a_{46}
*	a_{12}	a_{23}	a_{34}	a_{45}	a_{56}
a_{11}	a_{22}	a_{33}	a_{44}	a_{55}	a_{66}
a_{21}	a_{32}	a_{43}	a_{54}	a_{65}	*

Array elements marked * need not be set and are not referenced by the routine. Array elements marked + need not be set, but are defined on exit from the routine and contain the elements u_{14} , u_{25} and u_{36} .

The total number of floating-point operations required to solve the equations $AX = B$ depends upon the pivoting required, but if $n \gg k_l + k_u$ then it is approximately bounded by $O(nk_l(k_l + k_u))$ for the factorization and $O(n(2k_l + k_u)r)$ for the solution following the factorization.

The complex analogue of this routine is F07BNF (ZGBSV).

10 Example

This example solves the equations

$$Ax = b,$$

where A is the band matrix

$$A = \begin{pmatrix} -0.23 & 2.54 & -3.66 & 0 \\ -6.98 & 2.46 & -2.73 & -2.13 \\ 0 & 2.56 & 2.46 & 4.07 \\ 0 & 0 & -4.78 & -3.82 \end{pmatrix} \quad \text{and} \quad b = \begin{pmatrix} 4.42 \\ 27.13 \\ -6.14 \\ 10.50 \end{pmatrix}.$$

Details of the LU factorization of A are also output.

10.1 Program Text

```

Program f07baf

!      F07BAF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
      Use nag_library, Only: dgbsv, nag_wp, x04cef
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Integer                     :: i, ifail, info, j, k, kl, ku, ldab, &
                                   n
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: ab(:, :), b(:)
      Integer, Allocatable          :: ipiv(:)
!      .. Intrinsic Procedures ..
      Intrinsic                     :: max, min
!      .. Executable Statements ..
      Write (nout,*) 'F07BAF Example Program Results'
      Write (nout,*)
!      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n, kl, ku
      ldab = 2*kl + ku + 1
      Allocate (ab(ldab,n),b(n),ipiv(n))

!      Read the band matrix A and the right hand side b from data file

      k = kl + ku + 1
      Read (nin,*)((ab(k+i-j,j),j=max(i-kl,1),min(i+ku,n)),i=1,n)
      Read (nin,*) b(1:n)

!      Solve the equations Ax = b for x
!      The NAG name equivalent of dgbsv is f07baf
      Call dgbsv(n,kl,ku,1,ab,ldab,ipiv,b,n,info)

      If (info==0) Then

!          Print solution

          Write (nout,*) 'Solution'
          Write (nout,99999) b(1:n)

!          Print details of the factorization

          Write (nout,*)
          Flush (nout)

!          ifail: behaviour on error exit

```

```

!           =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
      Call x04cef(n,n,kl,kl+ku,ab,ldab,'Details of factorization',ifail)

!           Print pivot indices'

      Write (nout,*)
      Write (nout,*) 'Pivot indices'
      Write (nout,99998) ipiv(1:n)

      Else
        Write (nout,99997) 'The (' , info, ', ', info, ')',
          ' element of the factor U is zero'
      End If

99999 Format ((3X,7F11.4))
99998 Format ((3X,7I11))
99997 Format (1X,A,I3,A,I3,A,A)
      End Program f07baf

```

10.2 Program Data

F07BAF Example Program Data

```

4   1   2                               :Values of N, KL and KU

-0.23   2.54  -3.66
-6.98   2.46  -2.73  -2.13
        2.56   2.46   4.07
        -4.78  -3.82   :End of matrix A

4.42  27.13  -6.14  10.50   :End of vector B

```

10.3 Program Results

F07BAF Example Program Results

```

Solution
      -2.0000      3.0000      1.0000     -4.0000

Details of factorization
           1           2           3           4
1      -6.9800      2.4600     -2.7300     -2.1300
2         0.0330      2.5600      2.4600      4.0700
3              0.9605     -5.9329     -3.8391
4              0.8057     -0.7269

Pivot indices
           2           3           3           4

```
