

NAG Library Routine Document

F07CBF (DGTSVX)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F07CBF (DGTSVX) uses the LU factorization to compute the solution to a real system of linear equations

$$AX = B \quad \text{or} \quad A^T X = B,$$

where A is a tridiagonal matrix of order n and X and B are n by r matrices. Error bounds on the solution and a condition estimate are also provided.

2 Specification

```
SUBROUTINE F07CBF (FACT, TRANS, N, NRHS, DL, D, DU, DLF, DF, DUF, DU2,      &
                  IPIV, B, LDB, X, LDX, RCOND, FERR, BERR, WORK, IWORK,      &
                  INFO)
INTEGER          N, NRHS, IPIV(*), LDB, LDX, IWORK(N), INFO
REAL (KIND=nag_wp) DL(*), D(*), DU(*), DLF(*), DF(*), DUF(*), DU2(*),      &
                  B(LDB,*), X(LDX,*), RCOND, FERR(NRHS), BERR(NRHS),      &
                  WORK(3*N)
CHARACTER(1)     FACT, TRANS
```

The routine may be called by its LAPACK name ***dgtsvx***.

3 Description

F07CBF (DGTSVX) performs the following steps:

1. If FACT = 'N', the LU decomposition is used to factor the matrix A as $A = LU$, where L is a product of permutation and unit lower bidiagonal matrices and U is upper triangular with nonzeros in only the main diagonal and first two superdiagonals.
2. If some $u_{ii} = 0$, so that U is exactly singular, then the routine returns with INFO = i . Otherwise, the factored form of A is used to estimate the condition number of the matrix A . If the reciprocal of the condition number is less than ***machine precision***, INFO = $N + 1$ is returned as a warning, but the routine still goes on to solve for X and compute error bounds as described below.
3. The system of equations is solved for X using the factored form of A .
4. Iterative refinement is applied to improve the computed solution matrix and to calculate error bounds and backward error estimates for it.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

Higham N J (2002) *Accuracy and Stability of Numerical Algorithms* (2nd Edition) SIAM, Philadelphia

5 Arguments

- 1: FACT – CHARACTER(1) *Input*
On entry: specifies whether or not the factorized form of the matrix A has been supplied.
 FACT = 'F'
 DLF, DF, DUF, DU2 and IPIV contain the factorized form of the matrix A . DLF, DF, DUF, DU2 and IPIV will not be modified.
 FACT = 'N'
 The matrix A will be copied to DLF, DF and DUF and factorized.
Constraint: FACT = 'F' or 'N'.

- 2: TRANS – CHARACTER(1) *Input*
On entry: specifies the form of the system of equations.
 TRANS = 'N'
 $AX = B$ (No transpose).
 TRANS = 'T' or 'C'
 $A^T X = B$ (Transpose).
Constraint: TRANS = 'N', 'T' or 'C'.

- 3: N – INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.

- 4: NRHS – INTEGER *Input*
On entry: r , the number of right-hand sides, i.e., the number of columns of the matrix B .
Constraint: NRHS ≥ 0 .

- 5: DL(*) – REAL (KIND=nag_wp) array *Input*
Note: the dimension of the array DL must be at least $\max(1, N - 1)$.
On entry: the $(n - 1)$ subdiagonal elements of A .

- 6: D(*) – REAL (KIND=nag_wp) array *Input*
Note: the dimension of the array D must be at least $\max(1, N)$.
On entry: the n diagonal elements of A .

- 7: DU(*) – REAL (KIND=nag_wp) array *Input*
Note: the dimension of the array DU must be at least $\max(1, N - 1)$.
On entry: the $(n - 1)$ superdiagonal elements of A .

- 8: DLF(*) – REAL (KIND=nag_wp) array *Input/Output*
Note: the dimension of the array DLF must be at least $\max(1, N - 1)$.
On entry: if FACT = 'F', DLF contains the $(n - 1)$ multipliers that define the matrix L from the LU factorization of A .
On exit: if FACT = 'N', DLF contains the $(n - 1)$ multipliers that define the matrix L from the LU factorization of A .

- 9: DF(*) – REAL (KIND=nag_wp) array *Input/Output*
Note: the dimension of the array DF must be at least $\max(1, N)$.
On entry: if FACT = 'F', DF contains the n diagonal elements of the upper triangular matrix U from the LU factorization of A .
On exit: if FACT = 'N', DF contains the n diagonal elements of the upper triangular matrix U from the LU factorization of A .
- 10: DUF(*) – REAL (KIND=nag_wp) array *Input/Output*
Note: the dimension of the array DUF must be at least $\max(1, N - 1)$.
On entry: if FACT = 'F', DUF contains the $(n - 1)$ elements of the first superdiagonal of U .
On exit: if FACT = 'N', DUF contains the $(n - 1)$ elements of the first superdiagonal of U .
- 11: DU2(*) – REAL (KIND=nag_wp) array *Input/Output*
Note: the dimension of the array DU2 must be at least $\max(1, N - 2)$.
On entry: if FACT = 'F', DU2 contains the $(n - 2)$ elements of the second superdiagonal of U .
On exit: if FACT = 'N', DU2 contains the $(n - 2)$ elements of the second superdiagonal of U .
- 12: IPIV(*) – INTEGER array *Input/Output*
Note: the dimension of the array IPIV must be at least $\max(1, N)$.
On entry: if FACT = 'F', IPIV contains the pivot indices from the LU factorization of A .
On exit: if FACT = 'N', IPIV contains the pivot indices from the LU factorization of A ; row i of the matrix was interchanged with row $IPIV(i)$. $IPIV(i)$ will always be either i or $i + 1$; $IPIV(i) = i$ indicates a row interchange was not required.
- 13: B(LDB, *) – REAL (KIND=nag_wp) array *Input*
Note: the second dimension of the array B must be at least $\max(1, NRHS)$.
On entry: the n by r right-hand side matrix B .
- 14: LDB – INTEGER *Input*
On entry: the first dimension of the array B as declared in the (sub)program from which F07CBF (DGTSVX) is called.
Constraint: $LDB \geq \max(1, N)$.
- 15: X(LDX, *) – REAL (KIND=nag_wp) array *Output*
Note: the second dimension of the array X must be at least $\max(1, NRHS)$.
On exit: if INFO = 0 or $N + 1$, the n by r solution matrix X .
- 16: LDX – INTEGER *Input*
On entry: the first dimension of the array X as declared in the (sub)program from which F07CBF (DGTSVX) is called.
Constraint: $LDX \geq \max(1, N)$.
- 17: RCOND – REAL (KIND=nag_wp) *Output*
On exit: the estimate of the reciprocal condition number of the matrix A . If $RCOND = 0.0$, the matrix may be exactly singular. This condition is indicated by $INFO > 0$ and $INFO \leq N$. Otherwise, if RCOND is less than the *machine precision*, the matrix is singular to working precision. This condition is indicated by $INFO = N + 1$.

- 18: FERR(NRHS) – REAL (KIND=nag_wp) array *Output*
On exit: if INFO = 0 or N + 1, an estimate of the forward error bound for each computed solution vector, such that $\|\hat{x}_j - x_j\|_\infty / \|x_j\|_\infty \leq \text{FERR}(j)$ where \hat{x}_j is the j th column of the computed solution returned in the array X and x_j is the corresponding column of the exact solution X. The estimate is as reliable as the estimate for RCOND, and is almost always a slight overestimate of the true error.
- 19: BERR(NRHS) – REAL (KIND=nag_wp) array *Output*
On exit: if INFO = 0 or N + 1, an estimate of the component-wise relative backward error of each computed solution vector \hat{x}_j (i.e., the smallest relative change in any element of A or B that makes \hat{x}_j an exact solution).
- 20: WORK(3 × N) – REAL (KIND=nag_wp) array *Workspace*
- 21: IWORK(N) – INTEGER array *Workspace*
- 22: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0 and INFO < N

Element $\langle \text{value} \rangle$ of the diagonal is exactly zero. The factorization has not been completed, but the factor U is exactly singular, so the solution and error bounds could not be computed. RCOND = 0.0 is returned.

INFO > 0 and INFO = N

Element $\langle \text{value} \rangle$ of the diagonal is exactly zero. The factorization has been completed, but the factor U is exactly singular, so the solution and error bounds could not be computed. RCOND = 0.0 is returned.

INFO = N + 1

U is nonsingular, but RCOND is less than **machine precision**, meaning that the matrix is singular to working precision. Nevertheless, the solution and error bounds are computed because there are a number of situations where the computed solution can be more accurate than the value of RCOND would suggest.

7 Accuracy

For each right-hand side vector b , the computed solution \hat{x} is the exact solution of a perturbed system of equations $(A + E)\hat{x} = b$, where

$$|E| \leq c(n)\epsilon|L||U|,$$

$c(n)$ is a modest linear function of n , and ϵ is the **machine precision**. See Section 9.3 of Higham (2002) for further details.

If x is the true solution, then the computed solution \hat{x} satisfies a forward error bound of the form

$$\frac{\|x - \hat{x}\|_\infty}{\|\hat{x}\|_\infty} \leq w_c \text{cond}(A, \hat{x}, b)$$

where $\text{cond}(A, \hat{x}, b) = \frac{\|A^{-1}(|A|\hat{x} + |b|)\|_{\infty}}{\|\hat{x}\|_{\infty}} \leq \text{cond}(A) = \frac{\|A^{-1}\|_{\infty} \|A\|_{\infty}}{1} \leq \kappa_{\infty}(A)$. If \hat{x} is the j th column of X , then w_c is returned in $\text{BERR}(j)$ and a bound on $\|x - \hat{x}\|_{\infty} / \|\hat{x}\|_{\infty}$ is returned in $\text{FERR}(j)$. See Section 4.4 of Anderson *et al.* (1999) for further details.

8 Parallelism and Performance

F07CBF (DGTSVX) is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F07CBF (DGTSVX) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations required to solve the equations $AX = B$ is proportional to nr .

The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization. The solution is then refined, and the errors estimated, using iterative refinement.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

The complex analogue of this routine is F07CPF (ZGTSVX).

10 Example

This example solves the equations

$$AX = B,$$

where A is the tridiagonal matrix

$$A = \begin{pmatrix} 3.0 & 2.1 & 0 & 0 & 0 \\ 3.4 & 2.3 & -1.0 & 0 & 0 \\ 0 & 3.6 & -5.0 & 1.9 & 0 \\ 0 & 0 & 7.0 & -0.9 & 8.0 \\ 0 & 0 & 0 & -6.0 & 7.1 \end{pmatrix}$$

and

$$B = \begin{pmatrix} 2.7 & 6.6 \\ -0.5 & 10.8 \\ 2.6 & -3.2 \\ 0.6 & -11.2 \\ 2.7 & 19.1 \end{pmatrix}.$$

Estimates for the backward errors, forward errors and condition number are also output.

10.1 Program Text

```
Program f07cbfe

!      F07CBF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
```

```

      Use nag_library, Only: dgtsvx, nag_wp, x04caf
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Real (Kind=nag_wp)          :: rcond
      Integer                      :: i, ifail, info, ldb, ldx, n, nrhs
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: b(:,,:), berr(:), d(:), df(:), dl(:), &
                                         dlf(:), du(:), du2(:), duf(:),      &
                                         ferr(:), work(:), x(:,,:)
      Integer, Allocatable          :: ipiv(:), iwork(:)
!      .. Executable Statements ..
      Write (nout,*) 'F07CBF Example Program Results'
      Write (nout,*)
      Flush (nout)
!      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n, nrhs
      ldb = n
      ldx = n
      Allocate (b(ldb,nrhs),berr(nrhs),d(n),df(n),dl(n-1),dlf(n-1),du(n-1),      &
                du2(n-2),duf(n-1),ferr(nrhs),work(3*n),x(ldx,nrhs),ipiv(n),iwork(n))

!      Read the tridiagonal matrix A from data file

      Read (nin,*) du(1:n-1)
      Read (nin,*) d(1:n)
      Read (nin,*) dl(1:n-1)

!      Read the right hand matrix B

      Read (nin,*)(b(i,1:nrhs),i=1,n)

!      Solve the equations AX = B

!      The NAG name equivalent of dgtsvx is f07cbf
      Call dgtsvx('No factors','No transpose',n,nrhs,dl,d,du,dlf,df,duf,du2,      &
                 ipiv,b,ldb,x,ldx,rcond,ferr,berr,work,iwork,info)

      If ((info==0) .Or. (info==n+1)) Then

!      Print solution, error bounds and condition number

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
      Call x04caf('General',' ',n,nrhs,x,ldx,'Solution(s)',ifail)

      Write (nout,*)
      Write (nout,*) 'Backward errors (machine-dependent)'
      Write (nout,99999) berr(1:nrhs)
      Write (nout,*)
      Write (nout,*) 'Estimated forward error bounds (machine-dependent)'
      Write (nout,99999) ferr(1:nrhs)
      Write (nout,*)
      Write (nout,*) 'Estimate of reciprocal condition number'
      Write (nout,99999) rcond

      If (info==n+1) Then
        Write (nout,*)
        Write (nout,*) 'The matrix A is singular to working precision'
      End If
    Else
      Write (nout,99998) 'The (' , info, ', ', info, ')',      &
        ' element of the factor U is zero'
    End If

```

```

      End If

99999 Format ((3X,1P,7E11.1))
99998 Format (1X,A,I3,A,I3,A,A)
      End Program f07cbfe

```

10.2 Program Data

```

F07CBF Example Program Data
  5      2      :Values of N and NRHS
      2.1 -1.0  1.9  8.0
  3.0  2.3 -5.0 -0.9  7.1
  3.4  3.6  7.0 -6.0      :End of matrix A
  2.7  6.6
-0.5 10.8
  2.6 -3.2
  0.6 -11.2
  2.7 19.1      :End of matrix B

```

10.3 Program Results

F07CBF Example Program Results

Solution(s)

	1	2
1	-4.0000	5.0000
2	7.0000	-4.0000
3	3.0000	-3.0000
4	-4.0000	-2.0000
5	-3.0000	1.0000

Backward errors (machine-dependent)

7.2E-17	5.9E-17
---------	---------

Estimated forward error bounds (machine-dependent)

9.4E-15	1.4E-14
---------	---------

Estimate of reciprocal condition number

1.1E-02
