

NAG Library Routine Document

F07PWF (ZHPTRI)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F07PWF (ZHPTRI) computes the inverse of a complex Hermitian indefinite matrix A , where A has been factorized by F07PRF (ZHPTRF), using packed storage.

2 Specification

```
SUBROUTINE F07PWF (UPLO, N, AP, IPIV, WORK, INFO)
  INTEGER          N, IPIV(*), INFO
  COMPLEX (KIND=nag_wp) AP(*), WORK(N)
  CHARACTER(1)     UPLO
```

The routine may be called by its LAPACK name *zhptri*.

3 Description

F07PWF (ZHPTRI) is used to compute the inverse of a complex Hermitian indefinite matrix A , the routine must be preceded by a call to F07PRF (ZHPTRF), which computes the Bunch–Kaufman factorization of A , using packed storage.

If $UPLO = 'U'$, $A = PUDU^H P^T$ and A^{-1} is computed by solving $U^H P^T X P U = D^{-1}$ for X .

If $UPLO = 'L'$, $A = PLDL^H P^T$ and A^{-1} is computed by solving $L^H P^T X P L = D^{-1}$ for X .

4 References

Du Croz J J and Higham N J (1992) Stability of methods for matrix inversion *IMA J. Numer. Anal.* **12** 1–19

5 Arguments

- 1: **UPLO** – CHARACTER(1) *Input*
On entry: specifies how A has been factorized.
UPLO = 'U'
 $A = PUDU^H P^T$, where U is upper triangular.
UPLO = 'L'
 $A = PLDL^H P^T$, where L is lower triangular.
Constraint: UPLO = 'U' or 'L'.
- 2: **N** – INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.
- 3: **AP(*)** – COMPLEX (KIND=nag_wp) array *Input/Output*
Note: the dimension of the array AP must be at least $\max(1, N \times (N + 1)/2)$.
On entry: the factorization of A stored in packed form, as returned by F07PRF (ZHPTRF).

On exit: the factorization is overwritten by the n by n matrix A^{-1} .

More precisely,

if UPLO = 'U', the upper triangle of A^{-1} must be stored with element A_{ij} in $AP(i + j(j-1)/2)$ for $i \leq j$;

if UPLO = 'L', the lower triangle of A^{-1} must be stored with element A_{ij} in $AP(i + (2n-j)(j-1)/2)$ for $i \geq j$.

4: IPIV(*) – INTEGER array *Input*

Note: the dimension of the array IPIV must be at least $\max(1, N)$.

On entry: details of the interchanges and the block structure of D , as returned by F07PRF (ZHPTRF).

5: WORK(N) – COMPLEX (KIND=nag_wp) array *Workspace*

6: INFO – INTEGER *Output*

On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

Element $\langle value \rangle$ of the diagonal is exactly zero. D is singular and the inverse of A cannot be computed.

7 Accuracy

The computed inverse X satisfies a bound of the form

if UPLO = 'U', $|DU^T P^T X P U - I| \leq c(n)\epsilon(|D||U^T|P^T|X|P|U| + |D||D^{-1}|)$;

if UPLO = 'L', $|DL^T P^T X P L - I| \leq c(n)\epsilon(|D||L^T|P^T|X|P|L| + |D||D^{-1}|)$,

$c(n)$ is a modest linear function of n , and ϵ is the *machine precision*.

8 Parallelism and Performance

F07PWF (ZHPTRI) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of real floating-point operations is approximately $\frac{8}{3}n^3$.

The real analogue of this routine is F07PJF (DSPTRI).

10 Example

This example computes the inverse of the matrix A , where

$$A = \begin{pmatrix} -1.36 + 0.00i & 1.58 + 0.90i & 2.21 - 0.21i & 3.91 + 1.50i \\ 1.58 - 0.90i & -8.87 + 0.00i & -1.84 - 0.03i & -1.78 + 1.18i \\ 2.21 + 0.21i & -1.84 + 0.03i & -4.63 + 0.00i & 0.11 + 0.11i \\ 3.91 - 1.50i & -1.78 - 1.18i & 0.11 - 0.11i & -1.84 + 0.00i \end{pmatrix}.$$

Here A is Hermitian indefinite, stored in packed form, and must first be factorized by F07PRF (ZHPTRF).

10.1 Program Text

```

Program f07pwfe

!      F07PWF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
      Use nag_library, Only: nag_wp, x04ddf, zhptrf, zhptri
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Integer                     :: i, ifail, info, j, n
      Character (1)               :: uplo
!      .. Local Arrays ..
      Complex (Kind=nag_wp), Allocatable :: ap(:), work(:)
      Integer, Allocatable        :: ipiv(:)
      Character (1)               :: clabs(1), rlabs(1)
!      .. Executable Statements ..
      Write (nout,*) 'F07PWF Example Program Results'
!      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n

      Allocate (ap(n*(n+1)/2),work(n),ipiv(n))

!      Read A from data file

      Read (nin,*) uplo
      If (uplo=='U') Then
         Read (nin,*)((ap(i+j*(j-1)/2),j=i,n),i=1,n)
      Else If (uplo=='L') Then
         Read (nin,*)((ap(i+(2*n-j)*(j-1)/2),j=1,i),i=1,n)
      End If

!      Factorize A
!      The NAG name equivalent of zhptrf is f07prf
      Call zhptrf(uplo,n,ap,ipiv,info)

      Write (nout,*)
      Flush (nout)
      If (info==0) Then

!      Compute inverse of A
!      The NAG name equivalent of zhptri is f07pwf
      Call zhptri(uplo,n,ap,ipiv,work,info)

!      Print inverse

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
      Call x04ddf(uplo,'Nonunit',n,ap,'Bracketed','F7.4','Inverse',
                  'Integer',rlabs,'Integer',clabs,80,0,ifail)

```

```

      Else
        Write (nout,*) 'The factor D is singular'
      End If

      End Program f07pwfe

```

10.2 Program Data

F07PWF Example Program Data

```

4                                     :Value of N
'L'                                 :Value of UPLO
(-1.36, 0.00)
( 1.58,-0.90) (-8.87, 0.00)
( 2.21, 0.21) (-1.84, 0.03) (-4.63, 0.00)
( 3.91,-1.50) (-1.78,-1.18) ( 0.11,-0.11) (-1.84, 0.00) :End of matrix A

```

10.3 Program Results

F07PWF Example Program Results

```

Inverse
          1          2          3          4
1 ( 0.0826, 0.0000)
2 (-0.0335, 0.0440) (-0.1408, 0.0000)
3 ( 0.0603,-0.0105) ( 0.0422,-0.0222) (-0.2007, 0.0000)
4 ( 0.2391,-0.0926) ( 0.0304, 0.0203) ( 0.0982,-0.0635) ( 0.0073,-0.0000)

```
