

NAG Library Routine Document

F08KWF (ZGESVJ)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

F08KWF (ZGESVJ) computes the one-sided Jacobi singular value decomposition (SVD) of a complex m by n matrix A , $m \geq n$, with fast scaled rotations and de Rijk's pivoting, optionally computing the left and/or right singular vectors. For $m < n$, the routines F08KPF (ZGESVD) or F08KRF (ZGESDD) may be used.

2 Specification

```
SUBROUTINE F08KWF (JOBA, JOBU, JOBV, M, N, A, LDA, SVA, MV, V, LDV,      &
                  CWORK, LWORK, RWORK, LRWORK, INFO)
```

```
INTEGER                M, N, LDA, MV, LDV, LWORK, LRWORK, INFO
REAL (KIND=nag_wp)    SVA(N), RWORK(LRWORK)
COMPLEX (KIND=nag_wp) A(LDA,*), V(LDV,*), CWORK(LWORK)
CHARACTER(1)          JOBA, JOBU, JOBV
```

The routine may be called by its LAPACK name ***zgesvj***.

3 Description

The SVD is written as

$$A = U\Sigma V^H,$$

where Σ is an n by n diagonal matrix, U is an m by n unitary matrix, and V is an n by n unitary matrix. The diagonal elements of Σ are the singular values of A in descending order of magnitude. The columns of U and V are the left and the right singular vectors of A .

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Drmac Z and Veselic K (2008a) New fast and accurate Jacobi SVD algorithm I *SIAM J. Matrix Anal. Appl.* **29** 4

Drmac Z and Veselic K (2008b) New fast and accurate Jacobi SVD algorithm II *SIAM J. Matrix Anal. Appl.* **29** 4

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Arguments

1: JOBA – CHARACTER(1) *Input*

On entry: specifies the structure of matrix A .

JOBA = 'L'

The input matrix A is lower triangular.

JOBA = 'U'

The input matrix A is upper triangular.

JOB A = 'G'

The input matrix A is a general m by n matrix, $M \geq N$.

Constraint: JOB A = 'L', 'U' or 'G'.

2: JOB U – CHARACTER(1)

Input

On entry: specifies whether to compute the left singular vectors and if so whether you want to control their numerical orthogonality threshold.

JOB U = 'U'

The left singular vectors corresponding to the nonzero singular values are computed and returned in the leading columns of A . See more details in the description of A . The numerical orthogonality threshold is set to approximately $tol = ctol \times \epsilon$, where ϵ is the **machine precision** and $ctol = \sqrt{m}$.

JOB U = 'C'

Analogous to JOB U = 'U', except that you can control the level of numerical orthogonality of the computed left singular vectors. The orthogonality threshold is set to $tol = ctol \times \epsilon$, where $ctol$ is given on input in RWORK(1). The option JOB U = 'C' can be used if $m \times \epsilon$ is a satisfactory orthogonality of the computed left singular vectors, so $ctol = M$ could save a few sweeps of Jacobi rotations. See the descriptions of A and RWORK(1).

JOB U = 'N'

The matrix U is not computed. However, see the description of A .

Constraint: JOB U = 'U', 'C' or 'N'.

3: JOB V – CHARACTER(1)

Input

On entry: specifies whether and how to compute the right singular vectors.

JOB V = 'V'

The matrix V is computed and returned in the array V .

JOB V = 'A'

The Jacobi rotations are applied to the leading m_v by n part of the array V . In other words, the right singular vector matrix V is not computed explicitly, instead it is applied to an m_v by n matrix initially stored in the first MV rows of V .

JOB V = 'N'

The matrix V is not computed and the array V is not referenced.

Constraint: JOB V = 'V', 'A' or 'N'.

4: M – INTEGER

Input

On entry: m , the number of rows of the matrix A .

Constraint: $M \geq 0$.

5: N – INTEGER

Input

On entry: n , the number of columns of the matrix A .

Constraint: $M \geq N \geq 0$.

6: A(LDA,*) – COMPLEX (KIND=nag_wp) array

Input/Output

Note: the second dimension of the array A must be at least $\max(1, N)$.

On entry: the m by n matrix A .

On exit: the matrix U containing the left singular vectors of A .

If $\text{JOBV} = \text{'U'}$ or 'C'

if $\text{INFO} = 0$

$\text{rank}(A)$ unitary columns of U are returned in the leading $\text{rank}(A)$ columns of the array A . Here $\text{rank}(A) \leq N$ is the number of computed singular values of A that are above the safe range parameter, as returned by X02AMF. The singular vectors corresponding to underflowed or zero singular values are not computed. The value of $\text{rank}(A)$ is returned by rounding $\text{RWORK}(2)$ to the nearest whole number. Also see the descriptions of SVA and RWORK. The computed columns of U are mutually numerically unitary up to approximately $\text{tol} = \sqrt{m} \times \epsilon$; or $\text{tol} = \text{ctol} \times \epsilon$ ($\text{JOBV} = \text{'C'}$), where ϵ is the *machine precision* and ctol is supplied on entry in $\text{RWORK}(1)$, see the description of JOBV .

If $\text{INFO} > 0$

F08KWF (ZGESVJ) did not converge in 30 iterations (sweeps). In this case, the computed columns of U may not be unitary up to tol . The output U (stored in A), Σ (given by the computed singular values in SVA) and V is still a decomposition of the input matrix A in the sense that the residual $\|A - \alpha \times U \times \Sigma \times V^H\|_2 / \|A\|_2$ is small, where α is the value returned in $\text{RWORK}(1)$.

If $\text{JOBV} = \text{'N'}$

if $\text{INFO} = 0$

Note that the left singular vectors are ‘for free’ in the one-sided Jacobi SVD algorithm. However, if only the singular values are needed, the level of numerical orthogonality of U is not an issue and iterations are stopped when the columns of the iterated matrix are numerically unitary up to approximately $m \times \epsilon$. Thus, on exit, A contains the columns of U scaled with the corresponding singular values.

If $\text{INFO} > 0$

F08KWF (ZGESVJ) did not converge in 30 iterations (sweeps).

7: LDA – INTEGER

Input

On entry: the first dimension of the array A as declared in the (sub)program from which F08KWF (ZGESVJ) is called.

Constraint: $\text{LDA} \geq \max(1, M)$.

8: SVA(N) – REAL (KIND=nag_wp) array

Output

On exit: the, possibly scaled, singular values of A .

If $\text{INFO} = 0$

The singular values of A are $\sigma_i = \alpha \text{SVA}(i)$, for $i = 1, 2, \dots, n$, where α is the scale factor stored in $\text{RWORK}(1)$. Normally $\alpha = 1$, however, if some of the singular values of A might underflow or overflow, then $\alpha \neq 1$ and the scale factor needs to be applied to obtain the singular values.

If $\text{INFO} > 0$

F08KWF (ZGESVJ) did not converge in 30 iterations and $\alpha \times \text{SVA}$ may not be accurate.

9: MV – INTEGER

Input

On entry: if $\text{JOBV} = \text{'A'}$, the product of Jacobi rotations is applied to the first m_v rows of V .

If $\text{JOBV} \neq \text{'A'}$, MV is ignored. See the description of JOBV .

- 10: V(LDV,*) – COMPLEX (KIND=nag_wp) array Input/Output
- Note:** the second dimension of the array V must be at least $\max(1, N)$ if JOBV = 'V' or 'A', and at least 1 otherwise.
- On entry:* if JOBV = 'A', V must contain an m_v by n matrix to be premultiplied by the matrix V of right singular vectors.
- On exit:* the right singular vectors of A.
- If JOBV = 'V', V contains the n by n matrix of the right singular vectors.
- If JOBV = 'A', V contains the product of the computed right singular vector matrix and the initial matrix in the array V.
- If JOBV = 'N', V is not referenced.
- 11: LDV – INTEGER Input
- On entry:* the first dimension of the array V as declared in the (sub)program from which F08KWF (ZGESVJ) is called.
- Constraints:*
- if JOBV = 'V', $LDV \geq \max(1, N)$;
 - if JOBV = 'A', $LDV \geq \max(1, MV)$;
 - otherwise $LDV \geq 1$.
- 12: CWORK(LWORK) – COMPLEX (KIND=nag_wp) array Workspace
- On exit:* if INFO = 0, CWORK(1) contains the required minimal size of LWORK.
- 13: LWORK – INTEGER Input
- On entry:* the dimension of the array CWORK as declared in the (sub)program from which F08KWF (ZGESVJ) is called.
- Constraint:* $LWORK \geq M + N$.
- 14: RWORK(LRWORK) – REAL (KIND=nag_wp) array Workspace
- On entry:* if JOBU = 'C', $RWORK(1) = ctol$, where $ctol$ defines the threshold for convergence. The process stops if all columns of A are mutually orthogonal up to $ctol \times \epsilon$. It is required that $ctol \geq 1$, i.e., it is not possible to force the routine to obtain orthogonality below ϵ . $ctol$ greater than $1/\epsilon$ is meaningless, where ϵ is the **machine precision**.
- On exit:* contains information about the completed job.
- RWORK(1)
the scaling factor, α , such that $\sigma_i = \alpha SVA(i)$, for $i = 1, 2, \dots, n$ are the computed singular values of A. (See description of SVA.)
- RWORK(2)
 $nint(RWORK(2))$ gives the number of the computed nonzero singular values.
- RWORK(3)
 $nint(RWORK(3))$ gives the number of the computed singular values that are larger than the underflow threshold.
- RWORK(4)
 $nint(RWORK(4))$ gives the number of iterations (sweeps of Jacobi rotations) needed for numerical convergence.
- RWORK(5)
 $\max_{i \neq j} |\cos(A(:, i), A(:, j))|$ in the last iteration (sweep). This is useful information in cases when F08KWF (ZGESVJ) did not converge, as it can be used to estimate whether the output is still useful and for subsequent analysis.

RWORK(6)

The largest absolute value over all sines of the Jacobi rotation angles in the last sweep. It can be useful for subsequent analysis.

Constraint: if JOBU = 'C', RWORK(1) \geq 1.0.

15: LRWORK – INTEGER

Input

On entry: the dimension of the array RWORK as declared in the (sub)program from which F08KWF (ZGESVJ) is called.

Constraint: LRWORK \geq max(6, N).

16: INFO – INTEGER

Output

On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

INFO > 0

F08KWF (ZGESVJ) did not converge in the allowed number of iterations (30), but its output might still be useful.

7 Accuracy

The computed singular value decomposition is nearly the exact singular value decomposition for a nearby matrix $(A + E)$, where

$$\|E\|_2 = O(\epsilon)\|A\|_2,$$

and ϵ is the *machine precision*. In addition, the computed singular vectors are nearly unitary to working precision. See Section 4.9 of Anderson *et al.* (1999) for further details.

See Section 6 of Drmac and Veselic (2008a) for a detailed discussion of the accuracy of the computed SVD.

8 Parallelism and Performance

F08KWF (ZGESVJ) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

This SVD algorithm is numerically superior to the bidiagonalization based QR algorithm implemented by F08KPF (ZGESVD) and the divide and conquer algorithm implemented by F08KRF (ZGESDD) algorithms and is considerably faster than previous implementations of the (equally accurate) Jacobi SVD method. Moreover, this algorithm can compute the SVD faster than F08KPF (ZGESVD) and not much slower than F08KRF (ZGESDD). See Section 3.3 of Drmac and Veselic (2008b) for the details.

The real analogue of this routine is F08KJF (DGESVJ).

10 Example

This example finds the singular values and left and right singular vectors of the 6 by 4 matrix

$$A = \begin{pmatrix} 0.96 - 0.81i & -0.03 + 0.96i & -0.91 + 2.06i & -0.05 + 0.41i \\ -0.98 + 1.98i & -1.20 + 0.19i & -0.66 + 0.42i & -0.81 + 0.56i \\ 0.62 - 0.46i & 1.01 + 0.02i & 0.63 - 0.17i & -1.11 + 0.60i \\ -0.37 + 0.38i & 0.19 - 0.54i & -0.98 - 0.36i & 0.22 - 0.20i \\ 0.83 + 0.51i & 0.20 + 0.01i & -0.17 - 0.46i & 1.47 + 1.59i \\ 1.08 - 0.28i & 0.20 - 0.12i & -0.07 + 1.23i & 0.26 + 0.26i \end{pmatrix},$$

together with approximate error bounds for the computed singular values and vectors.

10.1 Program Text

Program f08kwfe

```
!      F08KWF Example Program Text
!
!      Mark 26 Release. NAG Copyright 2016.
!
!      .. Use Statements ..
!      Use nag_library, Only: ddisna, nag_wp, x02ajf, x04daf, zgesvj
!      .. Implicit None Statement ..
!      Implicit None
!      .. Parameters ..
!      Integer, Parameter
!      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
!      Real (Kind=nag_wp)
!      Integer                    :: eps, serrbd
!      Integer                    :: i, ifail, info, j, lda, ldv, lrwork, &
!                                lwork, m, n
!
!      .. Local Arrays ..
!      Complex (Kind=nag_wp), Allocatable :: a(:, :), cwork(:), v(:, :)
!      Real (Kind=nag_wp), Allocatable    :: rcondu(:), rcondv(:), rwork(:), &
!                                sva(:)
!
!      .. Intrinsic Procedures ..
!      Intrinsic                    :: abs, max, nint
!
!      .. Executable Statements ..
!      Write (nout,*) 'F08KWF Example Program Results'
!      Write (nout,*)
!      Flush (nout)
!      Skip heading in data file
!      Read (nin,*)
!      Read (nin,*) m, n
!      lda = m
!      ldv = n
!      lwork = n + m
!      lrwork = max(6,n)
!      Allocate (a(lda,n),rcondu(m),rcondv(m),sva(n),v(ldv,n),cwork(lwork), &
!              rwork(lrwork))
!
!      Read the m by n matrix A from data file
!
!      Read (nin,*)((a(i,j),j=1,n),i=1,m)
!
!      Compute the singular values and left and right singular vectors
!      of A (A = U*S*V, m.ge.n)
!
!      The NAG name equivalent of zgesvj is f08kwf
!      Call zgesvj('G','U','V',m,n,a,lda,sva,0,v,ldv,cwork,lwork,rwork,lrwork, &
!              info)
!      If (info==0) Then
!
!          Compute the approximate error bound for the computed singular values
!          using the 2-norm, s(1) = norm(A), and machine precision, eps.
!          eps = x02ajf()
!          serrbd = eps*sva(1)
!
!      Print solution
```

```

      Write (nout,*) 'Singular values'
      Write (nout,99999)(sva(j),j=1,n)

      If (abs(rwork(1)-1.0_nag_wp)>eps) Then
        Write (nout,99996) 'Values need scaling by factor = ', rwork(1)
      End If
      Write (nout,*)
      Flush (nout)

!      ifail: behaviour on error exit
!      =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
      Call x04daf('General',' ',m,n,a,lda,'Left singular vectors',ifail)

      Write (nout,*)
      Flush (nout)

      ifail = 0
      Call x04daf('General',' ',n,n,v,ldv,'Right singular vectors',ifail)

!      Call DDISNA (F08FLF) to estimate reciprocal condition
!      numbers for the singular vectors
      Call ddisna('Left',m,n,sva,rcondu,info)
      Call ddisna('Right',m,n,sva,rcondv,info)

!      Print the approximate error bounds for the singular values
!      and vectors
      Write (nout,'(/1X,A)') &
        'Error estimates (as multiples of machine precision):'
      Write (nout,'(/1X,A)') ' for the singular values'
      Write (nout,99998) nint(serrbd/x02ajf())
      Write (nout,'(/1X,A)') ' for left singular vectors'
      Write (nout,99998)(nint(serrbd/rcondu(i)/x02ajf()),i=1,n)
      Write (nout,'(/1X,A)') ' for right singular vectors'
      Write (nout,99998)(nint(serrbd/rcondv(i)/x02ajf()),i=1,n)
    Else
      Write (nout,99997) 'Failure in ZGESVJ. INFO =', info
    End If

99999 Format (3X,(8F8.4))
99998 Format (4X,6I4)
99997 Format (1X,A,I4)
99996 Format (/ ,1X,A,1P,E13.5)
      End Program f08kwfe

```

10.2 Program Data

F08KWF Example Program Data

```

  6  4
( 0.96,-0.81) (-0.03, 0.96) (-0.91, 2.06) (-0.05, 0.41) : m and n
(-0.98, 1.98) (-1.20, 0.19) (-0.66, 0.42) (-0.81, 0.56)
( 0.62,-0.46) ( 1.01, 0.02) ( 0.63,-0.17) (-1.11, 0.60)
(-0.37, 0.38) ( 0.19,-0.54) (-0.98,-0.36) ( 0.22,-0.20)
( 0.83, 0.51) ( 0.20, 0.01) (-0.17,-0.46) ( 1.47, 1.59)
( 1.08,-0.28) ( 0.20,-0.12) (-0.07, 1.23) ( 0.26, 0.26) : matrix A

```

10.3 Program Results

F08KWF Example Program Results

Singular values

```
3.9994 3.0003 1.9944 0.9995
```

Left singular vectors

```

      1      2      3      4
1  0.5632 -0.1814 -0.4517 -0.0171
   0.0151 -0.3390  0.2700  0.4820

2 -0.1386 -0.3097  0.1991  0.0245
   0.6070  0.0231  0.4227 -0.0405

```

```

3   0.0864 -0.2677 -0.4069  0.1363
    -0.1588  0.3268 -0.4452 -0.1991

```

```

4   -0.1486  0.2390 -0.1554  0.5883
     0.1489 -0.1115  0.0051 -0.1077

```

```

5    0.2459  0.5084  0.0337  0.0479
     0.1000  0.4916  0.2629  0.0891

```

```

6    0.3780 -0.0068 -0.1676  0.0806
    -0.0681 -0.0870  0.1359 -0.5766

```

Right singular vectors

```

           1           2           3           4
1   0.6968  0.2307 -0.0278 -0.2602
     0.0207  0.0670 -0.5116 -0.3552

```

```

2    0.0972  0.0045 -0.1897  0.8260
    -0.3520  0.2446 -0.2932  0.0511

```

```

3   -0.0399 -0.3854  0.5192 -0.2068
    -0.5414  0.4391  0.0397 -0.2237

```

```

4    0.1944  0.7355  0.4098  0.1193
    -0.2196 -0.0131  0.4201  0.1192

```

Error estimates (as multiples of machine precision):

for the singular values
4

for left singular vectors
4 4 4 4

for right singular vectors
4 4 4 4
