

NAG Library Routine Document

G05SEF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

G05SEF generates a vector of pseudorandom numbers taken from a Dirichlet distribution.

2 Specification

```
SUBROUTINE G05SEF (N, M, A, STATE, X, LDX, IFAIL)
  INTEGER          N, M, STATE(*), LDX, IFAIL
  REAL (KIND=nag_wp) A(M), X(LDX,M)
```

3 Description

The distribution has PDF (probability density function)

$$f(x) = \frac{1}{B(\alpha)} \prod_{i=1}^m x_i^{\alpha_i-1} \quad \text{and}$$

$$B(\alpha) = \frac{\prod_{i=1}^m \Gamma(\alpha_i)}{\Gamma\left(\sum_{i=1}^m \alpha_i\right)}$$

where $x = \{x_1, x_2, \dots, x_m\}$ is a vector of dimension m , such that $x_i > 0$ for all i and $\sum_{i=1}^m x_i = 1$.

G05SEF generates a draw from a Dirichlet distribution by first drawing m independent samples, $y_i \sim \text{gamma}(\alpha_i, 1)$, i.e., independent draws from a gamma distribution with parameters $\alpha_i > 0$ and one, and then setting $x_i = y_i / \sum_{j=1}^m y_j$.

One of the initialization routines G05KFF (for a repeatable sequence if computed sequentially) or G05KGF (for a non-repeatable sequence) must be called prior to the first call to G05SEF.

4 References

Dagpunar J (1988) *Principles of Random Variate Generation* Oxford University Press

Hastings N A J and Peacock J B (1975) *Statistical Distributions* Butterworth

5 Arguments

- | | | |
|----|--|--------------|
| 1: | N – INTEGER | <i>Input</i> |
| | <i>On entry:</i> n , the number of pseudorandom numbers to be generated. | |
| | <i>Constraint:</i> $N \geq 0$. | |
| 2: | M – INTEGER | <i>Input</i> |
| | <i>On entry:</i> m , the number of dimensions of the distribution. | |
| | <i>Constraint:</i> $M > 0$. | |

- 3: $A(M)$ – REAL (KIND=nag_wp) array *Input*
On entry: the parameter vector for the distribution.
Constraint: $A(i) > 0.0$, for $i = 1, 2, \dots, M$.
- 4: $STATE(*)$ – INTEGER array *Communication Array*
Note: the actual argument supplied **must** be the array STATE supplied to the initialization routines G05KFF or G05KGF.
On entry: contains information on the selected base generator and its current state.
On exit: contains updated information on the state of the generator.
- 5: $X(LDX, M)$ – REAL (KIND=nag_wp) array *Output*
On exit: the n pseudorandom numbers from the specified Dirichlet distribution, with $X(i, j)$ holding the j th dimension for the i th variate.
- 6: LDX – INTEGER *Input*
On entry: the first dimension of the array X as declared in the (sub)program from which G05SEF is called.
Constraint: $LDX \geq N$.
- 7: $IFAIL$ – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.
For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**
On exit: $IFAIL = 0$ unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry $IFAIL = 0$ or -1 , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

$IFAIL = 1$

On entry, $N = \langle value \rangle$.
Constraint: $N \geq 0$.

$IFAIL = 2$

On entry, $M = \langle value \rangle$.
Constraint: $M > 0$.

$IFAIL = 3$

On entry, at least one $A(i) \leq 0$.

$IFAIL = 4$

On entry, STATE vector has been corrupted or not initialized.

IFAIL = 6

On entry, LDX = $\langle value \rangle$ and N = $\langle value \rangle$.
Constraint: LDX \geq N.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

Not applicable.

8 Parallelism and Performance

G05SEF is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

None.

10 Example

This example prints a set of five pseudorandom numbers from a Dirichlet distribution with parameters $m = 4$ and $\alpha = \{2.0, 2.0, 2.0, 2.0\}$, generated by a single call to G05SEF, after initialization by G05KFF.

10.1 Program Text

```

Program g05sefe

!      G05SEF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
      Use nag_library, Only: g05kff, g05sef, nag_wp, x04caf
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: lseed = 1, nin = 5, nout = 6
!      .. Local Scalars ..
      Integer                     :: genid, ifail, ldx, lstate, m, n,      &
                                   subsid

!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: a(:), x(:, :)

```

```

Integer                                :: seed(lseed)
Integer, Allocatable                   :: state(:)
! .. Executable Statements ..
Write (nout,*) 'G05SEF Example Program Results'
Write (nout,*)
Flush (nout)

! Skip heading in data file
Read (nin,*)

! Read in the base generator information and seed
Read (nin,*) genid, subid, seed(1)

! Initial call to initializer to get size of STATE array
lstate = 0
Allocate (state(lstate))
ifail = 0
Call g05kff(genid,subid,seed,lseed,state,lstate,ifail)

! Reallocate STATE
Deallocate (state)
Allocate (state(lstate))

! Initialize the generator to a repeatable sequence
ifail = 0
Call g05kff(genid,subid,seed,lseed,state,lstate,ifail)

! Read in sample size and number of dimensions
Read (nin,*) n, m

ldx = n
Allocate (x(ldx,m),a(m))

! Read in the distribution parameters
Read (nin,*) a(1:m)

! Generate the variates
ifail = 0
Call g05sef(n,m,a,state,x,ldx,ifail)

! Display the variates
ifail = 0
Call x04caf('General',' ',n,m,x,ldx,' ',ifail)

End Program g05sefe

```

10.2 Program Data

G05SEF Example Program Data

```

1 1 1762543      :: GENID,SUBID,SEED(1)
5 4              :: N,M
2.0 2.0 2.0 2.0  :: A

```

10.3 Program Results

G05SEF Example Program Results

	1	2	3	4
1	0.3600	0.3138	0.0837	0.2426
2	0.2874	0.5121	0.1497	0.0509
3	0.2286	0.2190	0.3959	0.1566
4	0.1744	0.3961	0.2764	0.1530
5	0.1522	0.2845	0.2074	0.3559
