

NAG Library Routine Document

G08CLF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

G08CLF calculates the Anderson–Darling goodness-of-fit test statistic and its probability for the case of an unspecified exponential distribution.

2 Specification

```
SUBROUTINE G08CLF (N, ISSORT, Y, YBAR, A2, AA2, P, IFAIL)
  INTEGER          N, IFAIL
  REAL (KIND=nag_wp) Y(N), YBAR, A2, AA2, P
  LOGICAL          ISSORT
```

3 Description

Calculates the Anderson–Darling test statistic A^2 (see G08CHF) and its upper tail probability for the small sample correction:

$$\text{Adjusted } A^2 = A^2(1 + 0.6/n),$$

for n observations.

4 References

Anderson T W and Darling D A (1952) Asymptotic theory of certain ‘goodness-of-fit’ criteria based on stochastic processes *Annals of Mathematical Statistics* **23** 193–212

Stephens M A and D'Agostino R B (1986) *Goodness-of-Fit Techniques* Marcel Dekker, New York

5 Arguments

- 1: N – INTEGER *Input*
On entry: n , the number of observations.
Constraint: $N > 1$.
- 2: ISSORT – LOGICAL *Input*
On entry: set ISSORT = .TRUE. if the observations are sorted in ascending order; otherwise the routine will sort the observations.
- 3: Y(N) – REAL (KIND=nag_wp) array *Input*
On entry: y_i , for $i = 1, 2, \dots, n$, the n observations.
Constraint: if ISSORT = .TRUE., values must be sorted in ascending order. Each y_i must be greater than zero.
- 4: YBAR – REAL (KIND=nag_wp) *Output*
On exit: the maximum likelihood estimate of mean.

- 5: A2 – REAL (KIND=nag_wp) Output
On exit: A^2 , the Anderson–Darling test statistic.
- 6: AA2 – REAL (KIND=nag_wp) Output
On exit: the adjusted A^2 .
- 7: P – REAL (KIND=nag_wp) Output
On exit: p , the upper tail probability for the adjusted A^2 .
- 8: IFAIL – INTEGER Input/Output
On entry: IFAIL must be set to 0, –1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.
 For environments where it might be inappropriate to halt program execution when an error is detected, the value –1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. **When the value –1 or 1 is used it is essential to test the value of IFAIL on exit.**
On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or –1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, $N = \langle value \rangle$.
 Constraint: $N > 1$.

IFAIL = 3

ISSORT = .TRUE. and the data in Y is not sorted in ascending order.

IFAIL = 9

The data in Y must be greater than zero.

IFAIL = –99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = –399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = –999

Dynamic memory allocation failed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

Probabilities are calculated using piecewise polynomial approximations to values estimated by simulation.

8 Parallelism and Performance

G08CLF is not threaded in any implementation.

9 Further Comments

None.

10 Example

This example calculates the A^2 statistics for data assumed to arise from an unspecified exponential distribution and calculates the p -value.

10.1 Program Text

```

Program g08clfe

!      G08CLF Example Program Text
!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
!      Use nag_library, Only: g08clf, nag_wp
!      .. Implicit None Statement ..
!      Implicit None
!      .. Parameters ..
!      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
!      Real (Kind=nag_wp)          :: a2, aa2, p, ybar
!      Integer                     :: i, ifail, n
!      Logical                     :: issort
!      .. Local Arrays ..
!      Real (Kind=nag_wp), Allocatable :: y(:)
!      .. Executable Statements ..
!      Write (nout,*) 'G08CLF Example Program Results'
!      Write (nout,*)

!      Skip heading in data file
!      Read (nin,*)

!      Read number of observations
!      Read (nin,*) n

!      Memory allocation
!      Allocate (y(n))

!      Read observations
!      Read (nin,*)(y(i),i=1,n)

!      Let g08clf sort the data
!      issort = .False.

!      Calculate A-squared and probability
!      ifail = 0
!      Call g08clf(n,issort,y,ybar,a2,aa2,p,ifail)

!      Results
!      Write (nout, '(1X,A,E11.4)')
!      'H0: data from exponential distribution with mean', ybar
&

```

```
Write (nout,'(1X,A,1X,F8.4)') 'Test statistic, A-squared: ', a2
Write (nout,'(1X,A,1X,F8.4)') 'Adjusted A-squared: ', aa2
Write (nout,'(1X,A,1X,F8.4)') 'Upper tail probability: ', p

End Program g08clfe
```

10.2 Program Data

G08CLF Example Program Data

```
26 :: n
0.4782745 1.2858962 1.1163891 2.0410619 2.2648109 0.0833660 1.2527554
0.4031288 0.7808981 0.1977674 3.2539440 1.8113504 1.2279834 3.9178773
1.4494309 0.1358438 1.8061778 6.0441929 0.9671624 3.2035042 0.8067364
0.4179364 3.5351774 0.3975414 0.6120960 0.1332589 :: end of observations
```

10.3 Program Results

G08CLF Example Program Results

```
H0: data from exponential distribution with mean 0.1524E+01
Test statistic, A-squared:    0.1616
Adjusted A-squared:         0.1654
Upper tail probability:      0.9831
```
