

# NAG Library Routine Document

## S30JBF

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

### 1 Purpose

S30JBF computes the European option price together with its sensitivities (Greeks) using the Merton jump-diffusion model.

### 2 Specification

```

SUBROUTINE S30JBF (CALPUT, M, N, X, S, T, SIGMA, R, LAMBDA, JVOL, P,      &
                  LDP, DELTA, GAMMA, VEGA, THETA, RHO, VANNA, CHARM,      &
                  SPEED, COLOUR, ZOMMA, VOMMA, IFAIL)
INTEGER          M, N, LDP, IFAIL
REAL (KIND=nag_wp) X(M), S, T(N), SIGMA, R, LAMBDA, JVOL, P(LDP,N),      &
                  DELTA(LDP,N), GAMMA(LDP,N), VEGA(LDP,N),              &
                  THETA(LDP,N), RHO(LDP,N), VANNA(LDP,N),                &
                  CHARM(LDP,N), SPEED(LDP,N), COLOUR(LDP,N),             &
                  ZOMMA(LDP,N), VOMMA(LDP,N)
CHARACTER(1)     CALPUT

```

### 3 Description

S30JBF uses Merton's jump-diffusion model (Merton (1976)) to compute the price of a European option, together with the Greeks or sensitivities, which are the partial derivatives of the option price with respect to certain of the other input parameters. Merton's model assumes that the asset price is described by a Brownian motion with drift, as in the Black–Scholes–Merton case, together with a compound Poisson process to model the jumps. The corresponding stochastic differential equation is,

$$\frac{dS}{S} = (\alpha - \lambda k)dt + \hat{\sigma}dW_t + dq_t.$$

Here  $\alpha$  is the instantaneous expected return on the asset price,  $S$ ;  $\hat{\sigma}^2$  is the instantaneous variance of the return when the Poisson event does not occur;  $dW_t$  is a standard Brownian motion;  $q_t$  is the independent Poisson process and  $k = E[Y - 1]$  where  $Y - 1$  is the random variable change in the stock price if the Poisson event occurs and  $E$  is the expectation operator over the random variable  $Y$ .

This leads to the following price for a European option (see Haug (2007))

$$P_{\text{call}} = \sum_{j=0}^{\infty} \frac{e^{-\lambda T} (\lambda T)^j}{j!} C_j(S, X, T, r, \sigma'_j),$$

where  $T$  is the time to expiry;  $X$  is the strike price;  $r$  is the annual risk-free interest rate;  $C_j(S, X, T, r, \sigma'_j)$  is the Black–Scholes–Merton option pricing formula for a European call (see S30AAF).

$$\sigma'_j = \sqrt{z^2 + \delta^2 \left(\frac{j}{T}\right)},$$

$$z^2 = \sigma^2 - \lambda \delta^2,$$

$$\delta^2 = \frac{\gamma \sigma^2}{\lambda},$$

where  $\sigma$  is the total volatility including jumps;  $\lambda$  is the expected number of jumps given as an average per year;  $\gamma$  is the proportion of the total volatility due to jumps.

The value of a put is obtained by substituting the Black–Scholes–Merton put price for  $C_j(S, X, T, r, \sigma'_j)$ .

The option price  $P_{ij} = P(X = X_i, T = T_j)$  is computed for each strike price in a set  $X_i$ ,  $i = 1, 2, \dots, m$ , and for each expiry time in a set  $T_j$ ,  $j = 1, 2, \dots, n$ .

## 4 References

Haug E G (2007) *The Complete Guide to Option Pricing Formulas* (2nd Edition) McGraw-Hill

Merton R C (1976) Option pricing when underlying stock returns are discontinuous *Journal of Financial Economics* **3** 125–144

## 5 Arguments

- 1: CALPUT – CHARACTER(1) *Input*  
*On entry:* determines whether the option is a call or a put.  
CALPUT = 'C'  
A call; the holder has a right to buy.  
CALPUT = 'P'  
A put; the holder has a right to sell.  
*Constraint:* CALPUT = 'C' or 'P'.
- 2: M – INTEGER *Input*  
*On entry:* the number of strike prices to be used.  
*Constraint:*  $M \geq 1$ .
- 3: N – INTEGER *Input*  
*On entry:* the number of times to expiry to be used.  
*Constraint:*  $N \geq 1$ .
- 4: X(M) – REAL (KIND=nag\_wp) array *Input*  
*On entry:* X( $i$ ) must contain  $X_i$ , the  $i$ th strike price, for  $i = 1, 2, \dots, M$ .  
*Constraint:*  $X(i) \geq z$  and  $X(i) \leq 1/z$ , where  $z = \text{X02AMF}()$ , the safe range parameter, for  $i = 1, 2, \dots, M$ .
- 5: S – REAL (KIND=nag\_wp) *Input*  
*On entry:*  $S$ , the price of the underlying asset.  
*Constraint:*  $S \geq z$  and  $S \leq 1.0/z$ , where  $z = \text{X02AMF}()$ , the safe range parameter.
- 6: T(N) – REAL (KIND=nag\_wp) array *Input*  
*On entry:* T( $i$ ) must contain  $T_i$ , the  $i$ th time, in years, to expiry, for  $i = 1, 2, \dots, N$ .  
*Constraint:*  $T(i) \geq z$ , where  $z = \text{X02AMF}()$ , the safe range parameter, for  $i = 1, 2, \dots, N$ .
- 7: SIGMA – REAL (KIND=nag\_wp) *Input*  
*On entry:*  $\sigma$ , the annual total volatility, including jumps.  
*Constraint:* SIGMA > 0.0.

- 8: R – REAL (KIND=nag\_wp) Input  
*On entry:*  $r$ , the annual risk-free interest rate, continuously compounded. Note that a rate of 5% should be entered as 0.05.  
*Constraint:*  $R \geq 0.0$ .
- 9: LAMBDA – REAL (KIND=nag\_wp) Input  
*On entry:*  $\lambda$ , the number of expected jumps per year.  
*Constraint:*  $LAMBDA > 0.0$ .
- 10: JVOL – REAL (KIND=nag\_wp) Input  
*On entry:* the proportion of the total volatility associated with jumps.  
*Constraint:*  $0.0 \leq JVOL < 1.0$ .
- 11: P(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:*  $P(i,j)$  contains  $P_{ij}$ , the option price evaluated for the strike price  $X_i$  at expiry  $T_j$  for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .
- 12: LDP – INTEGER Input  
*On entry:* the first dimension of the arrays P, DELTA, GAMMA, VEGA, THETA, RHO, VANNA, CHARM, SPEED, COLOUR, ZOMMA and VOMMA as declared in the (sub)program from which S30JBF is called.  
*Constraint:*  $LDP \geq M$ .
- 13: DELTA(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:* the leading  $M \times N$  part of the array DELTA contains the sensitivity,  $\frac{\partial P}{\partial S}$ , of the option price to change in the price of the underlying asset.
- 14: GAMMA(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:* the leading  $M \times N$  part of the array GAMMA contains the sensitivity,  $\frac{\partial^2 P}{\partial S^2}$ , of DELTA to change in the price of the underlying asset.
- 15: VEGA(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:*  $VEGA(i,j)$ , contains the first-order Greek measuring the sensitivity of the option price  $P_{ij}$  to change in the volatility of the underlying asset, i.e.,  $\frac{\partial P_{ij}}{\partial \sigma}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .
- 16: THETA(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:*  $THETA(i,j)$ , contains the first-order Greek measuring the sensitivity of the option price  $P_{ij}$  to change in time, i.e.,  $-\frac{\partial P_{ij}}{\partial T}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ , where  $b = r - q$ .
- 17: RHO(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:*  $RHO(i,j)$ , contains the first-order Greek measuring the sensitivity of the option price  $P_{ij}$  to change in the annual risk-free interest rate, i.e.,  $-\frac{\partial P_{ij}}{\partial r}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .
- 18: VANNA(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:*  $VANNA(i,j)$ , contains the second-order Greek measuring the sensitivity of the first-order Greek  $\Delta_{ij}$  to change in the volatility of the asset price, i.e.,  $-\frac{\partial \Delta_{ij}}{\partial T} = -\frac{\partial^2 P_{ij}}{\partial S \partial \sigma}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .

- 19: CHARM(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:* CHARM( $i,j$ ), contains the second-order Greek measuring the sensitivity of the first-order Greek  $\Delta_{ij}$  to change in the time, i.e.,  $-\frac{\partial \Delta_{ij}}{\partial T} = -\frac{\partial^2 P_{ij}}{\partial S \partial T}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .
- 20: SPEED(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:* SPEED( $i,j$ ), contains the third-order Greek measuring the sensitivity of the second-order Greek  $\Gamma_{ij}$  to change in the price of the underlying asset, i.e.,  $-\frac{\partial \Gamma_{ij}}{\partial S} = -\frac{\partial^3 P_{ij}}{\partial S^3}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .
- 21: COLOUR(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:* COLOUR( $i,j$ ), contains the third-order Greek measuring the sensitivity of the second-order Greek  $\Gamma_{ij}$  to change in the time, i.e.,  $-\frac{\partial \Gamma_{ij}}{\partial T} = -\frac{\partial^3 P_{ij}}{\partial S^2 \partial T}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .
- 22: ZOMMA(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:* ZOMMA( $i,j$ ), contains the third-order Greek measuring the sensitivity of the second-order Greek  $\Gamma_{ij}$  to change in the volatility of the underlying asset, i.e.,  $-\frac{\partial \Gamma_{ij}}{\partial \sigma} = -\frac{\partial^3 P_{ij}}{\partial S^2 \partial \sigma}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .
- 23: VOMMA(LDP,N) – REAL (KIND=nag\_wp) array Output  
*On exit:* VOMMA( $i,j$ ), contains the second-order Greek measuring the sensitivity of the first-order Greek  $\Delta_{ij}$  to change in the volatility of the underlying asset, i.e.,  $-\frac{\partial \Delta_{ij}}{\partial \sigma} = -\frac{\partial^2 P_{ij}}{\partial \sigma^2}$ , for  $i = 1, 2, \dots, M$  and  $j = 1, 2, \dots, N$ .
- 24: IFAIL – INTEGER Input/Output  
*On entry:* IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.  
 For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**  
*On exit:* IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

## 6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, CALPUT =  $\langle value \rangle$  was an illegal value.

IFAIL = 2

On entry, M =  $\langle value \rangle$ .

Constraint:  $M \geq 1$ .

IFAIL = 3

On entry,  $N = \langle value \rangle$ .  
Constraint:  $N \geq 1$ .

IFAIL = 4

On entry,  $X(\langle value \rangle) = \langle value \rangle$ .  
Constraint:  $X(i) \geq \langle value \rangle$  and  $X(i) \leq \langle value \rangle$ .

IFAIL = 5

On entry,  $S = \langle value \rangle$ .  
Constraint:  $S \geq \langle value \rangle$  and  $S \leq \langle value \rangle$ .

IFAIL = 6

On entry,  $T(\langle value \rangle) = \langle value \rangle$ .  
Constraint:  $T(i) \geq \langle value \rangle$ .

IFAIL = 7

On entry,  $SIGMA = \langle value \rangle$ .  
Constraint:  $SIGMA > 0.0$ .

IFAIL = 8

On entry,  $R = \langle value \rangle$ .  
Constraint:  $R \geq 0.0$ .

IFAIL = 9

On entry,  $LAMBDA = \langle value \rangle$ .  
Constraint:  $LAMBDA > 0.0$ .

IFAIL = 10

On entry,  $JVOL = \langle value \rangle$ .  
Constraint:  $JVOL \geq 0.0$  and  $JVOL < 1.0$ .

IFAIL = 12

On entry,  $LDP = \langle value \rangle$  and  $M = \langle value \rangle$ .  
Constraint:  $LDP \geq M$ .

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.  
See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.  
See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.  
See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

## 7 Accuracy

The accuracy of the output is dependent on the accuracy of the cumulative Normal distribution function,  $\Phi$ , occurring in  $C_j$ . This is evaluated using a rational Chebyshev expansion, chosen so that the maximum relative error in the expansion is of the order of the *machine precision* (see S15ABF and S15ADF). An accuracy close to *machine precision* can generally be expected.

## 8 Parallelism and Performance

S30JBF is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

## 9 Further Comments

None.

## 10 Example

This example computes the price of two European calls with jumps. The time to expiry is 6 months, the stock price is 100 and strike prices are 80 and 90 respectively. The number of jumps per year is 5 and the percentage of the total volatility due to jumps is 25%. The risk-free interest rate is 8% per year while the total volatility is 25% per year.

### 10.1 Program Text

```

Program s30jbfe

!      S30JBF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
      Use nag_library, Only: nag_wp, s30jbfe
!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Real (Kind=nag_wp)          :: jvol, lambda, r, s, sigma
      Integer                     :: i, ifail, j, ldp, m, n
      Character (1)               :: calput
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: charm(:, :), colour(:, :), crho(:, :), &
                                         delta(:, :), gamma(:, :), p(:, :), &
                                         rho(:, :), speed(:, :), t(:, :), &
                                         theta(:, :), vanna(:, :), vega(:, :), &
                                         vomma(:, :), x(:, :), zomma(:, :)
!      .. Executable Statements ..
      Write (nout,*) 'S30JBF Example Program Results'

!      Skip heading in data file
      Read (nin,*)

      Read (nin,*) calput
      Read (nin,*) lambda
      Read (nin,*) s, sigma, r, jvol
      Read (nin,*) m, n

      ldp = m
      Allocate (charm(ldp,n),colour(ldp,n),crho(ldp,n),delta(ldp,n), &
                gamma(ldp,n),p(ldp,n),rho(ldp,n),speed(ldp,n),t(n),theta(ldp,n), &

```

```

      vanna(ldp,n),vega(ldp,n),vomma(ldp,n),x(m),zomma(ldp,n))

Read  (nin,*)(x(i),i=1,m)
Read  (nin,*)(t(i),i=1,n)

ifail = 0

Call  s30jbf(calput,m,n,x,s,t,sigma,r,lambda,jvol,p,ldp,delta,gamma,vega, &
      theta,rho,vanna,charm,speed,colour,zomma,vomma,ifail)

Write (nout,*)
Write (nout,*) 'Merton Jump-Diffusion Model'

Select Case (calput)
Case ('C','c')
  Write (nout,*) 'European Call :'
Case ('P','p')
  Write (nout,*) 'European Put :'
End Select

Write (nout,99996) ' Spot      = ', s
Write (nout,99996) ' Volatility = ', sigma
Write (nout,99996) ' Rate      = ', r
Write (nout,99996) ' Jumps     = ', lambda
Write (nout,99996) ' Jump vol  = ', jvol

Write (nout,*)

Do j = 1, n
  Write (nout,*)
  Write (nout,99999) t(j)
  Write (nout,*) ' Strike      Price      Delta      Gamma      Vega      Theta' &
    // '          Rho'

  Do i = 1, m
    Write (nout,99998) x(i), p(i,j), delta(i,j), gamma(i,j), vega(i,j), &
      theta(i,j), rho(i,j)
  End Do

  Write (nout,*)
  ' Strike      Price      Vanna      Charm      Speed      Colour      Zomma' // &
  ' Vomma'

  Do i = 1, m
    Write (nout,99997) x(i), p(i,j), vanna(i,j), charm(i,j), speed(i,j), &
      colour(i,j), zomma(i,j), vomma(i,j)
  End Do

End Do

99999 Format (1X,'Time to Expiry : ',1X,F8.4)
99998 Format (1X,7(F8.4,1X))
99997 Format (1X,8(F8.4,1X))
99996 Format (A,1X,F8.4)
End Program s30jbfe

```

## 10.2 Program Data

```

S30JBF Example Program Data
'C'      : Call = 'C', Put = 'P'
5.0      : LAMBDA (jumps)
100.0 0.25 0.08 0.25 : S, SIGMA, R, JVOL
2 1      : M, N
80.0
90.0     : X(I), I = 1,2,...M
0.5      : T(I), I = 1,2,...N

```

### 10.3 Program Results

S30JBF Example Program Results

Merton Jump-Diffusion Model

European Call :

Spot = 100.0000  
 Volatility = 0.2500  
 Rate = 0.0800  
 Jumps = 5.0000  
 Jump vol = 0.2500

Time to Expiry : 0.5000

Strike	Price	Delta	Gamma	Vega	Theta	Rho	
80.0000	23.6090	0.9431	0.0064	8.1206	-7.6718	35.3480	
90.0000	15.4193	0.8203	0.0149	18.5256	-9.9695	33.3037	
Strike	Price	Vanna	Charm	Speed	Colour	Zomma	Vomma
80.0000	23.6090	-0.6334	0.1080	-0.0006	-0.0035	0.0315	70.6824
90.0000	15.4193	-0.7726	0.0770	-0.0009	0.0109	-0.0186	49.7161

---