

NAG Library Routine Document

S30SAF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of ***bold italicised*** terms and other implementation-dependent details.

1 Purpose

S30SAF computes the Asian geometric continuous average-rate option price.

2 Specification

```
SUBROUTINE S30SAF (CALPUT, M, N, X, S, T, SIGMA, R, B, P, LDP, IFAIL)
INTEGER                M, N, LDP, IFAIL
REAL (KIND=nag_wp)    X(M), S, T(N), SIGMA, R, B, P(LDP,N)
CHARACTER(1)          CALPUT
```

3 Description

S30SAF computes the price of an Asian geometric continuous average-rate option for constant volatility, σ , risk-free rate, r , and cost of carry, b (see Kemna and Vorst (1990)). For a given strike price, X , the price of a call option with underlying price, S , and time to expiry, T , is

$$P_{\text{call}} = Se^{(\bar{b}-r)T}\Phi(\bar{d}_1) - Xe^{-rT}\Phi(\bar{d}_2),$$

and the corresponding put option price is

$$P_{\text{put}} = Xe^{-rT}\Phi(-\bar{d}_2) - Se^{(\bar{b}-r)T}\Phi(-\bar{d}_1),$$

where

$$\bar{d}_1 = \frac{\ln(S/X) + (\bar{b} + \sigma^2/2)T}{\sigma\sqrt{T}}$$

and

$$\bar{d}_2 = \bar{d}_1 - \sigma\sqrt{T},$$

with

$$\bar{\sigma} = \frac{\sigma}{\sqrt{3}}, \quad \bar{b} = \frac{1}{2}\left(r - \frac{\sigma^2}{6}\right).$$

Φ is the cumulative Normal distribution function,

$$\Phi(x) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^x \exp(-y^2/2) dy.$$

The option price $P_{ij} = P(X = X_i, T = T_j)$ is computed for each strike price in a set X_i , $i = 1, 2, \dots, m$, and for each expiry time in a set T_j , $j = 1, 2, \dots, n$.

4 References

Kemna A and Vorst A (1990) A pricing method for options based on average asset values *Journal of Banking and Finance* **14** 113–129

5 Arguments

- 1: CALPUT – CHARACTER(1) *Input*
On entry: determines whether the option is a call or a put.
CALPUT = 'C'
A call; the holder has a right to buy.
CALPUT = 'P'
A put; the holder has a right to sell.
Constraint: CALPUT = 'C' or 'P'.
- 2: M – INTEGER *Input*
On entry: the number of strike prices to be used.
Constraint: $M \geq 1$.
- 3: N – INTEGER *Input*
On entry: the number of times to expiry to be used.
Constraint: $N \geq 1$.
- 4: X(M) – REAL (KIND=nag_wp) array *Input*
On entry: X(*i*) must contain X_i , the *i*th strike price, for $i = 1, 2, \dots, M$.
Constraint: $X(i) \geq z$ and $X(i) \leq 1/z$, where $z = \text{X02AMF}()$, the safe range parameter, for $i = 1, 2, \dots, M$.
- 5: S – REAL (KIND=nag_wp) *Input*
On entry: S , the price of the underlying asset.
Constraint: $S \geq z$ and $S \leq 1.0/z$, where $z = \text{X02AMF}()$, the safe range parameter.
- 6: T(N) – REAL (KIND=nag_wp) array *Input*
On entry: T(*i*) must contain T_i , the *i*th time, in years, to expiry, for $i = 1, 2, \dots, N$.
Constraint: $T(i) \geq z$, where $z = \text{X02AMF}()$, the safe range parameter, for $i = 1, 2, \dots, N$.
- 7: SIGMA – REAL (KIND=nag_wp) *Input*
On entry: σ , the volatility of the underlying asset. Note that a rate of 15% should be entered as 0.15.
Constraint: SIGMA > 0.0.
- 8: R – REAL (KIND=nag_wp) *Input*
On entry: r , the annual risk-free interest rate, continuously compounded. Note that a rate of 5% should be entered as 0.05.
Constraint: $R \geq 0.0$.
- 9: B – REAL (KIND=nag_wp) *Input*
On entry: b , the annual cost of carry rate. Note that a rate of 8% should be entered as 0.08.
- 10: P(LDP, N) – REAL (KIND=nag_wp) array *Output*
On exit: P(*i*, *j*) contains P_{ij} , the option price evaluated for the strike price X_i at expiry T_j for $i = 1, 2, \dots, M$ and $j = 1, 2, \dots, N$.

- 11: LDP – INTEGER *Input*
On entry: the first dimension of the array P as declared in the (sub)program from which S30SAF is called.
Constraint: $LDP \geq M$.
- 12: IFAIL – INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this argument you should refer to Section 3.4 in How to Use the NAG Library and its Documentation for details.
 For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this argument, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**
On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL = 1

On entry, CALPUT = $\langle value \rangle$ was an illegal value.

IFAIL = 2

On entry, M = $\langle value \rangle$.

Constraint: $M \geq 1$.

IFAIL = 3

On entry, N = $\langle value \rangle$.

Constraint: $N \geq 1$.

IFAIL = 4

On entry, $X(\langle value \rangle) = \langle value \rangle$.

Constraint: $X(i) \geq \langle value \rangle$ and $X(i) \leq \langle value \rangle$.

IFAIL = 5

On entry, S = $\langle value \rangle$.

Constraint: $S \geq \langle value \rangle$ and $S \leq \langle value \rangle$.

IFAIL = 6

On entry, $T(\langle value \rangle) = \langle value \rangle$.

Constraint: $T(i) \geq \langle value \rangle$.

IFAIL = 7

On entry, SIGMA = $\langle value \rangle$.

Constraint: SIGMA > 0.0.

IFAIL = 8

On entry, $R = \langle value \rangle$.
Constraint: $R \geq 0.0$.

IFAIL = 11

On entry, $LDP = \langle value \rangle$ and $M = \langle value \rangle$.
Constraint: $LDP \geq M$.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.9 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.8 in How to Use the NAG Library and its Documentation for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.7 in How to Use the NAG Library and its Documentation for further information.

7 Accuracy

The accuracy of the output is dependent on the accuracy of the cumulative Normal distribution function, Φ . This is evaluated using a rational Chebyshev expansion, chosen so that the maximum relative error in the expansion is of the order of the *machine precision* (see S15ABF and S15ADF). An accuracy close to *machine precision* can generally be expected.

8 Parallelism and Performance

S30SAF is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

None.

10 Example

This example computes the price of an Asian geometric continuous average-rate put with a time to expiry of 3 months, a stock price of 80 and a strike price of 85. The risk-free interest rate is 5% per year, the cost of carry is 8% and the volatility is 20% per year.

10.1 Program Text

```
Program s30safe

!      S30SAF Example Program Text

!      Mark 26 Release. NAG Copyright 2016.

!      .. Use Statements ..
!      Use nag_library, Only: nag_wp, s30saf
```

```

!      .. Implicit None Statement ..
      Implicit None
!      .. Parameters ..
      Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
      Real (Kind=nag_wp)          :: b, r, s, sigma
      Integer                     :: i, ifail, j, ldp, m, n
      Character (1)                :: calput
!      .. Local Arrays ..
      Real (Kind=nag_wp), Allocatable :: p(:,,:), t(:,), x(:,)
!      .. Executable Statements ..
      Write (nout,*) 'S30SAF Example Program Results'

!      Skip heading in data file
      Read (nin,*)

      Read (nin,*) calput
      Read (nin,*) s, sigma, r, b
      Read (nin,*) m, n

      ldp = m
      Allocate (p(ldp,n),t(n),x(m))

      Read (nin,*)(x(i),i=1,m)
      Read (nin,*)(t(i),i=1,n)

      ifail = 0
      Call s30saf(calput,m,n,x,s,t,sigma,r,b,p,ldp,ifail)

      Write (nout,*)
      Write (nout,*) 'Asian Option: Geometric Continuous Average-Rate'

      Select Case (calput)
      Case ('C','c')
        Write (nout,*) 'Asian Call :'
      Case ('P','p')
        Write (nout,*) 'Asian Put :'
      End Select

      Write (nout,99998) ' Spot           = ', s
      Write (nout,99998) ' Volatility     = ', sigma
      Write (nout,99998) ' Rate           = ', r
      Write (nout,99998) ' Cost of carry = ', b

      Write (nout,*)
      Write (nout,*) ' Strike      Expiry      Option Price'

      Do i = 1, m

        Do j = 1, n
          Write (nout,99999) x(i), t(j), p(i,j)
        End Do

      End Do

99999 Format (1X,2(F9.4,1X),6X,F9.4)
99998 Format (A,1X,F8.4)
      End Program s30safe

```

10.2 Program Data

```

S30SAF Example Program Data
'P'           : Call = 'C', Put = 'P'
80.0 0.2 0.05 0.08 : S, SIGMA, R, B
1 1           : M, N
85.0          : X(I), I = 1,2,...M
0.25          : T(I), I = 1,2,...N

```

10.3 Program Results

S30SAF Example Program Results

Asian Option: Geometric Continuous Average-Rate

Asian Put :

Spot = 80.0000

Volatility = 0.2000

Rate = 0.0500

Cost of carry = 0.0800

Strike	Expiry	Option Price
85.0000	0.2500	4.6922
